

Content index

Request and Response	11
Request types.....	12
Xmlrpc.....	12
Simple.....	12
Jsonrpc.....	12
Response types.....	12
Xmlrpc.....	13
Simple.....	13
Jsonrpc.....	13
Json.....	13
Test.....	13
Debug.....	13
Xml.....	14
Errors	15
Error codes.....	16
SUCCESS (code: 1000).....	16
SUCCESS_PENDING (code: 1001).....	16
UNKNOWN_COMMAND (code: 2000).....	16
COMMAND_SYNTAX_ERROR (code: 2001).....	16
COMMAND_USE_ERROR (code: 2002).....	16
PARAM_MISSING (code: 2003).....	16
PARAM_VALUE_RANGE (code: 2004).....	16
PARAM_VALUE_SYNTAX (code: 2005).....	16
DELETED_COMMAND (code: 2100).....	17
UNIMPLEMENTED_COMMAND (code: 2101).....	17
BILLING_FAILURE (code: 2104).....	17
BILLING_NOT_ALLOWED (code: 2105).....	17
AUTH_ERROR_USER (code: 2200).....	17
AUTH_ERROR_OBJECT (code: 2201).....	17
OBJECT_EXISTS (code: 2302).....	17
OBJECT_NOT_EXISTS (code: 2303).....	18
OBJECT_STATUS_PROHIBITS_OP (code: 2304).....	18
OBJECT_ASSOCIATION_PROHIBITS_OP (code: 2305).....	19
PARAMETER_VALUE_POLICY_ERROR (code: 2306).....	19
UNIMPLEMENTED_OBJECT_SERVICE (code: 2307).....	19
COMMAND_FAILED (code: 2400).....	20
COMMAND_FAILED_FATAL (code: 2500).....	20
COMMAND_TIMEOUT (code: 2501).....	20
COMMAND_CONNECTIONSLIMIT (code: 2502).....	20
COMMAND_MAINTENANCE_MODE (code: 2503).....	21
COMMAND_PENDING_PREVIOUS_EXECUTION (code: 3101).....	21
COMMAND_FTP_MAX_ACCOUNTS (code: 3601).....	21
COMMAND_EMAIL_REDIRECTION_MAX_ACCOUNTS (code: 3602).....	21
COMMAND_EMAIL_DISTRIBUTIONLIST_MAX (code: 3603).....	21
COMMAND_SERVER_KVM_GET_ERROR (code: 3604).....	21
COMMAND_DEDICATED_SERVER_OS_ERROR (code: 3605).....	21
COMMAND_LICENSE_MAX_HOSTINGS (code: 3606).....	21
COMMAND_BILLING_PRODUCT_ERROR (code: 3607).....	22
COMMAND_BILLING_CREDIT (code: 3608).....	22
COMMAND_EMAIL_MAX_HOSTINGS (code: 3609).....	22
COMMAND_DOMAIN_FORBIDDEN_CONTACT_UPDATE (code: 3610).....	22
COMMAND_DBBB_SQLSERVER_NOT_ENOUGH_SPACE (code: 3612).....	22
COMMAND_EMAIL_DISTRIBUTION_LIST_EXISTS (code: 3613).....	22
COMMAND_SMS_NOT_REMAINING_MESSAGES (code: 3614).....	23
COMMAND_MYSQL_MAX_DATABASES (code: 3615).....	23
COMMAND_DOMAIN_IP_NOT_RESOLVING_DNS (code: 3616).....	23
COMMAND_EMAIL_NOT_ENABLED (code: 3617).....	23
COMMAND_REGENERATE_PASSWORD_SEND_METHOD (code: 3618).....	23

COMMAND_EMAIL_ACCOUNT_SET_REPEATED_PASSWORD (code: 3619)	23
COMMAND_BILLING_DOMAIN_FORBIDDEN_PREDEFINED_CONTACTS (code: 3620)	23
COMMAND_DOMAIN_TRANSFER_ALREADY_APPROVED (code: 3630)	23
COMMAND_DOMAIN_CERT_ALREADY_ASSOCIATED (code: 3631)	23
COMMAND_BILLING_PRODUCT_TEMPORARILY_DISABLED (code: 3621)	24
COMMAND_NFS_VOLUME_DOES_NOT_EXIST (code: 3640)	24
COMMAND_PARAM_IS_NOT_A_VALID_CERTIFICATE (code: 3641)	24
Commands	25
AdditionalStorage commands	26
AdditionalStorage_Repository_GetAll	26
AdditionalStorage_Repository_Delete	26
AdditionalStorage_Repository_Create	26
AdditionalStorage_Repository_SetPassword	27
Billing commands	28
Billing_Renew_Domain	28
Billing_Renew_Hosting	28
Billing_Renew_Vps	28
Billing_Renew_Sms	29
Billing_Renew_Multihosting	29
Billing_Buy_Domain	29
Billing_Buy_Hosting	30
Billing_Buy_DomainUsingContactsIds	30
Billing_Buy_Vps_Unmanaged_Windows	31
Billing_Buy_Vps_Unmanaged_Linux	31
Billing_Buy_Vps_Managed_Windows	32
Billing_Buy_Vps_Managed_Linux	32
Billing_Buy_Sms	32
Billing_Buy_Multihosting	33
Billing_GetConfigurableVpsOptions	33
Billing_Price_Domain	33
Billing_Price_Hosting	34
Billing_Price_Vps_Unmanaged_Windows	34
Billing_Price_Vps_Unmanaged_Linux	35
Billing_Price_Vps_Managed_Windows	35
Billing_Price_Vps_Managed_Linux	36
Billing_Price_Sms	36
Billing_Price_Multihosting	36
Billing_Autorenew_GetAll	37
Billing_Autorenew_SetOff	37
Billing_Autorenew_SetOn	37
Billing_Autorenew_SetNoRenewable	38
Billing_Transfer_Domain	38
Billing_Transfer_GetRequirements	39
Billing_Help_DomainExtraData	39
Billing_Period_Domain	39
Billing_Period_Hosting	39
Billing_Period_Vps	40
Billing_Period_Multihosting	40
Billing_NoRenewable_GetAll	40
Billing_NoRenewable_SetRenewable	41
Dedicated commands	42
Dedicated_Hosting_GetSpace	42
Dedicated_Hosting_Activate	42
Dedicated_Hosting_GetAll	42
Dedicated_Hosting_Delete	43
Dedicated_Hosting_Deactivate	43
Dedicated_Hosting_GetSetupName	43
Dedicated_Hosting_Create	43
Dedicated_Hosting_ChangeSetup	44

Dedicated_GetDataTransferInfo	44
Dedicated_GetMonitorizedPorts	44
Dedicated_GetUsedSpace	45
Dedicated_Monitorization_Activate	45
Dedicated_Monitorization_Deactivate	45
Dedicated_Monitorization_Get	46
Dedicated_MailReport_SetOff	46
Dedicated_MailReport_Get	46
Dedicated_MailReport_Set	47
Dedicated_Services_GetAll	47
Dedicated_Services_ChangeStatus	47
Dedicated_GetLicenses	48
Dedicated_GetBandwidthConsumption	48
Dedicated_GetServerInfo	48
Dedicated_Kvm_Get	49
Dedicated_Kvm_Unmount	49
Dedicated_Kvm_Mount	49
Dedicated_HostingSetup_Update	50
Dedicated_HostingSetup_GetCustomSetups	50
Dedicated_HostingSetup_GetAll	50
Dedicated_HostingSetup_GetOptions	50
Dedicated_HostingSetup_Delete	51
Dedicated_HostingSetup_Create	51
Dedicated_HostingSetup_Get	51
Dedicated_HostingSetup_GetDhSetups	52
Dedicated_GetTransferValue	52
Dedicated_Control_GetApacheProcesses	52
Dedicated_Control_GetSystemLoad	52
Dedicated_Control_GetWebserverStatus	53
Dedicated_Control_GetSystemStatus	53
Dedicated_Control_KillMysqlProcess	53
Dedicated_Control_GetMysqlProcesses	54
Dedicated_Control_GetCpuLoadByHosting	54
Dedicated_Nfs_Get	54
Dedicated_GetSpaceAndTransferReportPerHosting	55
Dedicated_ForVps_GetServerInfo	55
Dedicated_ForVps_GetTicketStatus	55
Dedicated_ForVps_Vps_Update	55
Dedicated_ForVps_Vps_Activate	56
Dedicated_ForVps_Vps_Create_Unmanaged	56
Dedicated_ForVps_Vps_Create_Managed	57
Dedicated_ForVps_Vps_GetAll	57
Dedicated_ForVps_Vps_Delete	58
Dedicated_ForVps_Vps_Deactivate	58
Dedicated_ForVps_Vps_GetTypes	58
Dedicated_PowerStatus_Restart	58
Domain commands	60
Domain_Dnss_Get	60
Domain_Dnss_Set	60
Domain_WhoisPrivacy_Get	60
Domain_WhoisPrivacy_Set	60
Domain_GetAuthcode	61
Domain_PanelIndependentAccess_SetPassword	61
Domain_CheckForTransfer	61
Domain_Status_Lock	62
Domain_Status_Get	62
Domain_Status_Unlock	62
Domain_Status_IsLocked	62
Domain_Contacts_SetAll	63

Domain_Contacts_GetAll	63
Domain_Contacts_Get	63
Domain_Contacts_Set	63
Domain_Contacts_GetRegistrantVerificationInfo	64
Domain_UrlShortener_Activate	64
Domain_UrlShortener_GetAll	64
Domain_UrlShortener_Delete	65
Domain_UrlShortener_Deactivate	65
Domain_UrlShortener_Create	65
Domain_GetInfoDomain	65
Domain_Redirection_Set301	66
Domain_Redirection_GetAll	66
Domain_Redirection_Delete	66
Domain_Redirection_Get	66
Domain_Redirection_SetFrame	67
Domain_Redirection_SetFrameSimple	67
Domain_Redirection_SetStd	68
Domain_GetRenovationDate	68
Domain_Test	68
Domain_Parking_Get	68
Domain_Parking_Set	69
Domain_GetExpirationDate	69
Domain_NameServer_GetAll	69
Domain_NameServer_Modify	70
Domain_NameServer_Register	70
Domain_NameServer_Delete	70
Domain_GetRegistrationDate	70
Domain_CheckForRegister	71
Domain_Transfer_GetAuthcode	71
Domain_Transfer_SetAuthcode	71
Domain_Transfer_Cancel	72
Domain_Transfer_Restart	72
Domain_Transfer_GetStatus	72
Domain_Zone_DeleteTypeSPF	72
Domain_Zone_GetTypeCname	73
Domain_Zone_GetTypeA	73
Domain_Zone_GetTypeTXT	73
Domain_Zone_GetAll	74
Domain_Zone_DeleteTypeAAAA	74
Domain_Zone_GetTypeMX	74
Domain_Zone_AddTypeTXT	74
Domain_Zone_DeleteTypeA	75
Domain_Zone_DeleteAll	75
Domain_Zone_Delete	75
Domain_Zone_AddTypeURL301	76
Domain_Zone_UrlShortener_Activate	76
Domain_Zone_UrlShortener_GetAll	76
Domain_Zone_UrlShortener_Delete	76
Domain_Zone_UrlShortener_Deactivate	77
Domain_Zone_UrlShortener_Create	77
Domain_Zone_AddTypeSRV	77
Domain_Zone_GetTypeURL301	78
Domain_Zone_GetTypeSRV	78
Domain_Zone_UpdateTypeA	78
Domain_Zone_GetTypeURL	79
Domain_Zone_AddTypeURL	79
Domain_Zone_GetTypeAAAA	79
Domain_Zone_DeleteTypeMX	80
Domain_Zone_DeleteTypeSRV	80

Domain_Zone_AddTypeA.....	80
Domain_Zone_AddTypeAAAA.....	81
Domain_Zone_AddTypeCname.....	81
Domain_Zone_DeleteTypeCname.....	81
Domain_Zone_DeleteTypeFrame.....	82
Domain_Zone_DeleteTypeTXT.....	82
Domain_Zone_DeleteTypeURL301.....	82
Domain_Zone_AddTypeFrame.....	83
Domain_Zone_GetTypeSPF.....	83
Domain_Zone_AddTypeMXS.....	83
Domain_Zone_DeleteTypeURL.....	83
Domain_Zone_GetTypeFrame.....	84
Domain_Zone_UpdateTypeAAAA.....	84
Domain_Zone_AddTypeMX.....	84
DomainVerification commands.....	86
DomainVerification_GetPending.....	86
Hosting commands.....	87
Hosting_GetInfo.....	87
Hosting_Php_PhpExecutionOnHtmlIsActive.....	87
Hosting_Php_OverwritePhpIni.....	87
Hosting_Php_ActivatePhpExecutionOnHtml.....	87
Hosting_Php_OverwritePhpIniWithDefaults.....	88
Hosting_Php_SetVersion.....	88
Hosting_Php_DeactivatePhpExecutionOnHtml.....	88
Hosting_Certificate_Install.....	88
Hosting_Certificate_Uninstall.....	89
Hosting_Certificate_ActivateLetsEncrypt.....	89
Hosting_Certificate_DeactivateLetsEncrypt.....	89
Hosting_PanelIndependentAccess_SetPassword.....	89
Hosting_Ftp_Activate.....	90
Hosting_Ftp_Deactivate.....	90
Hosting_Ftp_Account_GetAll.....	90
Hosting_Ftp_Account_CmdStatus_ListAll.....	90
Hosting_Ftp_Account_CmdStatus_GetDelete.....	91
Hosting_Ftp_Account_CmdStatus_GetSetPassword.....	91
Hosting_Ftp_Account_CmdStatus_GetCreate.....	91
Hosting_Ftp_Account_Delete.....	92
Hosting_Ftp_Account_Create.....	92
Hosting_Ftp_Account_SetPassword.....	92
Hosting_Ftp_Get.....	93
Hosting_Ftp_GetAccountsLimit.....	93
Hosting_GetMailInfo.....	93
Hosting_Import_ApplyForEmailAccountImap.....	94
Hosting_Import_ListAll.....	94
Hosting_Import_List.....	95
Hosting_Import_ApplyForEmailAccountPop.....	95
Hosting_Import_ApplyForFtp.....	95
Hosting_Import_ApplyForDdbb.....	96
Hosting_Subdomain_GetAll.....	97
Hosting_Subdomain_Delete.....	97
Hosting_Subdomain_Create.....	97
Hosting_UrlShortener_Activate.....	98
Hosting_UrlShortener_GetAll.....	98
Hosting_UrlShortener_Delete.....	98
Hosting_UrlShortener_Deactivate.....	98
Hosting_UrlShortener_Create.....	99
Hosting_Dsn_Mysql_GetAll.....	99
Hosting_Dsn_Mysql_Delete.....	99
Hosting_Dsn_Mysql_Create.....	100

Hosting_Dsn_Access_GetAll	100
Hosting_Dsn_Access_Delete	100
Hosting_Dsn_Access_Create	100
Hosting_Dsn_Sqlserver_GetAll	101
Hosting_Dsn_Sqlserver_Delete	101
Hosting_Dsn_Sqlserver_Create	101
Hosting_Https_Activate	102
Hosting_Https_Deactivate	102
Hosting_Https_Get	102
Hosting_Ssh_Activate	102
Hosting_Ssh_Deactivate	103
Hosting_Ssh_Get	103
Hosting_IsActive	103
Hosting_GetDaysWithBackups	103
Hosting_Test	104
Hosting_TlsMail_Activate	104
Hosting_TlsMail_Deactivate	104
Hosting_TlsMail_Get	105
Hosting_Backup_Database_GetTables	105
Hosting_Backup_Restore_EmailAccounts	105
Hosting_Backup_Restore_Database_Tables	106
Hosting_Backup_Restore_Database	106
Hosting_Backup_Restore_Resource	106
Hosting_Backup_Send_Database_Tables	107
Hosting_Backup_Send_Database	107
Hosting_Backup_Send_Resource	107
Hosting_Backup_GetResources	108
Hosting_Backup_GetEmailAccounts	108
Hosting_Backup_GetDatabases	108
Hosting_Backup_GetStatus	109
Hosting_Email_Filter_SetGeolocalization	109
Hosting_Email_Filter_GetAll	109
Hosting_Email_Filter_CreateForSpam	110
Hosting_Email_Filter_Delete	110
Hosting_Email_Filter_Create	110
Hosting_Email_Filter_GetGeolocalization	111
Hosting_Email_Dkim_Activate	111
Hosting_Email_Dkim_Deactivate	111
Hosting_Email_Dkim_Get	111
Hosting_Email_Dkim_IsActive	112
Hosting_Email_Antivirus_SetConfig	112
Hosting_Email_Antivirus_GetConfig	112
Hosting_Email_Antivirus_UpdateAttachedFileFilter	113
Hosting_Email_Antivirus_GetAttachedFilesFilters	113
Hosting_Email_Antispam_SetConfig	113
Hosting_Email_Antispam_Activate	113
Hosting_Email_Antispam_GetScore	114
Hosting_Email_Antispam_Deactivate	114
Hosting_Email_Antispam_AddDomainToWhitelist	114
Hosting_Email_Antispam_SetScore	114
Hosting_Email_Antispam_GetConfig	115
Hosting_Email_Antispam_GetWhitelist	115
Hosting_Email_Antispam_AddDomainToBlacklist	115
Hosting_Email_Antispam_GetBlacklist	116
Hosting_Email_Antispam_RemoveDomainFromWhitelist	116
Hosting_Email_Antispam_RemoveDomainFromBlacklist	116
Hosting_Email_UsedSpace_GetPerAlias	116
Hosting_Email_UsedSpace_Get	117
Hosting_Email_Account_Activate	117

Hosting_Email_Account_GetAll	117
Hosting_Email_Account_Delete	118
Hosting_Email_Account_Deactivate	118
Hosting_Email_Account_SetCopyTo	118
Hosting_Email_Account_Create	118
Hosting_Email_Account_GetCopyTo	119
Hosting_Email_Account_Get	119
Hosting_Email_Account_SetPassword	120
Hosting_Email_Account_RemoveCopyTo	120
Hosting_Email_Account_Empty	120
Hosting_Email_Redirection_ActivateCatchAll	121
Hosting_Email_Redirection_DeactivateCatchAll	121
Hosting_Email_Redirection_Update	121
Hosting_Email_Redirection_GetAll	121
Hosting_Email_Redirection_Delete	122
Hosting_Email_Redirection_Create	122
Hosting_Email_Redirection_Get	122
Hosting_Email_Autoresponse_Activate	123
Hosting_Email_Autoresponse_Delete	123
Hosting_Email_Autoresponse_Deactivate	123
Hosting_Email_Autoresponse_Create	124
Hosting_Email_Autoresponse_Get	124
Hosting_Email_AutomaticDeletion_CreateRule	124
Hosting_Email_AutomaticDeletion_DeleteRule	125
Hosting_Ddbb_GetAll	125
Hosting_Ddbb_Mysql_GetInfo	125
Hosting_Ddbb_Mysql_SetIpAcl	126
Hosting_Ddbb_Mysql_GetAll	126
Hosting_Ddbb_Mysql_Delete	126
Hosting_Ddbb_Mysql_Create	127
Hosting_Ddbb_Mysql_SetHostAcl	127
Hosting_Ddbb_Mysql_BackupTask_GetAll	127
Hosting_Ddbb_Mysql_BackupTask_Delete	128
Hosting_Ddbb_Mysql_BackupTask_Set	128
Hosting_Ddbb_Mysql_GetAclConfiguration	128
Hosting_Ddbb_Mysql_Backup_Get	129
Hosting_Ddbb_Mysql_Backup_Restore	129
Hosting_Ddbb_Mysql_CreateWithIpAcl	129
Hosting_Ddbb_Mysql_SetPassword	130
Hosting_Ddbb_Postgre_GetAll	130
Hosting_Ddbb_Postgre_Delete	130
Hosting_Ddbb_Postgre_Create	131
Hosting_Ddbb_Postgre_SetPassword	131
Hosting_Ddbb_Access_GetAllMdb	131
Hosting_Ddbb_MariaDb_GetAll	132
Hosting_Ddbb_MariaDb_Delete	132
Hosting_Ddbb_MariaDb_Create	132
Hosting_Ddbb_MariaDb_SetPassword	133
Hosting_Ddbb_MongoDb_GetAll	133
Hosting_Ddbb_MongoDb_Delete	133
Hosting_Ddbb_MongoDb_SetPassword	133
Hosting_Ddbb_Sqlserver_SetDataSize	134
Hosting_Ddbb_Sqlserver_GetAll	134
Hosting_Ddbb_Sqlserver_GetSpaceInfo	134
Hosting_Ddbb_Sqlserver_Delete	135
Hosting_Ddbb_Sqlserver_Create	135
Hosting_Ddbb_Sqlserver_GetGlobalSpaceInfo	135
Hosting_Ddbb_Sqlserver_SetPassword	136
Hosting_Ddbb_Sqlserver_SetTransactionsSize	136

Housing commands	137
Housing_GetDataTransferInfo	137
Housing_Monitorization_Activate	137
Housing_Monitorization_Deactivate	137
Housing_Monitorization_Get	137
Housing_GetBandwidthConsumption	138
Housing_GetServerInfo	138
Housing_Kvm_Get	138
Housing_Kvm_Unmount	139
Housing_Kvm_Mount	139
Housing_GetTransferValue	139
Housing_PowerStatus_Restart	139
Import commands	141
Import_GetStatus	141
Multihosting commands	142
Multihosting_Hosting_GetSpace	142
Multihosting_Hosting_Activate	142
Multihosting_Hosting_GetAll	142
Multihosting_Hosting_Delete	142
Multihosting_Hosting_Deactivate	143
Multihosting_Hosting_Create	143
Multihosting_Hosting_ChangeSetup	143
Multihosting_GetInfo	144
Multihosting_GetUsedSpace	144
Multihosting_MailReport_SetOff	144
Multihosting_MailReport_Get	145
Multihosting_MailReport_Set	145
Multihosting_GetLicenses	145
Multihosting_HostingSetup_Update	146
Multihosting_HostingSetup_GetAll	146
Multihosting_HostingSetup_GetOptions	146
Multihosting_HostingSetup_Delete	147
Multihosting_HostingSetup_Create	147
Multihosting_HostingSetup_Get	147
Multihosting_GetEmailAccountsNumber	148
Multihosting_GetUsedTransfer	148
Payment commands	149
Payment_Method_GetAll	149
Payment_Credit_GetDetailed	149
Payment_Credit_List	149
Payment_Credit_GetTotal	149
Services commands	151
Services_GetHostings	151
Services_GetManagedDedicatedServers	151
Services_GetHousingServers	151
Services_GetDomains	151
Services_GetUnmanagedCloudServers	152
Services_GetManagedVps	152
Services_GetAllManagedServersNames	152
Services_GetDedicatedServers	153
Services_GetCloudServers	153
Services_GetVps	153
Services_GetDomainTransfers	154
Services_GetSms	154
Services_GetMultihostings	154
Services_GetUnmanagedDedicatedServers	154
Services_GetManagedCloudServers	155
Services_GetUnmanagedVps	155
Sms commands	156

Sms_Programmed_Cancel	156
Sms_GetCredit	156
Sms_PaneIndependentAccess_SetPassword	156
Sms_SetUp	156
Sms_History_GetProgrammed	157
Sms_History_GetBulkSent	157
Sms_History_GetSent	157
Sms_Send_Bulk_Limited_Gsm7	158
Sms_Send_Bulk_Limited_Unicode	158
Sms_Send_Bulk_Long_Gsm7	158
Sms_Send_Bulk_Long_Unicode	159
Sms_GetSender	159
Sms_Phonebook_GetAllContacts	160
Sms_Phonebook_DeleteContact	160
Sms_Phonebook_CreateContact	160
Sms_Phonebook_UpdateContact	161
Sms_DeliveryList_Update	161
Sms_DeliveryList_GetAll	161
Sms_DeliveryList_Delete	161
Sms_DeliveryList_Create	162
Sms_DeliveryList_Get	162
Sms_DeliveryList_GetPhones	162
System commands	164
System_GetResponseTypes	164
System_GetRequestTypes	164
System_MethodHelp	164
System_MethodSignature	164
System_TestSimulation	164
System_ListMethods	165
System_GetApiVersion	165
User commands	166
User_GetInfo	166
User_Data_GetValidLegalForms	166
User_GetServices	166
User_GetNotifications	166
User_GetInvoicedAmount	167
User_GetLastLoginDate	167
User_Secondary_Update	167
User_Secondary_GetAll	168
User_Secondary_Delete	168
User_Secondary_Create	168
User_Default_GetAdminContact	169
User_Default_GetDnss	169
User_Default_GetTechContact	169
Vps commands	170
Vps_Hosting_Activate	170
Vps_Hosting_GetAll	170
Vps_Hosting_Delete	170
Vps_Hosting_Deactivate	170
Vps_Hosting_GetSetupName	171
Vps_Hosting_Create	171
Vps_Hosting_ChangeSetup	171
Vps_GetDataTransferInfo	172
Vps_GetMonitorizedPorts	172
Vps_GetUsedSpace	172
Vps_Monitorization_Activate	173
Vps_Monitorization_Deactivate	173
Vps_Monitorization_Get	173
Vps_GetAllHostingsFullReport	174

Vps_MailReport_SetOff	174
Vps_MailReport_Get	174
Vps_MailReport_Set	174
Vps_Services_GetAll	175
Vps_Services_ChangeStatus	175
Vps_GetLicenses	175
Vps_GetBandwidthConsumption	176
Vps_GetServerInfo	176
Vps_HostingSetup_Update	176
Vps_HostingSetup_GetAll	177
Vps_HostingSetup_GetOptions	177
Vps_HostingSetup_Delete	177
Vps_HostingSetup_Create	178
Vps_HostingSetup_Get	178
Vps_Control_GetApacheProcesses	178
Vps_Control_GetSystemLoad	178
Vps_Control_GetSystemStatus	179
Vps_Control_KillMysqlProcess	179
Vps_Control_GetMysqlProcesses	179
Vps_Control_GetCpuLoadByHosting	180
Vps_Nfs_Get	180
Vps_GetSpaceAndTransferReportPerHosting	180
Vps_PowerStatus_Reactivate	181
Vps_PowerStatus_TurnOn	181
Vps_PowerStatus_ElectricRestart	181
Vps_PowerStatus_Pause	181
Vps_PowerStatus_Get	182
Vps_PowerStatus_Suspend	182
Vps_PowerStatus_TurnOff	182
Vps_PowerStatus_Unpause	182
Vps_PowerStatus_Restart	183

Request and Response

Request types

Xmlrpc

Standard Xml Remote Procedure Call request.

Special HTTP request that sends XML encoded arguments and expects a XML encoded response.

Characteristics and requirements:

- Request data sent through HTTP POST query .
- Content-type indicated as "application/xml" on HTTP headers.
- User login data must be sent at "Authorization: Basic" on HTTP headers .
- Parameters must arrive ordered, as described in method signature.
- Only used with Xmlrpc response type.
- Simulation mode only available on web server at <https://dinahosting.com/api/> .

Simple

Simple HTTP REQUEST .

Standard HTTP request that sends key=value pairs in a URL encoded request.

Characteristics and requirements:

- Request data sent through a standard HTTP GET or POST query .
- User login authentication data might be sent at "Authorization: Basic" on HTTP headers or in request parameters AUTH_USER and AUTH_PWD.
- Parameters can be sent in any order. Keys are case sensitive.
- Can be used with any responseType.
- Can force client-side activation of simulation mode. Just add a boolean parameter SIMULATE=true to the request.

Example: https://dinahosting.com/special/api.php?AUTH_USER=yourUser&AUTH_PWD=yourPass&comm and=System_GetRequestTypes&responseType=Xml&SIMULATE=false

Jsonrpc

Json Remote Procedure Call request.

Special HTTP request that sends JSON encoded arguments and expects a JSON encoded response.

Characteristics and requirements:

- Request data sent through HTTP POST query .
- Content-type indicated as "application/json" on HTTP headers.
- User login data must be sent at "Authorization: Basic" on HTTP headers .
- Parameters can be sent in any order. Keys are case sensitive.
- Only used with Jsonrpc response type.
- Simulation mode only available on web server at <https://dinahosting.com/api/>.

Response types

Xmlrpc

Extensible markup language Remote procedure call response.

Standard XML response built with Zend XmlRpc server.
Easy to parse with Zend XmlRpc client, but heavier communication.

Recommended only for XmlRpc requests.

Simple

Simple key value plain text response.

Lightest response, but it isn't standard.
Parsing may be troublesome if response data is complex.
Useful for testing purposes.

Used with standard (Simple) HTTP requests.

Jsonrpc

JavaScript Object Notation Remote procedure call response.

Same as standard Json .

Only for JsonRpc requests.

Json

JavaScript Object Notation response.

Lightweight, multi-plataform, easy parseable response type.

Used with standard (Simple) HTTP requests.

Test

Testing response. Returns valid PHP code.
Harder to parse than Json or XML.

Used with standard (Simple) HTTP requests.

Debug

Debugging response.

Used with standard (Simple) HTTP requests.

Xml

Extensible markup language response.

Multi-plataform language. Lighter than our XmlRpc.

Used with standard (Simple) HTTP requests.

Errors

Error codes

SUCCESS (code: 1000)

Command execution ended OK and returned data if any.

Error message: *Success.*

Can be thrown by commands: All existing commands might return this error.

SUCCESS_PENDING (code: 1001)

Command execution ended OK but additional background action is pending.

Error message: *Success. Action is pending.*

Can be thrown by commands: None

UNKNOWN_COMMAND (code: 2000)

The user requested a command that doesn't exist.

Error message: *Unknown command.*

Can be thrown by commands: Thrown if requested command doesn't exist.

COMMAND_SYNTAX_ERROR (code: 2001)

There is at least one error at command arguments.

A parameter may be missing or has got a bad format.

See additional information at errors structure.

Error message: *Command syntax error.*

Can be thrown by commands: All existing commands might return this error.

COMMAND_USE_ERROR (code: 2002)

The user doesn't indicate a command on request, requested an invalid response type, or tried to use a command for something that isn't meant to.

Error message: *Command use error.*

Can be thrown by commands: All existing commands might return this error.

PARAM_MISSING (code: 2003)

The command requires a parameter that is missing on the request.

Error message: *Required param "%s" is missing.*

Can be thrown by commands: All existing commands might return this error.

PARAM_VALUE_RANGE (code: 2004)

A command parameter value length isn't valid. The value length might be too long or too short.

Error message: *Param "%s" length is not valid.*

Can be thrown by commands: All existing commands might return this error.

PARAM_VALUE_SYNTAX (code: 2005)

A command parameter value format isn't valid.

Error message: *Param "%s" value syntax is not valid.*

Can be thrown by commands: All existing commands might return this error.

DELETED_COMMAND (code: 2100)

The user requested a command that existed but it isn't available anymore, as it was deprecated and deleted.

Error message: *Command was deprecated and itsn't available anymore.*

Can be thrown by commands: None

UNIMPLEMENTED_COMMAND (code: 2101)

The user requested a command that exists but it isn't implemented, or tried to do simulation or MethodHelp over a command that doesn't implements it.

Error message: *Action %s currently cant be performed on this command.*

Can be thrown by commands: All existing commands might return this error.

BILLING_FAILURE (code: 2104)

The billing process failed. Check you've got enough cash and retry operation.

Error message: *Billing error.*

Can be thrown by commands: Billing_Renew_Domain, Billing_Renew_Hosting, Billing_Renew_Sms, Billing_Renew_Multihosting, Billing_Buy_Domain, Billing_Buy_Hosting, Billing_Buy_DomainUsingContactsIds, Billing_Buy_Sms, Billing_Buy_Multihosting, Billing_Autorenew_SetOn, Billing_Transfer_Domain

BILLING_NOT_ALLOWED (code: 2105)

User is not authorized to perform any billing operations.

Error message: *Billing operations are not allowed.*

Can be thrown by commands: None

AUTH_ERROR_USER (code: 2200)

The user authentication failed. Check that username and password sent on request are valid. Keep in mind that some request types require sending auth info on HTTP headers.

Error message: *Authentication error.*

Can be thrown by commands: All existing commands might return this error.

AUTH_ERROR_OBJECT (code: 2201)

The authenticated user is not authorized to execute this action on the required object (domain, hosting, ...). This could happen if you aren't the owner of the object, or the object internal status doesn't allow this action (it isn't active ...).

Error message: *Authorization error.*

Can be thrown by commands: All existing commands might return this error.

OBJECT_EXISTS (code: 2302)

The request is valid but it can be only completed if the requested object (zone, hosting, email account...) doesn't exists.

Error message: *Param "%s" value already exists.*

Can be thrown by commands: Hosting_Import_ApplyForEmailAccountImap, Hosting_Import_ApplyForEmailAccountPop, Hosting_Import_ApplyForFtp, Hosting_Import_ApplyForDdbb, Hosting_Subdomain_Create, Hosting_Dsn_Mysql_Create, Hosting_Dsn_Access_Create, Hosting_Dsn_Sqlserver_Create, Hosting_Email_Antispam_AddDomainToWhitelist, Hosting_Email_Antispam_AddDomainToBlacklist, Hosting_Email_Account_Create, Hosting_Email_Redirection_Create, Hosting_Email_Autoresponse_Create, Hosting_Ddbb_Mysql_Create, Hosting_Ddbb_Mysql_CreateWithIpAcl, Hosting_Ddbb_Postgre_Create, Hosting_Ddbb_MariaDb_Create, Hosting_Ddbb_Sqlserver_Create, Dedicated_Hosting_Create, Dedicated_HostingSetup_Create, Multihosting_Hosting_Create, Multihosting_HostingSetup_Create, Domain_Zone_AddTypeTXT, Domain_Zone_AddTypeURL301, Domain_Zone_UrlShortener_Activate, Domain_Zone_AddTypeSRV, Domain_Zone_AddTypeURL, Domain_Zone_AddTypeA, Domain_Zone_AddTypeAAAA, Domain_Zone_AddTypeCname, Domain_Zone_AddTypeFrame, Domain_Zone_AddTypeMXS, Domain_Zone_AddTypeMX, Billing_Buy_Domain, Billing_Buy_Hosting, Billing_Buy_DomainUsingContactsIds, Billing_Buy_Sms, Billing_Buy_Multihosting, Billing_Transfer_Domain, Vps_Hosting_Create, Vps_HostingSetup_Create

OBJECT_NOT_EXISTS (code: 2303)

The request is valid but it can be only completed if the requested object (zone, hosting, email account ...) already exists.

Error message: *Param "%s" value doesn't exist.*

Can be thrown by commands: Hosting_Ftp_Account_Delete, Hosting_Ftp_Account_SetPassword, Hosting_Import_ApplyForEmailAccountImap, Hosting_Import_ApplyForEmailAccountPop, Hosting_Import_ApplyForFtp, Hosting_Import_ApplyForDdbb, Hosting_Subdomain_Delete, Hosting_Subdomain_Create, Hosting_Email_Antispam_RemoveDomainFromWhitelist, Hosting_Email_Antispam_RemoveDomainFromBlacklist, Hosting_Email_Account_Activate, Hosting_Email_Account_Delete, Hosting_Email_Account_Deactivate, Hosting_Email_Account_SetCopyTo, Hosting_Email_Account_GetCopyTo, Hosting_Email_Account_SetPassword, Hosting_Email_Account_RemoveCopyTo, Hosting_Email_Account_Empty, Hosting_Email_Redirection_Update, Hosting_Email_Redirection_Delete, Hosting_Email_Autoresponse_Activate, Hosting_Email_Autoresponse_Delete, Hosting_Email_Autoresponse_Deactivate, Hosting_Email_Autoresponse_Create, Hosting_Email_Autoresponse_Get, Dedicated_Hosting_GetSpace, Dedicated_Hosting_Activate, Dedicated_Hosting_Delete, Dedicated_Hosting_Deactivate, Dedicated_Hosting_GetSetupName, Dedicated_Hosting_Create, Dedicated_Hosting_ChangeSetup, Dedicated_Services_ChangeStatus, Dedicated_HostingSetup_Update, Dedicated_HostingSetup_Get, Dedicated_Control_KillMysqlProcess, Multihosting_Hosting_GetSpace, Multihosting_Hosting_Activate, Multihosting_Hosting_Delete, Multihosting_Hosting_Deactivate, Multihosting_Hosting_ChangeSetup, Multihosting_HostingSetup_Update, Multihosting_HostingSetup_Get, Domain_Zone_DeleteTypeSPF, Domain_Zone_DeleteTypeAAAA, Domain_Zone_DeleteTypeA, Domain_Zone_Delete, Domain_Zone_UpdateTypeA, Domain_Zone_DeleteTypeMX, Domain_Zone_DeleteTypeSRV, Domain_Zone_AddTypeCname, Domain_Zone_DeleteTypeCname, Domain_Zone_DeleteTypeTXT, Domain_Zone_UpdateTypeAAAA, Domain_Zone_AddTypeMX, Billing_Renew_Domain, Billing_Renew_Hosting, Billing_Autorenew_SetOff, Billing_Autorenew_SetOn, Billing_Autorenew_SetNoRenewable, Billing_Transfer_Domain, Billing_NoRenewable_SetRenewable, Vps_Hosting_Activate, Vps_Hosting_Delete, Vps_Hosting_Deactivate, Vps_Hosting_GetSetupName, Vps_Hosting_Create, Vps_Hosting_ChangeSetup, Vps_Services_ChangeStatus, Vps_HostingSetup_Update, Vps_HostingSetup_Get, Vps_Control_KillMysqlProcess, Sms_Programmed_Cancel

OBJECT_STATUS_PROHIBITS_OP (code: 2304)

The request is valid but it can be only completed if the requested object status meets some condition.

Some condition must be achieved before executing the command again.

Please, read the command documentation for additional information about command limitations and requeriments.

Error message: *Param "%s" current value status prohibits operation.*

Can be thrown by commands: Hosting_Ftp_Account_Create, Hosting_Subdomain_GetAll,

Hosting_Subdomain_Delete, Hosting_Subdomain_Create, Hosting_UrlShortener_Activate,
 Hosting_UrlShortener_GetAll, Hosting_UrlShortener_Delete, Hosting_UrlShortener_Deactivate,
 Hosting_UrlShortener_Create, Hosting_TlsMail_Activate, Hosting_TlsMail_Deactivate,
 Hosting_TlsMail_Get, Domain_WhoisPrivacy_Set, Domain_UrlShortener_Activate,
 Domain_UrlShortener_GetAll, Domain_UrlShortener_Delete, Domain_UrlShortener_Deactivate,
 Domain_UrlShortener_Create, Domain_Transfer_GetAuthcode, Domain_Transfer_SetAuthcode,
 Domain_Transfer_Cancel, Domain_Transfer_Restart, Domain_Transfer_GetStatus,
 Domain_Zone_UrlShortener_Activate, Domain_Zone_UrlShortener_GetAll,
 Domain_Zone_UrlShortener_Delete, Domain_Zone_UrlShortener_Deactivate,
 Domain_Zone_UrlShortener_Create, Domain_Zone_AddTypeMX, Billing_Autorenew_SetOn

OBJECT_ASSOCIATION_PROHIBITS_OP (code: 2305)

The request is valid but can't be run because the object is currently associated to another object. Association must be broken before running this command.

Error message: *Param "%s" current value is associated to another object. Association must be broken.*

Can be thrown by commands: Domain_Zone_DeleteTypeAAAA, Domain_Zone_DeleteTypeA, Domain_Zone_Delete, Domain_Zone_DeleteTypeCname

PARAMETER_VALUE_POLICY_ERROR (code: 2306)

A internal or external parameter value is not valid. It's registry implementation dependant. This is relatively common if domain contacts are missing.

Error message: *Some argument value is not currently valid*

Can be thrown by commands: Hosting_Import_ApplyForFtp, Domain_Dnss_Set, Billing_Autorenew_SetOn

UNIMPLEMENTED_OBJECT_SERVICE (code: 2307)

The request is valid but requested object won't admit it, neither now nor later.

Please, read the command documentation for additional information about command limitations and requirements.

Error message: *Command cannot be run on requested object.*

Can be thrown by commands: Hosting_Php_PhpExecutionOnHtmlsActive, Hosting_Php_OverwritePhpIni, Hosting_Php_ActivatePhpExecutionOnHtml, Hosting_Php_OverwritePhpIniWithDefaults, Hosting_Php_SetVersion, Hosting_Php_DeactivatePhpExecutionOnHtml, Hosting_Ftp_Activate, Hosting_Ftp_Deactivate, Hosting_Ftp_Account_GetAll, Hosting_Ftp_Account_Delete, Hosting_Ftp_Account_Create, Hosting_Ftp_Account_SetPassword, Hosting_Ftp_Get, Hosting_Ftp_GetAccountsLimit, Hosting_GetMailInfo, Hosting_Dsn_Mysql_GetAll, Hosting_Dsn_Mysql_Delete, Hosting_Dsn_Mysql_Create, Hosting_Dsn_Access_GetAll, Hosting_Dsn_Access_Delete, Hosting_Dsn_Access_Create, Hosting_Dsn_Sqlserver_GetAll, Hosting_Dsn_Sqlserver_Delete, Hosting_Dsn_Sqlserver_Create, Hosting_Ssh_Activate, Hosting_Ssh_Deactivate, Hosting_Ssh_Get, Hosting_TlsMail_Activate, Hosting_TlsMail_Deactivate, Hosting_TlsMail_Get, Hosting_Email_Filter_SetGeolocalization, Hosting_Email_Filter_GetAll, Hosting_Email_Filter_CreateForSpam, Hosting_Email_Filter_Delete, Hosting_Email_Filter_Create, Hosting_Email_Filter_GetGeolocalization, Hosting_Email_Antivirus_SetConfig, Hosting_Email_Antivirus_GetConfig, Hosting_Email_Antivirus_UpdateAttachedFileFilter, Hosting_Email_Antivirus_GetAttachedFilesFilters, Hosting_Email_Antispam_SetConfig, Hosting_Email_Antispam_Activate, Hosting_Email_Antispam_GetScore, Hosting_Email_Antispam_Deactivate, Hosting_Email_Antispam_AddDomainToWhitelist, Hosting_Email_Antispam_SetScore, Hosting_Email_Antispam_GetConfig, Hosting_Email_Antispam_GetWhitelist, Hosting_Email_Antispam_AddDomainToBlacklist, Hosting_Email_Antispam_GetBlacklist, Hosting_Email_Antispam_RemoveDomainFromWhitelist, Hosting_Email_Antispam_RemoveDomainFromBlacklist, Hosting_Email_Account_Activate, Hosting_Email_Account_GetAll, Hosting_Email_Account_Delete, Hosting_Email_Account_Deactivate, Hosting_Email_Account_SetCopyTo, Hosting_Email_Account_Create,

Hosting_Email_Account_GetCopyTo, Hosting_Email_Account_Get, Hosting_Email_Account_SetPassword,
 Hosting_Email_Account_RemoveCopyTo, Hosting_Email_Account_Empty,
 Hosting_Email_Redirection_ActivateCatchAll, Hosting_Email_Redirection_DeactivateCatchAll,
 Hosting_Email_Redirection_Update, Hosting_Email_Redirection_GetAll,
 Hosting_Email_Redirection_Delete, Hosting_Email_Redirection_Create, Hosting_Email_Redirection_Get,
 Hosting_Email_Autoresponse_Activate, Hosting_Email_Autoresponse_Delete,
 Hosting_Email_Autoresponse_Deactivate, Hosting_Email_Autoresponse_Create,
 Hosting_Email_Autoresponse_Get, Hosting_Ddbb_Mysql_GetInfo, Hosting_Ddbb_Mysql_SetIpAcl,
 Hosting_Ddbb_Mysql_GetAll, Hosting_Ddbb_Mysql_Delete, Hosting_Ddbb_Mysql_Create,
 Hosting_Ddbb_Mysql_SetHostAcl, Hosting_Ddbb_Mysql_BackupTask_GetAll,
 Hosting_Ddbb_Mysql_BackupTask_Delete, Hosting_Ddbb_Mysql_BackupTask_Set,
 Hosting_Ddbb_Mysql_GetAclConfiguration, Hosting_Ddbb_Mysql_Backup_Get,
 Hosting_Ddbb_Mysql_Backup_Restore, Hosting_Ddbb_Mysql_CreateWithIpAcl,
 Hosting_Ddbb_Mysql_SetPassword, Hosting_Ddbb_Postgre_GetAll, Hosting_Ddbb_Postgre_Delete,
 Hosting_Ddbb_Postgre_Create, Hosting_Ddbb_Postgre_SetPassword, Hosting_Ddbb_MariaDb_GetAll,
 Hosting_Ddbb_MariaDb_Delete, Hosting_Ddbb_MariaDb_Create, Hosting_Ddbb_MariaDb_SetPassword,
 Hosting_Ddbb_MongoDb_GetAll, Hosting_Ddbb_MongoDb_Delete,
 Hosting_Ddbb_MongoDb_SetPassword, Hosting_Ddbb_Sqlserver_SetDataSize,
 Hosting_Ddbb_Sqlserver_GetAll, Hosting_Ddbb_Sqlserver_GetSpaceInfo,
 Hosting_Ddbb_Sqlserver_Delete, Hosting_Ddbb_Sqlserver_Create,
 Hosting_Ddbb_Sqlserver_GetGlobalSpaceInfo, Hosting_Ddbb_Sqlserver_SetPassword,
 Hosting_Ddbb_Sqlserver_SetTransactionsSize, Dedicated_GetMonitorizedPorts,
 Dedicated_ForVps_Vps_Update, Dedicated_ForVps_Vps_Activate,
 Dedicated_ForVps_Vps_Create_Unmanaged, Dedicated_ForVps_Vps_Create_Managed,
 Dedicated_ForVps_Vps_GetAll, Dedicated_ForVps_Vps_Delete, Dedicated_ForVps_Vps_Deactivate,
 Dedicated_ForVps_Vps_GetTypes, Domain_CheckForTransfer, Domain_NameServer_GetAll,
 Domain_CheckForRegister, Domain_Transfer_GetAuthcode, Domain_Transfer_SetAuthcode,
 Billing_Renew_Domain, Billing_Autorenew_SetOn, Vps_GetMonitorizedPorts

COMMAND_FAILED (code: 2400)

Command failed because of an internal error. Command request is valid but we couldn't finish it.
 You can try again later o contact with support for additional details.

Error message: *Command failed.*

Can be thrown by commands: All existing commands might return this error.

COMMAND_FAILED_FATAL (code: 2500)

Command execution ended with an internal fatal error.

The execution might end OK but something went wrong. Or maybe command execution doesn't started at all.

We'll look at the problem and fix it ASAP.

Error message: *Command failed, internal error.*

Can be thrown by commands: All existing commands might return this error.

COMMAND_TIMEOUT (code: 2501)

We received a timeout during execution of command.

Command execution could end ok but we didn't get the response at time.

Error message: *Timeout on execution, command might be complete.*

Can be thrown by commands: All existing commands might return this error.

COMMAND_CONNECTIONSLIMIT (code: 2502)

User tried to complete too many command executions in a period of time and/or got banned.

Please, just wait and try again later.

Error message: *Too many connections, command won't execute. Try again later.*

Can be thrown by commands: None

COMMAND_MAINTENANCE_MODE (code: 2503)

Server is in maintenance mode.

Error message: *Maintenance mode. Try again later.*

Can be thrown by commands: None

COMMAND_PENDING_PREVIOUS_EXECUTION (code: 3101)

There is a existing execution for this delayed command.

Error message: *There is a previous pending execution.*

Can be thrown by commands: Hosting_Ftp_Account_Delete, Hosting_Ftp_Account_Create, Hosting_Ftp_Account_SetPassword

COMMAND_FTP_MAX_ACCOUNTS (code: 3601)

Hosting already reached maximum FTP accounts number.

Error message: *Reached max number of FTP accounts.*

Can be thrown by commands: None

COMMAND_EMAIL_REDIRECTION_MAX_ACCOUNTS (code: 3602)

Hosting already reached maximum email redirections number.

Error message: *Reached max number of email redirections.*

Can be thrown by commands: Hosting_Email_Redirection_Create

COMMAND_EMAIL_DISTRIBUTIONLIST_MAX (code: 3603)

Hosting already reached maximum distribution list number.

Error message: *Reached max number of email distribution lists.*

Can be thrown by commands: None

COMMAND_SERVER_KVM_GET_ERROR (code: 3604)

Server is missing KVM information.

Error message: *Missing KVM information.*

Can be thrown by commands: Housing_Kvm_Get, Dedicated_Kvm_Get

COMMAND_DEDICATED_SERVER_OS_ERROR (code: 3605)

Server Operating System can't run this command.

Error message: *Server O.S. is not compatible with this command.*

Can be thrown by commands: Dedicated_Control_GetApacheProcesses, Dedicated_Control_KillMysqlProcess, Vps_Control_KillMysqlProcess

COMMAND_LICENSE_MAX_HOSTINGS (code: 3606)

Server has reached the maximum number of hostings.

This limit is defined by the current server license.

Error message: *Reached maximum number of hostings - license limit.*

Can be thrown by commands: Dedicated_Hosting_Create, Multihosting_Hosting_Create, Vps_Hosting_Create

COMMAND_BILLING_PRODUCT_ERROR (code: 3607)

The requested product is not valid and billing process is aborted.
Remember that not all domain TLDs share same registration periods.

Error message: *Invalid product.*

Can be thrown by commands: Billing_Renew_Domain, Billing_Renew_Hosting, Billing_Renew_Vps, Billing_Renew_Sms, Billing_Renew_Multihosting, Billing_Buy_Domain, Billing_Buy_Hosting, Billing_Buy_DomainUsingContactsIds, Billing_Buy_Vps_Unmanaged_Windows, Billing_Buy_Vps_Unmanaged_Linux, Billing_Buy_Vps_Managed_Windows, Billing_Buy_Vps_Managed_Linux, Billing_Buy_Sms, Billing_Buy_Multihosting, Billing_Price_Domain, Billing_Price_Hosting, Billing_Price_Vps_Unmanaged_Windows, Billing_Price_Vps_Unmanaged_Linux, Billing_Price_Vps_Managed_Windows, Billing_Price_Vps_Managed_Linux, Billing_Price_Sms, Billing_Price_Multihosting, Billing_Transfer_Domain, Billing_Help_DomainExtraData, Billing_Period_Domain, Billing_Period_Hosting, Billing_Period_Vps, Billing_Period_Multihosting

COMMAND_BILLING_CREDIT (code: 3608)

The user has not enough credit for completing the billing process.

Error message: *Not enough credit.*

Can be thrown by commands: Billing_Renew_Domain, Billing_Renew_Hosting, Billing_Renew_Sms, Billing_Renew_Multihosting, Billing_Buy_Domain, Billing_Buy_Hosting, Billing_Buy_DomainUsingContactsIds, Billing_Buy_Sms, Billing_Buy_Multihosting, Billing_Transfer_Domain

COMMAND_EMAIL_MAX_HOSTINGS (code: 3609)

Server cannot create more hostings currently on this server.
It has reached the email accounts limit. Please, delete some and try again.

Error message: *Reached maximum number of email accounts on server.*

Can be thrown by commands: Hosting_Email_Account_Create

COMMAND_DOMAIN_FORBIDDEN_CONTACT_UPDATE (code: 3610)

Domain contacts update can't be run because of registry policy blocks certain contactType data change.
Example: .es registrant and .eu registrant contacts update are forbidden. These must be removed from request.

Error message: *Requested contact change is forbidden by registry policy.*

Can be thrown by commands: Domain_Contacts_SetAll, Domain_Contacts_Set

COMMAND_DDBB_SQLSERVER_NOT_ENOUGH_SPACE (code: 3612)

There is not enough space for the requested SqlServer operation.

Error message: *Not enough space. Check params "%s".*

Can be thrown by commands: Hosting_Ddbb_Sqlserver_Create

COMMAND_EMAIL_DISTRIBUTION_LIST_EXISTS (code: 3613)

Can't create the account. It exists a distribution list with the same email.

Error message: *It exists a distribution list with the same email.*

Can be thrown by commands: None

COMMAND_SMS_NOT_REMAINING_MESSAGES (code: 3614)

The user has not remaining messages for completing the sending process.

Error message: *Not remaining messages.*

Can be thrown by commands: None

COMMAND_MYSQL_MAX_DATABASES (code: 3615)

Server cannot create more MySQL databases currently on this server.

Error message: *Reached max number of MySQL databases.*

Can be thrown by commands: None

COMMAND_DOMAIN_IP_NOT_RESOLVING_DNS (code: 3616)

Some IP doesn't resolve a DNS.

Error message: *Some IP doesn't resolve a DNS.*

Can be thrown by commands: None

COMMAND_EMAIL_NOT_ENABLED (code: 3617)

Email accounts are not allowed on this hosting.

Error message: *Email accounts are not allowed on this hosting.*

Can be thrown by commands: None

COMMAND_REGENERATE_PASSWORD_SEND_METHOD (code: 3618)

Send method is not valid for this contact.

Error message: *Send method is not valid for this contact.*

Can be thrown by commands: None

COMMAND_EMAIL_ACCOUNT_SET_REPEATED_PASSWORD (code: 3619)

Password can not match any of the last 5 used in this account..

Error message: *Password can not match any of the last 5 used in this account.*

Can be thrown by commands: Hosting_Email_Account_SetPassword

COMMAND_BILLING_DOMAIN_FORBIDDEN_PREDEFINED_CONTACTS (code: 3620)

Some registries have special requirements that must be fit by user default domain registration contacts.

Error message: *Invalid predefined contacts for this TLD .%s*

Can be thrown by commands: Billing_Buy_Domain, Billing_Buy_DomainUsingContactsIds

COMMAND_DOMAIN_TRANSFER_ALREADY_APPROVED (code: 3630)

Domain transfer was already approved.

Error message: *Domain transfer was already approved.*

Can be thrown by commands: Domain_Transfer_Cancel, Domain_Transfer_Restart

COMMAND_DOMAIN_CERT_ALREADY_ASSOCIATED (code: 3631)

A cert has already been associated with this domain.

Error message: *A cert has already been associated with this domain.*

Can be thrown by commands: None

COMMAND_BILLING_PRODUCT_TEMPORARILY_DISABLED (code: 3621)

Product reference temporarily disabled by promotion or other reasons

Error message: *Product reference temporarily disabled by promotion or other reasons.*

Can be thrown by commands: None

COMMAND_NFS_VOLUME_DOES_NOT_EXIST (code: 3640)

Server does not have a nfs volume

Error message: *Server does not have a nfs volume*

Can be thrown by commands: None

COMMAND_PARAM_IS_NOT_A_VALID_CERTIFICATE (code: 3641)

(Missing documentation).

Error message: *(Missing response message, the error code might be on implementation).*

Can be thrown by commands: None

Commands

AdditionalStorage commands

AdditionalStorage_Repository_GetAll

Description:

Returns the repositories of an additional storage.

Version: 1.0

Parameters:

additionalStorage (string): Additional storage hostname. The parameter is required.

repositoryType (string): All repository types or one of them. The parameter is required. Accepted parameter values: "all", "ftp", "webdav", "svn", "git".

Response:

type: **struct**

Example:

'None'

AdditionalStorage_Repository_Delete

Description:

It deletes a repository in an additional storage.

Version: 1.0

Parameters:

additionalStorage (string): Additional storage hostname. The parameter is required.

type (string): Type. The parameter is required. Accepted parameter values: "ftp", "webdav", "svn", "git".

username (string): Account username. The parameter is required. Parameter value must be an alphanumeric string. Parameter length must be between 6 and 24 characters.

folder (string): Folder associated to the account. The parameter is required. Parameter value must be a valid name. Parameter length must be between 3 and 24 characters.

Response:

type: **struct**

Example:

'None'

AdditionalStorage_Repository_Create

Description:

It creates a repository in an additional storage.

Version: 1.0

Parameters:

additionalStorage (string): Additional storage hostname. The parameter is required.

type (string): Type. The parameter is required. Accepted parameter values: "ftp", "webdav", "svn", "git".

username (string): Account username. The parameter is required. Parameter value must be an alphanumeric string. Parameter length must be between 6 and 24 characters.

password (string): Account password. The parameter is required. Parameter value must be a string between 4 and 16 alphanumeric characters with fewer than 3 consecutive or repeated characters.

folder (string): Folder associated to the account. The parameter is required. Parameter value must be a

valid name. Parameter length must be between 3 and 24 characters.

Response:

type: **struct**

Example:

'None'

AdditionalStorage_Repository_SetPassword

Description:

It changes a repository password in an additional storage.

Version: 1.0

Parameters:

additionalStorage (**string**): Additional storage hostname. The parameter is required.

type (**string**): Type. The parameter is required. Accepted parameter values: "ftp","webdav","svn","git".

username (**string**): Account username. The parameter is required. Parameter value must be an alphanumeric string. Parameter length must be between 6 and 24 characters.

folder (**string**): Folder associated to the account. The parameter is required. Parameter value must be a valid name. Parameter length must be between 3 and 24 characters.

password (**string**): New account password. The parameter is required. Parameter value must be a string between 4 and 16 alphanumeric characters with fewer than 3 correlative or reapeded characters.

Response:

type: **struct**

Example:

'None'

Billing commands

Billing_Renew_Domain

Description:

Manually renew an existing domain name. Payment is done at runtime.

Domain must be currently registered at Dinahosting.

1.0 -> 1.1: Improved simulation mode.

1.1 -> 1.2: COMMAND_BILLING_CREDIT error.

1.2 -> 1.3: OBJECT_NOT_EXISTS error.

1.3 -> 1.4: New TLDs are supported.

Version: 1.4

Parameters:

domain (**string**): Domain name. The parameter is required.

period (**int**): Renew period (years). The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 10 inclusive.

whoisProtection (**bool**): Default is false. Set true to also renovate an already active whois protection for this domain. The parameter is optional. Parameter value must be a boolean (true or false).

paymentMethodType (**string**): Default is saldo. Set it to "bono" to use that payment Method. The parameter is optional. Accepted parameter values: "saldo","bono".

Response:

type: **void**

Billing_Renew_Hosting

Description:

Manually renew an existing hosting. Payment is done at runtime.

Hosting must exist in a Dinahosting server.

1.0 -> 1.1: Improved simulation mode.

1.1 -> 1.2: COMMAND_BILLING_CREDIT error.

Version: 1.2

Parameters:

hosting (**string**): Hosting name. The parameter is required.

period (**int**): Contratation period (months). The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 120 inclusive.

Response:

type: **void**

Billing_Renew_Vps

Description:

Renews a VPS.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

period (**int**): Contratation period (months). The parameter is required. Accepted parameter values:

"1", "3", "12".

Response:

type: **boolean**

Example:

'None'

Billing_Renew_Sms

Description:

Manually renew an existing SMS account. Payment is done at runtime.

1.0 -> 1.1: Improved simulation mode.

1.1 -> 1.2: COMMAND_BILLING_CREDIT error.

Version: 1.2

Parameters:

account (**string**): Sms account number. The parameter is required.

credit (**int**): Additional credit. The parameter is required. Parameter value must be a valid integer. Accepted parameter values: "50", "100", "1000", "5000", "20000".

Response:

type: **void**

Billing_Renew_Multihosting

Description:

Manually renew an existing multihosting. Payment is done at runtime.

1.0 -> 1.1: Improved simulation mode.

1.1 -> 1.2: COMMAND_BILLING_CREDIT error.

Version: 1.2

Parameters:

serverName (**string**): Server name. The parameter is required.

period (**int**): Renew period (years). The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 5 inclusive.

Response:

type: **void**

Billing_Buy_Domain

Description:

Buy and register a unused domain name.

1.0 -> 1.1: Improved simulation mode.

1.1 -> 1.2: COMMAND_BILLING_CREDIT error.

1.2 -> 1.3: New TLDs are supported.

1.3 -> 1.4: New contact keys (RegistrantIdentification, AdminIdentification, TechIdentification, BillingIdentification) - required for esNic domain validation.

1.4 -> 1.5: New optional contact keys (RegistrantFax, AdminFax, TechFax, BillingFax)

1.5 -> 1.6: New parameter extraData.

1.6 -> 1.7: New validation for esNic registration and new error code: COMMAND_BILLING_DOMAIN_FORBIDDEN_PREDEFINED_CONTACTS

Version: 1.7

Parameters:

domain (**string**): Domain name. The parameter is required.

period (**int**): Registration period (years). The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 10 inclusive.

contacts (**struct**): Array containing contacts (see Domain_Contacts_GetAll). Omit OrganizationName and LegalForm parameters in cases where contact is not an organization. The parameter is required. Parameter value must be a valid contacts.

dnss (**array**): Array containing at least 2 DNS strings. The parameter is optional. Parameter value must be a valid array of 2-8 unique DNS.

whoisProtection (**bool**): Default is false. Set true to buy domain whois protection. Is activated immediately after register this domain. The parameter is optional. Parameter value must be a boolean (true or false).

showRegistrantInfoOnWhois (**bool**): Default is false. Set true to show registrant info on whois. The parameter is optional. Parameter value must be a boolean (true or false).

showAdminContactInfoOnWhois (**bool**): Default is false. Set true to show admin contact info on whois. The parameter is optional. Parameter value must be a boolean (true or false).

showTechContactInfoOnWhois (**bool**): Default is false. Set true to show tech contact info on whois. The parameter is optional. Parameter value must be a boolean (true or false).

paymentMethodType (**string**): Default is saldo. Set it to "bono" to use that payment Method. The parameter is optional. Accepted parameter values: "saldo", "bono".

extraData (**struct**): Hash array containing additional data. The parameter is optional.

Response:

type: **void**

Billing_Buy_Hosting

Description:

Buy a new hosting.

1.2 -> 1.3: Improved simulation mode. Deprecated hostingType 810.

1.3 -> 1.4: COMMAND_BILLING_CREDIT error.

Version: 1.4

Parameters:

hosting (**string**): Hosting name. The parameter is required.

period (**int**): Contration period (months). The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 120 inclusive.

hostingType (**int**): Hosting type. 1 = hosting personal, 2 = hosting professional, 3 = hosting professional plus, 10 = Correo10, 419 = AppWordpress, 425 = AppConcrete5, 431 = AppMediaWiki, 436 = AppMagento, 470 = AppJoomla!, 498 = AppPhpBB. The parameter is required. Accepted parameter values: "1", "2", "3", "10", "419", "425", "431", "436", "470", "498".

serverOs (**string**): Host server operating system. The parameter is required. Accepted parameter values: "LINUX", "WINDOWS".

Response:

type: **void**

Billing_Buy_DomainUsingContactsIds

Description:

Buy and register a unused domain name.

1.0 -> 1.1: Improved simulation mode.

1.1 -> 1.2: COMMAND_BILLING_CREDIT error.

1.2 -> 1.3: New TLDs are supported.

1.3 -> 1.4: EsNic domain validation for technical contact: must be a natural person

1.4 -> 1.5: New parameter extraData.

1.5 -> 1.6: New validation for esNic registration and new error code:

COMMAND_BILLING_DOMAIN_FORBIDDEN_PREDEFINED_CONTACTS

Version: 1.6

Parameters:

domain (**string**): Domain name. The parameter is required.

period (**int**): Registration period (years). The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 10 inclusive.

contacts (**struct**): Array containing contacts ids. The parameter is required. Parameter value must be valid contacts ids.

dnss (**array**): Array containing at least 2 DNS strings. The parameter is optional. Parameter value must be a valid array of 2-8 unique DNS.

whoisProtection (**bool**): Default is false. Set true to buy domain whois protection. Is activated immediately after register this domain. The parameter is optional. Parameter value must be a boolean (true or false).

showRegistrantInfoOnWhois (**bool**): Default is false. Set true to show registrant info on whois. The parameter is optional. Parameter value must be a boolean (true or false).

showAdminContactInfoOnWhois (**bool**): Default is false. Set true to show admin contact info on whois. The parameter is optional. Parameter value must be a boolean (true or false).

showTechContactInfoOnWhois (**bool**): Default is false. Set true to show tech contact info on whois. The parameter is optional. Parameter value must be a boolean (true or false).

paymentMethodType (**string**): Default is saldo. Set it to "bono" to use that payment Method. The parameter is optional. Accepted parameter values: "saldo","bono".

extraData (**struct**): Hash array containing additional data. The parameter is optional.

Response:

type: **void**

Billing_Buy_Vps_Unmanaged_Windows

Description:

Buys an unmanaged windows VPS.

Version: 1.0

Parameters:

type (**string**): Type. The parameter is required. Accepted parameter values: "V-Server Pro","V-Server Pro Plus","V-Server Elite".

period (**int**): Contration period (months). The parameter is required. Accepted parameter values: "1","3","12".

vcpusCount (**int**): Number of vcpus. The parameter is required. Accepted parameter values: "1","2","4".

diskType (**string**): Disk type. Use the command 'Billing_GetConfigurableVpsOptions' to get the list of available disk types. The parameter is required.

diskImage (**string**): Disk image. Use the command 'Billing_GetConfigurableVpsOptions' to get the list of available disk images. The parameter is required.

Response:

type: **boolean**

Example:

'None'

Billing_Buy_Vps_Unmanaged_Linux

Description:

Buys an unmanaged linux VPS.

Version: 1.0

Parameters:

type (**string**): Type. The parameter is required. Accepted parameter values: "V-Server Pro", "V-Server Pro Plus", "V-Server Elite".

period (**int**): Contratation period (months). The parameter is required. Accepted parameter values: "1", "3", "12".

vcpusCount (**int**): Number of vcpus. The parameter is required. Accepted parameter values: "1", "2", "4".

diskType (**string**): Disk type. Use the command 'Billing_GetConfigurableVpsOptions' to get the list of available disk types. The parameter is required.

diskImage (**string**): Disk image. Use the command 'Billing_GetConfigurableVpsOptions' to get the list of available disk images. The parameter is required.

Response:

type: **boolean**

Example:

'None'

Billing_Buy_Vps_Managed_Windows

Description:

Buys a managed windows VPS.

Version: 1.0

Parameters:

type (**string**): Type. The parameter is required. Accepted parameter values: "V-Server Pro", "V-Server Pro Plus", "V-Server Elite".

period (**int**): Contratation period (months). The parameter is required. Accepted parameter values: "1", "3", "12".

vcpusCount (**int**): Number of vcpus. The parameter is required. Accepted parameter values: "1", "2", "4".

diskType (**string**): Disk type. Use the command 'Billing_GetConfigurableVpsOptions' to get the list of available disk types. The parameter is required.

Response:

type: **boolean**

Example:

'None'

Billing_Buy_Vps_Managed_Linux

Description:

Buys a managed linux VPS.

Version: 1.0

Parameters:

type (**string**): Type. The parameter is required. Accepted parameter values: "V-Server Pro", "V-Server Pro Plus", "V-Server Elite".

period (**int**): Contratation period (months). The parameter is required. Accepted parameter values: "1", "3", "12".

vcpusCount (**int**): Number of vcpus. The parameter is required. Accepted parameter values: "1", "2", "4".

diskType (**string**): Disk type. Use the command 'Billing_GetConfigurableVpsOptions' to get the list of available disk types. The parameter is required.

diskImage (**string**): Disk image. Use the command 'Billing_GetConfigurableVpsOptions' to get the list of available disk images. The parameter is required.

Response:

type: **boolean**

Example:

'None'

Billing_Buy_Sms

Description:

Buy a new SMS account.

1.0 -> 1.1: Improved simulation mode.

1.1 -> 1.2: COMMAND_BILLING_CREDIT error.

Version: 1.2

Parameters:

account (**string**): Sms account number. The parameter is required.

credit (**int**): Initial credit. The parameter is required. Parameter value must be a valid integer. Accepted parameter values: "50","100","1000","5000","20000".

Response:

type: **void**

Billing_Buy_Multihosting

Description:

Buy a new multihosting.

1.2 -> 1.3: Improved simulation mode.

1.3 -> 1.4: COMMAND_BILLING_CREDIT error.

Version: 1.4

Parameters:

period (**int**): Contration period (years). The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 5 inclusive.

serverOs (**string**): Host server operating system. The parameter is required. Accepted parameter values: "LINUX","WINDOWS".

Response:

type: **void**

Billing_GetConfigurableVpsOptions

Description:

Gets configurable options for buying a VPS.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **struct**

Example:

'None'

Billing_Price_Domain

Description:

Get price for a domain name (register, transfer or renew).

1.0 -> 1.1: New TLDs are supported.

Version: 1.1

Parameters:

tld (**string**): Domain name TLD. Example: com.es (as is). The parameter is required.

period (**int**): Registration period (years). The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 10 inclusive.

action (**string**): Action done over domain. Different actions may have different prices. The parameter is required. Accepted parameter values: "create","renew","transfer".

whoisProtection (**bool**): Default is false. Set true to include domain whois protection price. The parameter is optional. Parameter value must be a boolean (true or false).

currency (**string**): Currency. Default: EUR. The parameter is optional. Accepted parameter values: "USD","EUR".

Response:

type: **float**

Example:

'None'

Billing_Price_Hosting

Description:

Get price for a hosting (new or renew).

Version: 1.2

Parameters:

period (**int**): Contratation period (months). The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 120 inclusive.

hostingType (**int**): Hosting type. 1 = hosting personal, 2 = hosting professional, 3 = hosting professional plus, 10 = Correo10, 810 = hosting blog. The parameter is required. Accepted parameter values: "1","2","3","10","810".

serverOs (**string**): Host server operating system. The parameter is required. Accepted parameter values: "LINUX","WINDOWS".

action (**string**): Action done over domain. Different actions may have different prices. The parameter is required. Accepted parameter values: "create","renew".

currency (**string**): Currency. Default: EUR. The parameter is optional. Accepted parameter values: "USD","EUR".

Response:

type: **float**

Example:

'None'

Billing_Price_Vps_Unmanaged_Windows

Description:

Gets the price of an unmanaged windows VPS.

Version: 1.0

Parameters:

type (**string**): Type. The parameter is required. Accepted parameter values: "V-Server Pro","V-Server Pro Plus","V-Server Elite".

period (**int**): Contratation period (months). The parameter is required. Accepted parameter values: "1","3","12".

vcpusCount (**int**): Number of vcpus. The parameter is required. Accepted parameter values: "1","2","4".

diskType (**string**): Disk type. Use the command 'Billing_GetConfigurableVpsOptions' to get the list of available disk types. The parameter is required.

diskImage (**string**): Disk image. Use the command 'Billing_GetConfigurableVpsOptions' to get the list of

available disk images. The parameter is required.

action (**string**): Action done over domain. Different actions may have different prices. The parameter is required. Accepted parameter values: "create","renew".

currency (**string**): Currency. Default: EUR. The parameter is optional. Accepted parameter values: "USD","EUR".

Response:

type: **float**

Example:

'None'

Billing_Price_Vps_Unmanaged_Linux

Description:

Gets the price of an unmanaged linux VPS.

Version: 1.0

Parameters:

type (**string**): Type. The parameter is required. Accepted parameter values: "V-Server Pro","V-Server Pro Plus","V-Server Elite".

period (**int**): Contratation period (months). The parameter is required. Accepted parameter values: "1","3","12".

vcpusCount (**int**): Number of vcpus. The parameter is required. Accepted parameter values: "1","2","4".

diskType (**string**): Disk type. Use the command 'Billing_GetConfigurableVpsOptions' to get the list of available disk types. The parameter is required.

action (**string**): Action done over domain. Different actions may have different prices. The parameter is required. Accepted parameter values: "create","renew".

currency (**string**): Currency. Default: EUR. The parameter is optional. Accepted parameter values: "USD","EUR".

Response:

type: **float**

Example:

'None'

Billing_Price_Vps_Managed_Windows

Description:

Gets the price of a managed windows VPS.

Version: 1.0

Parameters:

type (**string**): Type. The parameter is required. Accepted parameter values: "V-Server Pro","V-Server Pro Plus","V-Server Elite".

period (**int**): Contratation period (months). The parameter is required. Accepted parameter values: "1","3","12".

vcpusCount (**int**): Number of vcpus. The parameter is required. Accepted parameter values: "1","2","4".

diskType (**string**): Disk type. Use the command 'Billing_GetConfigurableVpsOptions' to get the list of available disk types. The parameter is required.

action (**string**): Action done over domain. Different actions may have different prices. The parameter is required. Accepted parameter values: "create","renew".

currency (**string**): Currency. Default: EUR. The parameter is optional. Accepted parameter values: "USD","EUR".

Response:

type: **float**

Example:

'None'

Billing_Price_Vps_Managed_Linux

Description:

Gets the price of a managed linux VPS.

Version: 1.0

Parameters:

type (string): Type. The parameter is required. Accepted parameter values: "V-Server Pro","V-Server Pro Plus","V-Server Elite".

period (int): Contratation period (months). The parameter is required. Accepted parameter values: "1","3","12".

vcpusCount (int): Number of vcpus. The parameter is required. Accepted parameter values: "1","2","4".

diskType (string): Disk type. Use the command 'Billing_GetConfigurableVpsOptions' to get the list of available disk types. The parameter is required.

action (string): Action done over domain. Different actions may have different prices. The parameter is required. Accepted parameter values: "create","renew".

currency (string): Currency. Default: EUR. The parameter is optional. Accepted parameter values: "USD","EUR".

Response:

type: float

Example:

'None'

Billing_Price_Sms

Description:

Get price for a SMS account (new or renew).

Version: 1.0

Parameters:

credit (int): Initial credit. The parameter is required. Parameter value must be a valid integer. Accepted parameter values: "50","100","1000","5000","20000".

action (string): Action done over domain. Different actions may have different prices. The parameter is required. Accepted parameter values: "create","renew".

currency (string): Currency. Default: EUR. The parameter is optional. Accepted parameter values: "USD","EUR".

Response:

type: float

Example:

'None'

Billing_Price_Multihosting

Description:

Get price for a multihosting (new or renew).

Version: 1.2

Parameters:

period (**int**): Contratation period (years). The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 5 inclusive.

serverOs (**string**): Host server operating system. The parameter is required. Accepted parameter values: "LINUX","WINDOWS".

action (**string**): Action done over domain. Different actions may have different prices. The parameter is required. Accepted parameter values: "create","renew".

currency (**string**): Currency. Default: EUR. The parameter is optional. Accepted parameter values: "USD","EUR".

Response:

type: **float**

Example:

'None'

Billing_Autorenew_GetAll

Description:

Returns renewable services with autorenovation info.

1.0 -> 1.1 Return only renewable services.

1.1 -> 1.2 Added domain parameter to filter results

Version: 1.2

Parameters:

currency (**string**): Currency. Default: EUR. The parameter is optional. Accepted parameter values: "USD","EUR".

showRenovationPeriods (**bool**): True to add possible renovation periods (months) for each service. The parameter is optional. Parameter value must be a boolean (true or false).

domain (**string**): Domain to filter results The parameter is optional.

Response:

type: **array**

Example:

(Example too long, see web.)

Billing_Autorenew_SetOff

Description:

Set autorenovation OFF for a service. Service won't autorenew automatically at expiration date.

Version: 1.02

Parameters:

id (**int**): Service ID (as returned by Billing_Autorenew_GetAll). The parameter is required. Parameter value must be a valid integer.

Response:

type: **void**

Billing_Autorenew_SetOn

Description:

Set autorenovation ON for a service. Service will renew automatically at expiration date.

No payment is done until expiration date.

1.0 -> 1.1: Added some validation error codes for invalid paymentMethodId .

Version: 1.1

Parameters:

id (**int**): Service ID (as returned by Billing_Autorenew_GetAll). The parameter is required. Parameter value must be a valid integer.

paymentMethodId (**int**): Payment method ID (as returned by Payment_Method_GetAll). The parameter is required. Parameter value must be a valid integer.

period (**int**): Renovation period (years or months, see periodUnit parameter). Optional. The parameter is optional. Parameter value must be a valid integer. Parameter value must be between values 1 and 120 inclusive.

periodUnit (**string**): Period unit. The parameter is required. Accepted parameter values: "YEAR","MONTH".

Response:

type: **void**

Billing_Autorenew_SetNoRenewable

Description:

Set service as no-renewable.

Service won't autorenew automatically at expiration date, service expiration won't be reported at expiration date, service won't be eligible for renew.

Version: 1.00

Parameters:

id (**int**): Service ID (as returned by Billing_Autorenew_GetAll). The parameter is required. Parameter value must be a valid integer.

Response:

type: **void**

Billing_Transfer_Domain

Description:

Buy and transfer to Dinahosting an existing domain name.

Some domains require an auth code to complete the transfer. There is a command for this: Api_Command_Domain_Transfer_SetAuthcode.

1.0 -> 1.1 Improved simulation mode.

1.1 -> 1.2: COMMAND_BILLING_CREDIT error.

1.2 -> 1.3: OBJECT_EXISTS and OBJECT_NOT_EXISTS errors.

1.3 -> 1.4: New TLDs are supported.

1.4 -> 1.5: New contact keys (RegistrantIdentification, AdminIdentification, TechIdentification, BillingIdentification) - required for esNic domain validation.

EsNic domain validation for technical contact: must be a natural person

Version: 1.5

Parameters:

domain (**string**): Domain name. The parameter is required.

period (**int**): Registration period (years). Default: 1 year. The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 10 inclusive.

contacts (**struct**): Array containing contacts (see Domain_Contacts_GetAll). Optional, but many of the tlds require registrant information (see Billing_Transfer_GetRequirements). The parameter is optional. Parameter value must be a valid contacts.

dns (**array**): Array containing DNS strings (see Domain_Dns_Get). Optional. The parameter is optional. Parameter value must be a valid array of 2-8 unique DNS.

whoisProtection (**bool**): Default is false. Set true to buy domain whois protection. Is activated immediately after transfer this domain. The parameter is optional. Parameter value must be a boolean (true or false).

paymentMethodType (*string*): Default is saldo. Set it to "bono" to use that payment Method. The parameter is optional. Accepted parameter values: "saldo", "bono".

Response:
type: *void*

Billing_Transfer_GetRequirements

Description:
Gets transfer requirements.
Version: 1.0

Parameters:
This command doesn't accept any parameters

Response:
type: *struct*
Example:
'None'

Billing_Help_DomainExtraData

Description:
Get extraData structure information.
Version: 1.0

Parameters:
action (*string*): Action that might need extraData. The parameter is required. Accepted parameter values: "create", "transfer".
tld (*string*): Domain name TLD. Example: com.es (as is). The parameter is optional.

Response:
type: *struct*
Example:
'None'

Billing_Period_Domain

Description:
Get valid contratation periods (years) for each domain TLD and action.
1.1 -> 1.2: New TLDs are supported.
Version: 1.2

Parameters:
action (*string*): Action done over domain. Different actions may have different periods. The parameter is required. Accepted parameter values: "create", "renew", "transfer".
tld (*string*): Domain name TLD. Example: com.es (as is). The parameter is optional.

Response:
type: *struct*
Example:
(Example too long, see web.)

Billing_Period_Hosting

Description:

Get valid contratation periods (years) for each hosting type.

Version: 1.0

Parameters:

action (**string**): Action done over hosting. Different actions may have different periods. The parameter is required. Accepted parameter values: "create", "renew".

Response:

type: **struct**

Example:

```
array('1' => array(1,2,3,5,10),
'2' => array(1,2,3,5,10),
'3' => array(1,2,3,5,10),
'419' => array(1,2,3,5,10),
'425' => array(1,2,3,5,10),
'431' => array(1,2,3,5,10),
'436' => array(1,2,3,5,10),
'470' => array(1,2,3,5,10),
'498' => array(1,2,3,5,10),
)
```

Billing_Period_Vps

Description:

Gets the selectable billing periods for VPS.

Version: 1.0

Parameters:

action (**string**): Action done over VPS. Different actions may have different periods. The parameter is required. Accepted parameter values: "create", "renew".

Response:

type: **struct**

Example:

```
'None'
```

Billing_Period_Multihosting

Description:

Get valid contratation periods (years) for a multihosting.

Version: 1.0

Parameters:

action (**string**): Action done over multihosting. Different actions may have different periods. The parameter is required. Accepted parameter values: "create", "renew".

Response:

type: **struct**

Example:

```
array('mh' => array(1,2,3,4,5),
)
```


Billing_NoRenewable_GetAll

Description:

Returns no-renewable services list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

'None'

Billing_NoRenewable_SetRenewable

Description:

Set service as renewable. Service expiration will be reported at expiration date, service will be eligible for renew.

Service can be autorenewed but you must set autorenew on (see Billing_Autorenew_SetOn).

Version: 1.0

Parameters:

id (**int**): Service ID (as returned by Billing_NoRenewable_GetAll). The parameter is required. Parameter value must be a valid integer.

Response:

type: **void**

Dedicated commands

Dedicated_Hosting_GetSpace

Description:

Returns used hosting space.
 Only for managed dedicated servers.
 Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.
domainName (string): Hosting domain name. The parameter is required.

Response:

type: **struct**

Example:

```
array('total_space' => 2,
'space_limit' => 2000,
'homes_space' => 0,
'web_space' => 1.537109375,
'webmail_space' => 0,
'bds_space' => 0.0478515625,
'mail_space' => 0,
'ftp_space' => 0,
'others_space' => 0,
)
```

Dedicated_Hosting_Activate

Description:

Activates an existing but inactive hosting.
 Only for managed dedicated servers.
 Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.
domainName (string): Hosting domain name. The parameter is required.

Response:

type: **void**

Dedicated_Hosting_GetAll

Description:

Returns existing hostings on dedicated.
 Only for managed dedicated servers.
 Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.
onlyActiveHostings (bool): True to add filter: return only active hostings. False or empty, execute without

filter. The parameter is optional. Parameter value must be a boolean (true or false).

Response:

type: **array**

Example:

```
array('probando2.shiai.es','probandohosting.com','aaaaaaaa.es','bbbbbb.com','154fdsa1f.com','pruebahostin
gdw27.com')
```

Dedicated_Hosting_Delete

Description:

Deletes an existing hosting.

Only for managed dedicated servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

domainName (**string**): Hosting domain name. The parameter is required.

Response:

type: **void**

Dedicated_Hosting_Deactivate

Description:

Deactivates an existing and active hosting.

Only for managed dedicated servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

domainName (**string**): Hosting domain name. The parameter is required.

Response:

type: **void**

Dedicated_Hosting_GetSetupName

Description:

Returns hosting setup name.

Only for managed dedicated servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

domainName (**string**): Hosting domain name. The parameter is required.

Response:

type: **string**

Example:

'None'

Dedicated_Hosting_Create

Description:

Creates a new hosting.

Only for managed dedicated servers.

1.0 -> 1.1: Added an existing setup name validation.

Version: 1.1

Parameters:

serverName (*string*): Server name. The parameter is required.

domainName (*string*): Hosting domain name. The parameter is required.

setupName (*string*): Existing setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

setZones (*bool*): True to set new zones, false to leave them unchanged. Default: true. The parameter is required. Parameter value must be a boolean (true or false).

Response:

type: *void*

Dedicated_Hosting_ChangeSetup

Description:

Changes setup of a existing hosting.

Only for managed dedicated servers.

Version: 1.0

Parameters:

serverName (*string*): Server name. The parameter is required.

domainName (*string*): Hosting domain name. The parameter is required.

setupName (*string*): Existing setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

Response:

type: *void*

Dedicated_GetDataTransferInfo

Description:

Returns data transfer summary.

Version: 1.0

Parameters:

serverName (*string*): Server name. The parameter is required.

Response:

type: *struct*

Example:

(Example too long, see web.)

Dedicated_GetMonitorizedPorts

Description:

Returns monitorized ports with their status.

Only for unmanaged servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **array**

Example:

(Example too long, see web.)

Dedicated_GetUsedSpace

Description:

Returns used space.

Only for managed dedicated servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

```
array('total_space' => 12,
'space_limit' => 0,
'homes_space' => 0,
'web_space' => 12.287109375,
'webmail_space' => 0,
'bds_space' => 0.095703125,
'mail_space' => 0,
'ftp_space' => 0,
'others_space' => 0,
)
```

Dedicated_Monitorization_Activate

Description:

Activate monitorization.

Only for non-managed dedicated servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

emails (**array**): Array of emails. The parameter is required.

Response:

type: **void**

Dedicated_Monitorization_Deactivate

Description:

Deactivate monitorization.

Only for non-managed dedicated servers.

Version: 1.0

Parameters:

serverName (*string*): Server name. The parameter is required.

Response:

type: *void*

Dedicated_Monitorization_Get

Description:

Returns monitorization configuration.

Only for non-managed dedicated servers.

Version: 1.0

Parameters:

serverName (*string*): Server name. The parameter is required.

Response:

type: *struct*

Example:

```
array('emails' => array("),
'activated' => false,
)
```

Dedicated_MailReport_SetOff

Description:

Deactivate consumption email report.

Only for managed dedicated servers.

Version: 1.0

Parameters:

serverName (*string*): Server name. The parameter is required.

Response:

type: *void*

Dedicated_MailReport_Get

Description:

Returns consumption email report status.

Only for managed dedicated servers.

Version: 1.0

Parameters:

serverName (*string*): Server name. The parameter is required.

Response:

type: *struct*

Example:

```
array('periodicity' => 'never',
'emailTo' => ",
)
```

Dedicated_MailReport_Set

Description:

Set consumption email report.
Only for managed dedicated servers.
Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.
emailTo (**string**): Destination emails separated with commas. The parameter is required. Parameter value must be a valid email address.
periodicity (**string**): Report periodicity. The parameter is required. Accepted parameter values: "daily", "weekly", "monthly".

Response:

type: **void**

Dedicated_Services_GetAll

Description:

Returns services status.
Only for managed dedicated servers.
Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

```
array('iis' => 'started',
'pop3' => 'started',
'smtp' => 'started',
'ftp' => 'started',
'mysql' => 'started',
'web' => 'started',
)
```

Dedicated_Services_ChangeStatus

Description:

Change server service status.
Only for managed dedicated servers.
Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.
serviceName (**string**): Service name. The parameter is required. Accepted parameter values: "web", "mysql", "pop3", "smtp", "ftp", "dinascanner".

serviceAction (**string**): Action over service. The parameter is required. Accepted parameter values: "start", "stop", "activate", "deactivate", "restart".

Response:

type: **void**

Dedicated_GetLicenses

Description:

Returns licenses information.

Only for managed dedicated servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

```
array('totalLicenses' => 25,
'availableLicenses' => 19,
'usedLicenses' => 6,
)
```

Dedicated_GetBandwidthConsumption

Description:

Returns bandwidth consumption summary.

Only for non-managed dedicated servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

month (**int**): Month number. The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 12 inclusive.

year (**int**): Year. The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 2002 and 2012 inclusive.

Response:

type: **struct**

Example:

(Example too long, see web.)

Dedicated_GetServerInfo

Description:

Returns dedicated server info.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

(Example too long, see web.)

Dedicated_Kvm_Get

Description:

Returns KVM configuration.

Only for non-managed dedicated servers.

1.0 -> 1.1: new keys: user, password

Version: 1.1

Parameters:

serverName (**string**): Server name The parameter is required.

Response:

type: **struct**

Example:

```
array('user' => '6pri',
      'password' => 'yeqyr8',
      'ip' => '10.10.10.10',
    )
```

Dedicated_Kvm_Unmount

Description:

Unmount KVM.

Only for non-managed dedicated servers.

Version: 1.0

Parameters:

serverName (**string**): Server name The parameter is required.

allowed_ip (**string**): IP that will be granted access. If it's missing, we'll use the requesting client IP. The parameter is optional. Parameter value must be a valid IP v4 address.

Response:

type: **void**

Dedicated_Kvm_Mount

Description:

Mount KVM and get public IP.

Only for non-managed dedicated servers.

1.0 -> 1.1: returns mounted IP

1.1 -> 1.2: new parameter: allowed_ip

Version: 1.2

Parameters:

serverName (**string**): Server name The parameter is required.

allowed_ip (**string**): IP that will be granted access. If it's missing, we'll use the requesting client IP. The parameter is optional. Parameter value must be a valid IP v4 address.

Response:

type: **string**

Example:

'None'

Dedicated_HostingSetup_Update

Description:

Updates an existing user custom hosting setup.

Only for managed dedicated servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

setupName (**string**): Existing setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

options (**struct**): New setup options (as returned by Dedicated_HostingSetup_Get). The parameter is required.

Response:

type: **void**

Dedicated_HostingSetup_GetCustomSetups

Description:

Returns all user custom hosting setups.

Only for managed dedicated servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

(Example too long, see web.)

Dedicated_HostingSetup_GetAll

Description:

Returns all available hosting setups.

Only for managed dedicated servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

(Example too long, see web.)

Dedicated_HostingSetup_GetOptions

Description:

Returns all available hosting setup options.
 Only for managed dedicated servers.
 Version: 1.0

Parameters:

`serverName` (`string`): Server name. The parameter is required.

Response:

type: `struct`

Example:

(Example too long, see web.)

Dedicated_HostingSetup_Delete

Description:

Deletes a existing user custom hosting setup.
 Only for managed dedicated servers.
 Version: 1.0

Parameters:

`serverName` (`string`): Server name. The parameter is required.

`setupName` (`string`): Setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

Response:

type: `void`

Dedicated_HostingSetup_Create

Description:

Creates a new user custom hosting setup.
 Only for managed dedicated servers.
 Version: 1.0

Parameters:

`serverName` (`string`): Server name. The parameter is required.

`setupName` (`string`): Setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

`options` (`struct`): Setup options (as returned by `Dedicated_HostingSetup_Get`). The parameter is required.

Response:

type: `void`

Dedicated_HostingSetup_Get

Description:

Returns an user custom hosting setup.
 Only for managed dedicated servers.
 Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

setupName (string): Setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

Response:

type: **struct**

Example:

(Example too long, see web.)

Dedicated_HostingSetup_GetDhSetups

Description:

Returns all DH default hosting setups.

Only for managed dedicated servers.

Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: **struct**

Example:

(Example too long, see web.)

Dedicated_GetTransferValue

Description:

Returns max data transfer value (MBs).

Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: **int**

Example:

1500

Dedicated_Control_GetApacheProcesses

Description:

Returns apache active processes information.

Only for linux managed dedicated servers.

Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: **array**

Example:

(Example too long, see web.)

Dedicated_Control_GetSystemLoad

Description:

Returns cpu load by hosting information.
 Only for managed dedicated servers.
 Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: **struct**
 Example:
 (Example too long, see web.)

Dedicated_Control_GetWebserverStatus

Description:

Returns webserver information.
 Only for managed dedicated servers.
 Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: **struct**
 Example:
 (Example too long, see web.)

Dedicated_Control_GetSystemStatus

Description:

Returns sysyem information.
 Only for managed dedicated servers.
 Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: **struct**
 Example:
 (Example too long, see web.)

Dedicated_Control_KillMysqlProcess

Description:

Kill mysql active processes .
 Only for managed dedicated servers.
 Version: 1.0

Parameters:

serverName ([string](#)): Server name. The parameter is required.

pid ([int](#)): Process id. The parameter is required. Parameter value must be a valid integer.

Response:

type: [void](#)

Dedicated_Control_GetMysqlProcesses

Description:

Returns mysql active processes information.

Only for managed dedicated servers.

Version: 1.0

Parameters:

serverName ([string](#)): Server name. The parameter is required.

Response:

type: [array](#)

Example:

```
array(array('info' => 'show',
'id' => 6,
'host' => 'gdc.dinasever.com:37883',
'ddbb' => 'NULL',
'user' => 'root',
'command' => 'Query',
'time' => 'NULL',
'status' => 'NULL',
))
```

Dedicated_Control_GetCpuLoadByHosting

Description:

Returns cpu load by hosting information.

Only for managed dedicated servers.

Version: 1.0

Parameters:

serverName ([string](#)): Server name. The parameter is required.

Response:

type: [array](#)

Example:

```
array(array('hosting' => 'others',
'used_cpu' => 100,
'percent_used_cpu' => 100,
))
```

Dedicated_Nfs_Get

Description:

Returns NFS server name

Version: 1.0

Parameters:

serverName (*string*): Server name The parameter is required.

Response:

type: *struct*

Example:

'None'

Dedicated_GetSpaceAndTransferReportPerHosting

Description:

Returns a summary of the space and transfer data per hosting.

Version: 1.0

Parameters:

serverName (*string*): Server name. The parameter is required.

Response:

type: *struct*

Example:

'None'

Dedicated_ForVps_GetServerInfo

Description:

Returns the information of a dedicated server.

Version: 1.0

Parameters:

serverName (*string*): Server name. The parameter is required.

Response:

type: *struct*

Example:

'None'

Dedicated_ForVps_GetTicketStatus

Description:

Returns the status information about creating, updating and modifying VPS in a dedicated server.

Version: 1.0

Parameters:

serverName (*string*): Server name. The parameter is required.

ticketId (*int*): Ticket ID. The parameter is required. Parameter value must be a valid integer.

Response:

type: *array*

Example:

'None'

Dedicated_ForVps_Vps_Update

Description:

Generates and returns a ticket for updating a VPS in a dedicated server. The ticket status can be consulted with the command '\Dedicated_ForVps_GetTicketStatus\'.

Please note this command has a delayed execution and it'll return SUCCESS_PENDING code on success and a ticket id (integer) on the data field. Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

vpsHostname (string): VPS hostname. The parameter is required.

alias (string): VPS alias. The parameter is optional.

description (string): VPS description. The parameter is optional.

vcpusCount (int): Number of vcpus. The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 4 inclusive.

ram (int): RAM (MB). Use the command 'Dedicated_ForVps_GetServerInfo' to check the available RAM. The parameter is required. Parameter value must be a valid integer. Parameter value must be greater or equal than 512.

diskSpace (int): Disk space (GB). Use the command 'Dedicated_ForVps_GetServerInfo' to check the available space. The parameter is required. Parameter value must be a valid integer. Parameter value must be greater or equal than 10.

transferLimit (int): Transfer limit (GB). Set empty for unlimited. Use the command 'Dedicated_ForVps_GetServerInfo' to check the available transfer limit. The parameter is optional.

Response:

type: int

Example:

'None'

Dedicated_ForVps_Vps_Activate

Description:

Activates a VPS in a dedicated server.

Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

vpsHostname (string): VPS hostname. The parameter is required.

Response:

type: void

Dedicated_ForVps_Vps_Create_Unmanaged

Description:

Generates and returns a ticket for creating an unmanaged VPS in a dedicated server. The ticket status can be consulted with the command '\Dedicated_ForVps_GetTicketStatus\'.

Please note this command has a delayed execution and it'll return SUCCESS_PENDING code on success and a ticket id (integer) on the data field. Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

alias (string): VPS alias. The parameter is optional.

description (string): VPS description. The parameter is optional.

diskImage (**string**): Image disk. Use the command 'Dedicated_ForVps_Vps_GetTypes' to get a list of available images. The parameter is required.

vcpusCount (**int**): Number of vcpus. The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 4 inclusive.

ram (**int**): RAM (MB). Use the command 'Dedicated_ForVps_GetServerInfo' to check the available RAM. The parameter is required. Parameter value must be a valid integer. Parameter value must be greater or equal than 512.

diskSpace (**int**): Disk space (GB). Use the command 'Dedicated_ForVps_GetServerInfo' to check the available space. The parameter is required. Parameter value must be a valid integer. Parameter value must be greater or equal than 10.

transferLimit (**int**): Transfer limit (GB). Set empty for unlimited. Use the command 'Dedicated_ForVps_GetServerInfo' to check the available transfer limit. The parameter is optional.

Response:

type: **int**

Example:

'None'

Dedicated_ForVps_Vps_Create_Managed

Description:

Generates and returns a ticket for creating a managed VPS in a dedicated server. The ticket status can be consulted with the command '\Dedicated_ForVps_GetTicketStatus\'. Please note this command has a delayed execution and it'll return SUCCESS_PENDING code on success and a ticket id (integer) on the data field. Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

alias (**string**): VPS alias. The parameter is optional.

description (**string**): VPS description. The parameter is optional.

diskImage (**string**): Image disk. Use the command 'Dedicated_ForVps_Vps_GetTypes' to get a list of available images. The parameter is required.

vcpusCount (**int**): Number of vcpus. The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 4 inclusive.

ram (**int**): RAM (MB). Use the command 'Dedicated_ForVps_GetServerInfo' to check the available RAM. The parameter is required. Parameter value must be a valid integer. Parameter value must be greater or equal than 512.

diskSpace (**int**): Disk space (GB). Use the command 'Dedicated_ForVps_GetServerInfo' to check the available space. The parameter is required. Parameter value must be a valid integer. Parameter value must be greater or equal than 10.

transferLimit (**int**): Transfer limit (GB). Set empty for unlimited. Use the command 'Dedicated_ForVps_GetServerInfo' to check the available transfer limit. The parameter is optional.

Response:

type: **int**

Example:

'None'

Dedicated_ForVps_Vps_GetAll

Description:

It returns the VPS list of the dedicated server.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

'None'

Dedicated_ForVps_Vps_Delete

Description:

Generates and returns a ticket for deleting a VPS in a dedicated server.

The ticket status can be consulted with the command '\Dedicated_ForVps_GetTicketStatus\'.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

vpsHostname (**string**): VPS hostname. The parameter is required.

Response:

type: **void**

Dedicated_ForVps_Vps_Deactivate

Description:

Desactivates a VPS in a dedicated server.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

vpsHostname (**string**): VPS hostname. The parameter is required.

Response:

type: **void**

Dedicated_ForVps_Vps_GetTypes

Description:

Returns the types of VPS, based on the type of administration and disk image.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

'None'

Dedicated_PowerStatus_Restart

Description:

Restart server.

Only for non-managed dedicated servers.

Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: void

Domain commands

Domain_Dnss_Get

Description:

Returns array with DNS of domain.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

Response:

type: **struct**

Example:

```
array('Dns1' => 'ns2.gestiondecuenta.com',
'Dns2' => 'ns.gestiondecuenta.com',
)
```

Domain_Dnss_Set

Description:

Sets new DNS of domain.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

dnss (array): Array containing DNS strings. The parameter is required. Parameter value must be a valid array of 2-8 unique DNS.

Response:

type: **void**

Domain_WhoisPrivacy_Get

Description:

Returns domain whois privacy configuration.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

Response:

type: **struct**

Example:

```
array('activated' => true,
'redirection' => 'informedk_org562@privacidadwhois.com',
)
```

Domain_WhoisPrivacy_Set

Description:

Configures domain whois privacy.

Version: 1.0

Parameters:

domain ([string](#)): Domain name. The parameter is required.

redirectionEmail ([string](#)): Email direction where received emails are sent to. The parameter is optional. Parameter value must be a valid email address.

enable ([boolean](#)): Enables or disables whois protection. The parameter is optional. Parameter value must be a boolean (true or false).

Response:

type: [void](#)

Domain_GetAuthcode

Description:

Returns authcode of domain for outgoing transfer.

Version: 1.0

Parameters:

domain ([string](#)): Domain name. The parameter is required.

Response:

type: [string](#)

Example:

`'BqDCrmqJ788}'*~'`

Domain_PanelIndependentAccess_SetPassword

Description:

Set a new password for domain panel independent access.

Version: 1.1

Parameters:

domain ([string](#)): Domain name. The parameter is required.

newPassword ([string](#)): New password. The parameter is required.

Response:

type: [void](#)

Domain_CheckForTransfer

Description:

Check if a domain name is available for transfer to Dinahosting.

Returns true if domain is registered but not in Dinahosting.

This doesn't guarantee a successful transfer.

Version: 1.1

Parameters:

domain ([string](#)): Domain name. The parameter is required.

Response:

 type: **bool**

Example:

false

Domain_Status_Lock

Description:

Locks domain status.

Version: 1.0

Parameters:
domain (**string**): Domain name. The parameter is required.

Response:

 type: **void**

Domain_Status_Get

Description:

Returns status of domain.

Version: 1.0

Parameters:
domain (**string**): Domain name. The parameter is required.

Response:

 type: **string**

Example:

'clientDeleteProhibited, clientTransferProhibited'

Domain_Status_Unlock

Description:

Unlocks domain status.

Version: 1.0

Parameters:
domain (**string**): Domain name. The parameter is required.

Response:

 type: **void**

Domain_Status_IsLocked

Description:

This commands checks domain status and returns boolean true if domain is currently locked.

Version: 1.0

Parameters:
domain (**string**): Domain name. The parameter is required.

Response:

 type: **bool**

Example:

true

Domain_Contacts_SetAll

Description:

Sets new contacts of domain.

Version: 1.1

Parameters:
domain (**string**): Domain name. The parameter is required.

contacts (**struct**): Array containing contacts (see Domain_Contacts_GetAll). The parameter is required. Parameter value must be a valid contacts.

Response:

 type: **void**

Domain_Contacts_GetAll

Description:

Returns array with contacts of domain.

1.0 -> 1.1: Added Fax key.

Version: 1.1

Parameters:
domain (**string**): Domain name. The parameter is required.

Response:

 type: **struct**

Example:

(Example too long, see web.)

Domain_Contacts_Get

Description:

Returns array with contacts of domain. Only returns contacts of one type (example: registrant).

1.0 -> 1.1: Added Fax key.

Version: 1.1

Parameters:
domain (**string**): Domain name. The parameter is required.

contactType (**string**): Contact type (registrant, admin, billing or technical). The parameter is required. Accepted parameter values: "registrant","admin","billing","tech".

Response:

 type: **struct**

Example:

(Example too long, see web.)

Domain_Contacts_Set

Description:

Sets new contacts of domain. Only updates one type of contacts (example: billing).
Version: 1.1

Parameters:

domain (*string*): Domain name. The parameter is required.
contactType (*string*): Contact type (registrant, admin, billing or technical). The parameter is required.
 Accepted parameter values: "registrant","admin","billing","tech".
contacts (*struct*): Array containing contacts (see Domain_Contacts_Get for format). The parameter is required. Parameter value must be a valid contacts.

Response:

type: *void*

Domain_Contacts_GetRegistrantVerificationInfo

Description:

Gets registrant verification info.
Version: 1.0

Parameters:

domain (*string*): Domain name. The parameter is required.

Response:

type: *struct*
 Example:
 'None'

Domain_UrlShortener_Activate

Description:

Activates shortener on a domain.
Version: 1.0

Parameters:

domain (*string*): Domain. The parameter is required.

Response:

type: *void*

Domain_UrlShortener_GetAll

Description:

Returns shortened URLs on a domain.
Version: 1.0

Parameters:

domain (*string*): Domain. The parameter is required.

Response:

type: **struct**

Example:

'None'

Domain_UrlShortener_Delete

Description:

Deletes a shortened URL on a domain

Version: 1.0

Parameters:

domain (**string**): Domain. The parameter is required.

keyword (**string**): Keyword of the shortened URL to be deleted. The parameter is required.

Response:

type: **void**

Domain_UrlShortener_Deactivate

Description:

Deactivates shortener on a domain.

Use with caution: it deletes all the shortened URLs created under the domain.

Version: 1.0

Parameters:

domain (**string**): Domain. The parameter is required.

Response:

type: **void**

Domain_UrlShortener_Create

Description:

Creates a new shortened URL on a domain.

Use with caution: shortened URLs on a domain make traffic being redirected to the shortener.

Version: 1.0

Parameters:

domain (**string**): Domain. The parameter is required.

url (**string**): URL to be shorten. The parameter is required. Parameter value must be a valid URL.

title (**string**): URL title. The parameter is optional.

Response:

type: **void**

Domain_GetInfoDomain

Description:

Returns registry info of domain.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

Response:

type: **struct**

Example:

(Example too long, see web.)

Domain_Redirection_Set301

Description:

Sets 301 URL Redirecion on whole domain or domain zone.

1.0 -> 1.1: Optionally now can add a subdomain redirection.

Version: 1.1

Parameters:

domain (string): Domain name. The parameter is required.

url (string): URL redirection destination. The parameter is required. Parameter value must be a valid URL.

host (string): Subdomain hostname. The parameter is optional. Parameter length must be between 0 and 64 characters.

Response:

type: **void**

Domain_Redirection_GetAll

Description:

Returns all URL redirections on whole domain and domain zone redirections, if any.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

Response:

type: **array**

Example:

(Example too long, see web.)

Domain_Redirection_Delete

Description:

Delete URL redirection over whole domain.

1.0 -> 1.1: Optionally now can remove any subdomain redirections.

Version: 1.1

Parameters:

domain (string): Domain name. The parameter is required.

removeAll (bool): Set true for deleting any subdomain redirection zones. The parameter is optional. Parameter value must be a boolean (true or false).

Response:

type: **void**

Domain_Redirection_Get

Description:

Returns current URL redirection on whole domain, if any.
Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

Response:

type: **struct**

Example:

```
array('Type' => 'FRAME',
      'Url' => 'http://www.dinahosting.com',
      'Title' => "",
      'Description' => "",
      'Keywords' => "",
      )
```

Domain_Redirection_SetFrame

Description:

Sets Frame URL Redirecion on whole domain.
Version: 1.1

Parameters:

domain (string): Domain name. The parameter is required.

url (string): URL redirection framed destination. The parameter is required. Parameter value must be a valid URL.

title (string): Frame title. The parameter is optional. Parameter length must be between 0 and 255 characters.

description (string): Frame description meta. The parameter is optional. Parameter length must be between 0 and 255 characters.

keywords (string): Frame keywords meta. The parameter is optional. Parameter length must be between 0 and 255 characters.

favicon (string): Frame favicon URL. The parameter is optional. Parameter length must be between 0 and 255 characters.

viewport (string): Frame viewport meta. The parameter is optional. Parameter length must be between 0 and 255 characters.

Response:

type: **void**

Domain_Redirection_SetFrameSimple

Description:

Sets Frame Redirecion on whole domain or domain zone.
Version: 1.1

Parameters:

domain (string): Domain name. The parameter is required.

url (string): URL redirection destination. The parameter is required. Parameter value must be a valid URL.

host (string): Subdomain hostname. The parameter is optional. Parameter length must be between 0 and 64 characters.

Response:

 type: `void`

Domain_Redirection_SetStd

Description:

Sets Standard URL Redirecion on whole domain or domain zone.

1.0 -> 1.1: Optionally now can add a subdomain redirection.

Version: 1.1

Parameters:

`domain` (`string`): Domain name. The parameter is required.

`url` (`string`): URL redirection destination. The parameter is required. Parameter value must be a valid URL.

`host` (`string`): Subdomain hostname. The parameter is optional. Parameter length must be between 0 and 64 characters.

Response:

 type: `void`

Domain_GetRenovationDate

Description:

Returns expected domain deactivation date.

Version: 1.0

Parameters:

`domain` (`string`): Domain name. The parameter is required.

Response:

 type: `string`

Example:

`'2013-07-06'`

Domain_Test

Description:

Domain command Testing

Version: 1.0

Parameters:

`domain` (`string`): Domain name, for testing purposes. The parameter is required.

`optional` (`string`): An optional parameter. The parameter is optional.

Response:

 type: `struct`

Example:

`'None'`

Domain_Parking_Get

Description:

Returns parking info.

Version: 1.0

Parameters:

domain (*string*): Domain name. The parameter is required.

Response:

type: *struct*

Example:

```
array('Title' => 'Mi página en parking',
'Description' => 'Estas es la web de dinahosting',
)
```

Domain_Parking_Set

Description:

Sets domain on parking.

Version: 1.0

Parameters:

domain (*string*): Domain name. The parameter is required.

title (*string*): Title for parking webpage. The parameter is optional. Parameter length must be between 0 and 254 characters.

description (*string*): Description for parking webpage. The parameter is optional.

Response:

type: *void*

Domain_GetExpirationDate

Description:

Returns registry expiration date of domain.

Version: 1.0

Parameters:

domain (*string*): Domain name. The parameter is required.

Response:

type: *string*

Example:

```
'2014-02-10'
```

Domain_NameServer_GetAll

Description:

Returns array with registered DNS server names and IPs over domain.

Version: 1.0

Parameters:

domain (*string*): Domain name. The parameter is required.

Response:

type: `array`

Example:

```
array(array('name' => 'ns2.afiliacionweb.com',
'ip' => '85.112.29.233',
),array('name' => 'ns1.afiliacionweb.com',
'ip' => '85.112.29.232',
))
```

Domain_NameServer_Modify

Description:

Modify existing DNS server over domain.

Version: 1.0

Parameters:

`domain` (`string`): Domain name. The parameter is required.

`hostname` (`string`): Hostname. The parameter is required.

`ip` (`string`): IP Address. The parameter is required. Parameter value must be a valid IP address (v4 or v6). Keep in mind that v6 is currently experimental, might not work.

Response:

type: `void`

Domain_NameServer_Register

Description:

Register a DNS server over domain.

Version: 1.0

Parameters:

`domain` (`string`): Domain name. The parameter is required.

`hostname` (`string`): Hostname. The parameter is required.

`ip` (`string`): IP Address. The parameter is required. Parameter value must be a valid IP address (v4 or v6). Keep in mind that v6 is currently experimental, might not work.

Response:

type: `void`

Domain_NameServer_Delete

Description:

Delete a DNS server over domain.

Version: 1.0

Parameters:

`domain` (`string`): Domain name. The parameter is required.

`hostname` (`string`): Hostname. The parameter is required.

Response:

type: `void`

Domain_GetRegistrationDate

Description:

Returns registration date of domain.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

Response:

type: string

Example:

'2003-02-10'

Domain_CheckForRegister

Description:

Check if a domain name is available for register on Dinahosting.

Returns true if domain is not registered and domain is not currently in activation process on Dinahosting.

Version: 1.1

Parameters:

domain (string): Domain name. The parameter is required.

Response:

type: bool

Example:

false

Domain_Transfer_GetAuthcode

Description:

Returns authcode used for incoming domain transfer.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

Response:

type: string

Example:

'None'

Domain_Transfer_SetAuthcode

Description:

Set authcode for incoming domain transfer.

Changes won't take effect until a new transfer petition takes place.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

newAuthcode (string): New authcode. The parameter is required.

Response:

 type: **void**

Domain_Transfer_Cancel

Description:

Cancels a domain transfer.

Version: 1.0

Parameters:
domain (**string**): Domain name. The parameter is required.

Response:

 type: **void**

Domain_Transfer_Restart

Description:

Restarts a domain transfer.

Version: 1.0

Parameters:
domain (**string**): Domain name. The parameter is required.

Response:

 type: **void**

Domain_Transfer_GetStatus

Description:

Returns status of incoming domain transfer.

On transfer codes: 'WAIT_INIT','WAIT_APROB','WAIT_AUTH','WAIT_TRANSFER'

Error codes: 'KO_AUTH','FAILED','BLOCKED','REJECTED','CANCELED','DELETED','UNKNOWN'

OK codes: 'ACTIVE'

1.0 -> 1.1 Transfer codes and simulation mode.

Version: 1.1

Parameters:
domain (**string**): Domain name. The parameter is required.

Response:

 type: **string**

Example:

'None'

Domain_Zone_DeleteTypeSPF

Description:

Deletes a domain SPF type zone.

Version: 1.1

Parameters:

domain (*string*): Domain name. The parameter is required.

hostname (*string*): Hostname. The parameter is required. Parameter length must be between 0 and 64 characters.

value (*string*): Value (optional). For specifying what to delete if there are several zones under the same hostname. The parameter is optional.

Response:

type: *void*

Domain_Zone_GetTypeCname

Description:

Returns domain zones.

Version: 1.0

Parameters:

domain (*string*): Domain name. The parameter is required.

Response:

type: *array*

Example:

```
array(array('destinationHostname' => 'google.com',
'hostname' => 'preproduccion',
))
```

Domain_Zone_GetTypeA

Description:

Returns domain zones.

Version: 1.0

Parameters:

domain (*string*): Domain name. The parameter is required.

Response:

type: *array*

Example:

(Example too long, see web.)

Domain_Zone_GetTypeTXT

Description:

Returns domain zones.

Version: 1.0

Parameters:

domain (*string*): Domain name. The parameter is required.

Response:

type: *array*

Example:

```
array(array('host' => 'key_9344._domainkey',
'text' => 'Address',
))
```

Domain_Zone_GetAll

Description:

Returns domain zones.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

orderBy (string): Ordination types: no ordination, by type, by hostname. The parameter is optional. Accepted parameter values: "none", "type", "hostname".

Response:

type: array

Example:

(Example too long, see web.)

Domain_Zone_DeleteTypeAAAA

Description:

Deletes a domain AAAA type zone.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

hostname (string): Hostname. The parameter is required. Parameter length must be between 0 and 64 characters.

ip (string): IP v6 Address. The parameter is required. Parameter length must be between 0 and 39 characters. Parameter value must be a valid IP v6 address.

Response:

type: void

Domain_Zone_GetTypeMX

Description:

Returns domain zones.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

Response:

type: array

Example:

```
array(array('host' => 'SOA',
'type' => 'MX',
'address' => 'mx4.mepegotolafiesta.com.',
))
```

Domain_Zone_AddTypeTXT

Description:

Adds a new type TXT zone .
This command doesn't work with .tel domains.
Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.
hostname (string): Origin hostname. The parameter is required. Parameter length must be between 0 and 64 characters.
text (string): Text. The parameter is required.

Response:

type: void

Domain_Zone_DeleteTypeA

Description:

Deletes a domain A type zone.
Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.
hostname (string): Hostname. The parameter is required. Parameter length must be between 0 and 64 characters.
ip (string): IP v4 Address. The parameter is required. Parameter length must be between 0 and 15 characters. Parameter value must be a valid IP v4 address.

Response:

type: void

Domain_Zone_DeleteAll

Description:

Deletes domain zones of a given type.
Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.
type (string): Zone type. The parameter is required. Accepted parameter values: "A", "AAAA", "CNAME", "frame", "URL", "URL_301", "TXT", "SRV", "SPF", "MX".

Response:

type: void

Domain_Zone_Delete

Description:

Deletes a domain zone (any type except A, AAAA and SRV).
Version: 1.0

Parameters:

domain (*string*): Domain name. The parameter is required.

hostname (*string*): Hostname. The parameter is required. Parameter length must be between 0 and 64 characters.

Response:

type: *void*

Domain_Zone_AddTypeURL301

Description:

Adds a new type URL zone (standard redirection).

This command doesn't work with .tel domains.

Version: 1.0

Parameters:

domain (*string*): Domain name. The parameter is required.

hostname (*string*): Origin hostname. The parameter is required. Parameter length must be between 0 and 64 characters.

destinationUrl (*string*): Destination URL. The parameter is required. Parameter value must be a valid URL.

Response:

type: *void*

Domain_Zone_UrlShortener_Activate

Description:

Activates shortener on a subdomain.

Version: 1.0

Parameters:

domain (*string*): Domain. The parameter is required.

hostname (*string*): Hostname. The parameter is required. Parameter length must be between 0 and 64 characters.

Response:

type: *void*

Domain_Zone_UrlShortener_GetAll

Description:

Returns shortened URLs on a subdomain.

Version: 1.0

Parameters:

domain (*string*): Domain. The parameter is required.

Response:

type: *struct*

Example:

'None'

Domain_Zone_UrlShortener_Delete

Description:

Deletes a shortened URL on a subdomain
Version: 1.0

Parameters:

domain (string): Domain. The parameter is required.
keyword (string): Keyword of the shortened URL to be deleted. The parameter is required.

Response:

type: void

Domain_Zone_UrlShortener_Deactivate

Description:

Deactivates shortener on a subdomain.
Use with caution: it deletes all the shortened URLs created under the subdomain.
Version: 1.0

Parameters:

domain (string): Domain. The parameter is required.

Response:

type: void

Domain_Zone_UrlShortener_Create

Description:

Creates a new shortened URL on a subdomain.
Version: 1.0

Parameters:

domain (string): Domain. The parameter is required.
url (string): URL to be shorten. The parameter is required. Parameter value must be a valid URL.
title (string): URL title. The parameter is optional.

Response:

type: void

Domain_Zone_AddTypeSRV

Description:

Adds a new type SRV zone (service zone).
This command doesn't work with .tel domains.
1.0 -> 1.1: Improved parameter validation and documentation.
Version: 1.1

Parameters:

domain (string): Domain name. The parameter is required.
service (string): Service. The parameter is required. Accepted parameter values: "http", "ftp", "scp", "https", "ftpd", "smtp", "imap", "pop3", "imaps", "pop3s", "named", "ldap", "ssh", "dhcp", "radius", "sip", "sipfederationtls", "xmp

p-server", "xmpp-client", "jabber", "autodiscover", "sipinternaltls".

protocol (string): Protocol. The parameter is required. Accepted parameter values: "tcp", "udp", "tls".

priority (int): Priority (integer value). The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 0 and 100 inclusive.

weight (int): Weight (integer value) used when same priority. The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 0 and 100 inclusive.

port (int): Destination port number (integer value). The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 0 and 65535 inclusive.

destination (string): Destination domain . The parameter is required.

Response:

type: void

Domain_Zone_GetTypeURL301

Description:

Returns domain zones.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

Response:

type: array

Example:

```
array(array('destinationUrl' => 'http://aaa.es',
'hostname' => 'ns',
))
```

Domain_Zone_GetTypeSRV

Description:

Returns domain zones.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

Response:

type: array

Example:

```
array(array('service' => 'http',
'protocol' => 'tcp',
'priority' => 10,
'weight' => 70,
'port' => 8080,
'destination' => 'comoor.es',
),array('service' => 'http',
'protocol' => 'tcp',
'priority' => 10,
'weight' => 30,
'port' => 80,
'destination' => 'comor.es',
))
```

Domain_Zone_UpdateTypeA

Description:

Update an existing type A zone.
 This command doesn't work with .tel domains.
 Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.
hostname (string): Hostname. The parameter is required. Parameter length must be between 0 and 64 characters.
ip (string): New IP v4 Address. The parameter is required. Parameter length must be between 0 and 15 characters. Parameter value must be a valid IP v4 address.
oldIp (string): Old IP v4 Address. The parameter is optional.

Response:

type: void

Domain_Zone_GetTypeURL

Description:

Returns domain zones.
 Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

Response:

type: array
 Example:

```
array(array('destinationUrl' => 'http://www.example.com/test',
'hostname' => 'test',
))
```

Domain_Zone_AddTypeURL

Description:

Adds a new type URL zone (standard redirection).
 This command doesn't work with .tel domains.
 Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.
hostname (string): Origin hostname. The parameter is required. Parameter length must be between 0 and 64 characters.
destinationUrl (string): Destination URL. The parameter is required. Parameter value must be a valid URL.

Response:

type: void

Domain_Zone_GetTypeAAAA

Description:

Returns domain zones.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

Response:

type: array

Example:

```
array(array('ip' => '2001:470:0:76:0:0:2',
'hostname' => 'trescuatro',
))
```

Domain_Zone_DeleteTypeMX

Description:

Deletes a domain MX type zone.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

host (string): Host. The parameter is required. Accepted parameter values: "SOA", "mx1", "mx2".

address (string): Address. The parameter is required. Parameter length must be between 0 and 64 characters.

Response:

type: void

Domain_Zone_DeleteTypeSRV

Description:

Deletes a domain SRV type zone.

1.0 -> 1.1: Major bugfix.

Version: 1.1

Parameters:

domain (string): Domain name. The parameter is required.

service (string): Service. The parameter is required. Accepted parameter values: "http", "ftp", "scp", "https", "tftp", "smtp", "imap", "pop3", "imaps", "pop3s", "named", "ldap", "ssh", "dhcp", "radius", "sip", "sipfederationtls", "xmpp-server", "xmpp-client", "jabber", "autodiscover", "sipinternaltls".

protocol (string): Protocol. The parameter is required. Accepted parameter values: "tcp", "udp", "tls".

priority (int): Priority (integer value). The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 0 and 100 inclusive.

weight (int): Weight (integer value) used when same priority. The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 0 and 100 inclusive.

port (int): Destination port number (integer value). The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 0 and 65535 inclusive.

destination (string): Destination domain . The parameter is required.

Response:

type: void

Domain_Zone_AddTypeA

Description:

Adds a new type A zone.
 This command doesn't work with .tel domains.
 Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.
hostname (string): Hostname. The parameter is required. Parameter length must be between 0 and 64 characters.
ip (string): IP v4 Address. The parameter is required. Parameter length must be between 0 and 15 characters. Parameter value must be a valid IP v4 address.

Response:

type: void

Domain_Zone_AddTypeAAAA

Description:

Adds a new type AAAA zone.
 This command doesn't work with .tel domains.
 Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.
hostname (string): Hostname. The parameter is required. Parameter length must be between 0 and 64 characters.
ip (string): IP v6 Address. The parameter is required. Parameter length must be between 0 and 39 characters. Parameter value must be a valid IP v6 address.

Response:

type: void

Domain_Zone_AddTypeCname

Description:

Adds a new type CNAME zone.
 This command doesn't work with .tel domains.
 Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.
hostname (string): Origin hostname. The parameter is required. Parameter length must be between 0 and 64 characters.
destinationHostname (string): Destination hostname. The parameter is required.

Response:

type: void

Domain_Zone_DeleteTypeCname

Description:

Deletes a domain CNAME type zone.

Version: 1.0

Parameters:

domain (*string*): Domain name. The parameter is required.

hostname (*string*): Hostname. The parameter is required. Parameter length must be between 0 and 64 characters.

Response:

type: *void*

Domain_Zone_DeleteTypeFrame

Description:

Deletes a domain FRAME type zone.

Version: 1.0

Parameters:

domain (*string*): Domain name. The parameter is required.

hostname (*string*): Hostname. Set empty for deleting an entire domain redirect. The parameter is optional. Parameter length must be between 0 and 64 characters.

Response:

type: *void*

Domain_Zone_DeleteTypeTXT

Description:

Deletes a domain TXT type zone.

Version: 1.1

Parameters:

domain (*string*): Domain name. The parameter is required.

hostname (*string*): Hostname. The parameter is required. Parameter length must be between 0 and 64 characters.

value (*string*): Value (optional). For specifying what to delete if there are several zones under the same hostname. The parameter is optional.

Response:

type: *void*

Domain_Zone_DeleteTypeURL301

Description:

Deletes a domain URL 301 type zone.

Version: 1.0

Parameters:

domain (*string*): Domain name. The parameter is required.

hostname (*string*): Hostname. Set empty for deleting an entire domain redirect. The parameter is optional. Parameter length must be between 0 and 64 characters.

Response:

type: `void`

Domain_Zone_AddTypeFrame

Description:

Adds a new type FRAME zone (frame redirection).
 This command doesn't work with .tel domains.
 Version: 1.0

Parameters:

domain (`string`): Domain name. The parameter is required.
hostname (`string`): Origin hostname. The parameter is required. Parameter length must be between 0 and 64 characters.
destinationUrl (`string`): Destination URL. The parameter is required. Parameter value must be a valid URL.

Response:

type: `void`

Domain_Zone_GetTypeSPF

Description:

Returns domain zones.
This command has pending some modifications: Make response data format more friendly.
 Version: 1.0

Parameters:

domain (`string`): Domain name. The parameter is required.

Response:

type: `array`
 Example:

```
array(array('address' => 'no|||',
))
```

Domain_Zone_AddTypeMXS

Description:

Adds a new type MX simple zone.
 This command doesn't work with .tel domains.
 Version: 1.0

Parameters:

domain (`string`): Domain name. The parameter is required.
hostname (`string`): Hostname. The parameter is required. Parameter length must be between 0 and 64 characters.
ip (`string`): IP v4 Address. The parameter is required. Parameter length must be between 0 and 15 characters. Parameter value must be a valid IP v4 address.

Response:

type: `void`

Domain_Zone_DeleteTypeURL

Description:

Deletes a domain URL type zone.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

hostname (string): Hostname. Set empty for deleting an entire domain redirect. The parameter is optional.

Parameter length must be between 0 and 64 characters.

Response:

type: void

Domain_Zone_GetTypeFrame

Description:

Returns domain zones.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

Response:

type: array

Example:

```
array(array('destinationUrl' => 'http://www.dinahosting.com',
'hostname' => '@',
),array('destinationUrl' => 'http://www.dinahosting.com',
'hostname' => 'www',
))
```

Domain_Zone_UpdateTypeAAAA

Description:

Update an existing type AAAA zone.

This command doesn't work with .tel domains.

Version: 1.0

Parameters:

domain (string): Domain name. The parameter is required.

hostname (string): Hostname. The parameter is required. Parameter length must be between 0 and 64 characters.

ip (string): New IP v6 Address. The parameter is required. Parameter length must be between 0 and 39 characters. Parameter value must be a valid IP v6 address.

oldIp (string): Old IP v6 Address. The parameter is optional.

Response:

type: void

Domain_Zone_AddTypeMX

Description:

Adds a new type MX zone.

This command doesn't work with .tel domains.
The MX zone requires that a A zone already exists.
Version: 1.0

Parameters:

domain (**string**): Domain name. The parameter is required.

mxNumber (**int**): Mx number. The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 7 inclusive.

hostname (**string**): Hostname. The parameter is required. Parameter length must be between 0 and 64 characters.

Response:

type: **void**

DomainVerification commands

DomainVerification_GetPending

Description:

Returns all pending domain verifications.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: `array`

Example:

(Example too long, see web.)

Hosting commands

Hosting_GetInfo

Description:

Returns hosting webserver information with traffic and space metrics.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **struct**

Example:

(Example too long, see web.)

Hosting_Php_PhpExecutionOnHtmlIsActive

Description:

Checks if hosting can execute PHP code on HTML.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **bool**

Example:

'None'

Hosting_Php_OverwritePhpIni

Description:

Overwrite php.ini values with custom text.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

text (string): New text contents for php.ini file. The parameter is required.

Response:

type: **void**

Hosting_Php_ActivatePhpExecutionOnHtml

Description:

Allows PHP execution on HTML.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: void

Hosting_Php_OverwritePhpIniWithDefaults

Description:

Overwrite php.ini values with defaults.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: void

Hosting_Php_SetVersion

Description:

Changes hosting PHP version.

Version: 1.2 Version parameter allows any content. Availability validation of PHP version added.

Parameters:

hosting (string): Hosting name. The parameter is required.

version (string): Check available versions with Hosting_GetInfo command. The parameter is required.

Response:

type: void

Hosting_Php_DeactivatePhpExecutionOnHtml

Description:

Forbids PHP execution on HTML.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: void

Hosting_Certificate_Install

Description:

Installs certificate on the hosting

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

cert (*string*): Certificate. The parameter is required.
key (*string*): Key. The parameter is required.
crtIntermediate (*string*): Certificate intermediate. The parameter is required.

Response:

type: *void*

Hosting_Certificate_Uninstall

Description:

Uninstalls the certificate of the hosting

Version: 1.0

Parameters:

hosting (*string*): Hosting name. The parameter is required.

Response:

type: *void*

Hosting_Certificate_ActivateLetsEncrypt

Description:

Activates Let's encrypt certificate on the hosting

Version: 1.1 Added optional subdomains parameter.

Parameters:

hosting (*string*): Hosting name. The parameter is required.

subdomains (*string*): Subdomains separated by commas. The parameter is optional.

Response:

type: *void*

Hosting_Certificate_DeactivateLetsEncrypt

Description:

Deactivates Let's encrypt certificate on the hosting

Version: 1.0

Parameters:

hosting (*string*): Hosting name. The parameter is required.

Response:

type: *void*

Hosting_PanelIndependentAccess_SetPassword

Description:

Set a new password for hosting panel independent access.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.
newPassword (string): New password. The parameter is required.

Response:
 type: void

Hosting_Ftp_Activate

Description:
 Activate FTP access.
 Version: 1.1

Parameters:
hosting (string): Hosting name. The parameter is required.

Response:
 type: void

Hosting_Ftp_Deactivate

Description:
 Deactivate FTP access.
 Version: 1.1

Parameters:
hosting (string): Hosting name. The parameter is required.

Response:
 type: void

Hosting_Ftp_Account_GetAll

Description:
 Returns all existing FTP accounts.
 Version: 1.1

Parameters:
hosting (string): Hosting name. The parameter is required.

Response:
 type: struct
 Example:

```
array(array('account' => 'test-linux-personal',
'folder' => "",
'date' => '2010-03-17 12:51:02',
'main' => true,
))
```

Hosting_Ftp_Account_CmdStatus_ListAll

Description:
 List all imports

Version: 1.0

Parameters:

hosting (string): Destination hosting name. The parameter is required.

Response:

type: array

Example:

'None'

Hosting_Ftp_Account_CmdStatus_GetDelete

Description:

Get delayed Hosting_Ftp_Account_Delete execution information.

Version: 1.0

Parameters:

hosting (string): Destination hosting name. The parameter is required.

orderId (int): Command order id. The parameter is required. Parameter value must be a valid integer.

Response:

type: array

Example:

'None'

Hosting_Ftp_Account_CmdStatus_GetSetPassword

Description:

Get delayed Hosting_Ftp_Account_SetPassword execution information.

Version: 1.0

Parameters:

hosting (string): Destination hosting name. The parameter is required.

orderId (int): Command order id. The parameter is required. Parameter value must be a valid integer.

Response:

type: array

Example:

'None'

Hosting_Ftp_Account_CmdStatus_GetCreate

Description:

Get delayed Hosting_Ftp_Account_Create execution information.

Version: 1.0

Parameters:

hosting (string): Destination hosting name. The parameter is required.

orderId (int): Command order id. The parameter is required. Parameter value must be a valid integer.

Response:

type: array

Example:

'None'

Hosting_Ftp_Account_Delete

Description:

Deletes a FTP account.

1.0 -> 1.1: Minor improvements.

1.1 -> 1.2: Turned into a delayed execution command.

Please note this command has a delayed execution and it'll return SUCCESS_PENDING code on success and a ticket id (integer) on the data field. Version: 1.2

Parameters:

hosting (string): Hosting name. The parameter is required.

account (string): FTP account name. The parameter is required. Parameter length must be between 1 and 35 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: int

Example:

'None'

Hosting_Ftp_Account_Create

Description:

Creates a new FTP account.

1.0 -> 1.1: Minor improvements.

1.1 -> 1.2: Folder parameter is now optional (may be left empty or missing).

1.2 -> 1.3: Turned into a delayed execution command.

Please note this command has a delayed execution and it'll return SUCCESS_PENDING code on success and a ticket id (integer) on the data field. Version: 1.3

Parameters:

hosting (string): Hosting name. The parameter is required.

account (string): FTP account name. The parameter is required. Parameter length must be between 1 and 35 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

password (string): Account password. The parameter is required. Parameter length must be between 6 and 71 characters.

folder (string): Remote folder. If missing or empty, the FTP account will use a default folder (like /www/). The parameter is optional. Parameter length must be between 0 and 150 characters. Parameter length must be between 1 and 255 characters. It should be a valid unix path.

Response:

type: int

Example:

'None'

Hosting_Ftp_Account_SetPassword

Description:

Changes FTP account password.

1.0 -> 1.1: Minor improvements.

1.1 -> 1.2: Improved password validation.

1.2 -> 1.3: Turned into a delayed execution command.

Please note this command has a delayed execution and it'll return SUCCESS_PENDING code on success and a ticket id (integer) on the data field. Version: 1.3

Parameters:

hosting (string): Hosting name. The parameter is required.

account (string): FTP account name. The parameter is required. Parameter length must be between 1 and 35 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

password (string): New account password. The parameter is required. Parameter length must be between 6 and 71 characters. Parameter length must be at least 6 characters. It can contain only alphanumeric characters. String must contain at least one number and one character. Unsafe patterns as 111111 or 123456 aren't allowed.

Response:

type: **int**

Example:

'None'

Hosting_Ftp_Get

Description:

Get FTP access status.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **bool**

Example:

true

Hosting_Ftp_GetAccountsLimit

Description:

Get FTP account number limit for this hosting.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **struct**

Example:

```
array('moreAccountsAllowed' => false,
'accountLimitNumber' => 0,
)
```

Hosting_GetMailInfo

Description:

Returns hosting mailserver information.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **struct**

Example:

```
array('server' => 'v1193.dinasever.com',
'host' => 'mail.test-edu-personalizacion-avanzada.com',
'TLS_activable' => true,
'TLS_is_active' => false,
)
```

Hosting_Import_ApplyForEmailAccountmap

Description:

Apply for an email import through IMAP to your hosting.

1.0 -> 1.1: Removed unused parameter.

Please note this command has a delayed execution and it'll return SUCCESS_PENDING code on success and a ticket id (integer) on the data field. Version: 1.1

Parameters:

hosting (string): Destination hosting name. The parameter is required.

originEmailAddress (string): Origin full email address. The parameter is required. Parameter value must be a valid email address.

originPassword (string): Origin user password. The parameter is required. Parameter length must be between 1 and 255 characters.

originServer (string): Origin server hostname or IP with (or without) port. Default port: 143. The parameter is required.

create (bool): Create destination email account. The parameter is optional. Parameter value must be a boolean (true or false).

destinationUser (string): Destination new email account alias (without hostname). If it's empty, we'll use originEmailAddress account alias as the destination name. The parameter is optional. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

destinationPassword (string): Only used if create is true. Destination user password. If it's empty, we'll use originPassword as the destination password on creation. The parameter is optional. Parameter length must be between 0 and 16 characters.

notificationMail (string): Email address for a notification. The parameter is optional. Parameter value must be a valid email address.

Response:

type: **int**

Example:

'None'

Hosting_Import_ListAll

Description:

List all imports

Version: 1.0

Parameters:

hosting (string): Destination hosting name. The parameter is required.

Response:

type: array

Example:

'None'

Hosting_Import_List

Description:

List unfinished (PENDING or STARTED) imports.

Version: 1.0

Parameters:

hosting (string): Destination hosting name. The parameter is required.

Response:

type: array

Example:

'None'

Hosting_Import_ApplyForEmailAccountPop

Description:

Apply for an email import through POP to your hosting.

1.0 -> 1.1: Removed unused parameter.

Please note this command has a delayed execution and it'll return SUCCESS_PENDING code on success and a ticket id (integer) on the data field. Version: 1.1

Parameters:

hosting (string): Destination hosting name. The parameter is required.

originEmailAddress (string): Origin full email address. The parameter is required. Parameter value must be a valid email address.

originPassword (string): Origin user password. The parameter is required. Parameter length must be between 1 and 255 characters.

originServer (string): Origin server hostname or IP with (or without) port. Default port: 110. The parameter is required.

create (bool): Create destination account. The parameter is optional. Parameter value must be a boolean (true or false).

destinationUser (string): Destination new email account alias (without hostname). If it's empty, we'll use originEmailAddress account alias as the destination name. The parameter is optional. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

destinationPassword (string): Only used if create is true. Destination user password. If it's empty, we'll use originPassword as the destination password on creation. The parameter is optional. Parameter length must be between 0 and 16 characters.

destinationFolder (string): Destination folder outside inbox. The parameter is optional. Parameter length must be between 0 and 255 characters.

notificationMail (string): Email address for a notification. The parameter is optional. Parameter value must be a valid email address.

Response:

type: int

Example:

'None'

Hosting_Import_ApplyForFtp

Description:

Apply for a database import to your hosting.

1.0 -> 1.1: Removed unused parameter.

1.1 -> 1.2: Parameters "create" and "destinationPassword" are now deprecated.

Please note this command has a delayed execution and it'll return SUCCESS_PENDING code on success and a ticket id (integer) on the data field. Version: 1.2

Parameters:

hosting (string): Destination hosting name. The parameter is required.

originUser (string): Origin user name. The parameter is required. Parameter length must be between 1 and 35 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

originPassword (string): Origin user password. The parameter is required. Parameter length must be between 3 and 35 characters.

originServer (string): Origin server hostname. Port is 21. The parameter is required.

originDirectory (string): Destination directory. The parameter is optional. Parameter length must be between 1 and 255 characters. It should be a valid unix path.

create (bool): Deprecated parameter. The parameter is optional. Parameter value must be a boolean (true or false).

destinationUser (string): Destination new user name. If it's empty, we'll use originUser as the destination user name on creation. The parameter is optional. Parameter length must be between 1 and 35 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

destinationPassword (string): Deprecated parameter. The parameter is optional.

notificationMail (string): Email address for a notification. The parameter is optional. Parameter value must be a valid email address.

Response:

type: **int**

Example:

'None'

Hosting_Import_ApplyForDdbb

Description:

Apply for a database import to your hosting.

1.0 -> 1.1: Removed unused parameter.

Please note this command has a delayed execution and it'll return SUCCESS_PENDING code on success and a ticket id (integer) on the data field. Version: 1.1

Parameters:

hosting (string): Destination hosting name. The parameter is required.

originDdbbName (string): Origin database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

originUser (string): Origin user name. The parameter is required. Parameter length must be between 1 and 16 characters.

originPassword (string): Origin user password. The parameter is required. Parameter length must be between 1 and 255 characters.

originServer (string): Origin server hostname or IP with (or without) port. Default port: 3306. The parameter is required.

create (bool): Create destination DDBB. The parameter is optional. Parameter value must be a boolean (true or false).

destinationDdbName (**string**): Destination new database name. If it's empty, we'll use originDdbName as the destination database name. The parameter is optional. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

destinationUser (**string**): Destination new user name. If it's empty, we'll use originUser as the destination user name on creation. The parameter is optional. Parameter length must be between 0 and 16 characters.

destinationPassword (**string**): Only used if create is true. Destination user password. If it's empty, we'll use originPassword as the destination password on creation. The parameter is optional. Parameter length must be between 0 and 16 characters.

notificationMail (**string**): Email address for a notification. The parameter is optional. Parameter value must be a valid email address.

Response:

type: **int**

Example:

'None'

Hosting_Subdomain_GetAll

Description:

Returns all existing subdomains on hosting.

Version: 1.0

Parameters:

hosting (**string**): Hosting domain name. The parameter is required.

Response:

type: **array**

Example:

(Example too long, see web.)

Hosting_Subdomain_Delete

Description:

Delete a subdomain on hosting.

Version: 1.0

Parameters:

hosting (**string**): Hosting domain name. The parameter is required.

host (**string**): Host for subdomain name. The parameter is required. Parameter length must be between 1 and 50 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: **void**

Hosting_Subdomain_Create

Description:

Create a subdomain on hosting.

1.0 -> 1.1: Fix on directory path validation.

Version: 1.1

Parameters:

hosting (string): Hosting domain name. The parameter is required.

host (string): Host for subdomain name. The parameter is required. Parameter length must be between 1 and 50 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

directory (string): Subdirectory name for account files. Default value: same as host . The parameter is optional. Parameter length must be between 1 and 255 characters. It should be a valid unix path.

ftpAccount (string): FTP account name. Default value: same as host . The parameter is optional. Parameter length must be between 1 and 50 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: void

Hosting_UrlShortener_Activate

Description:

Activates shortener on a hosting.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

folder (string): Hosting folder to store shorten URLs. The parameter is required.

Response:

type: void

Hosting_UrlShortener_GetAll

Description:

Returns shortened URLs on a hosting.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: struct

Example:

'None'

Hosting_UrlShortener_Delete

Description:

Deletes a shortened URL on a hosting

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

keyword (string): Keyword of the shortened URL to be deleted. The parameter is required.

Response:

type: void

Hosting_UrlShortener_Deactivate

Description:

Deactivates shortener on a hosting.

Use with caution: it deletes all the shortened URLs created under the hosting.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: void

Hosting_UrlShortener_Create

Description:

Creates a new shortened URL on a hosting.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

url (string): URL to be shorten. The parameter is required. Parameter value must be a valid URL.

title (string): URL title. The parameter is optional.

Response:

type: void

Hosting_Dsn_Mysql_GetAll

Description:

Returns all Mysql database source names.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: array

Example:

(Example too long, see web.)

Hosting_Dsn_Mysql_Delete

Description:

Delete selected Mysql Database Source Name.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

dsnName (string): DSN name. The parameter is required. Parameter value must be a valid database server name (dsn). Parameter length must be between 1 and 30 characters, only alphanumeric, underscore, dot or dash.

Response:

 type: `void`

Hosting_Dsn_Mysql_Create

Description:

Creates a new Mysql Data Source Name.

Version: 1.1

Parameters:

`hosting` (`string`): Hosting name. The parameter is required.

`ddbName` (`string`): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

`dsnName` (`string`): DSN name. The parameter is required. Parameter value must be a valid database server name (dsn). Parameter length must be between 1 and 30 characters, only alphanumeric, underscore, dot or dash.

`dsnDescription` (`string`): Database description. The parameter is required.

Response:

 type: `void`

Hosting_Dsn_Access_GetAll

Description:

Returns all MS Access database source names.

Version: 1.1

Parameters:

`hosting` (`string`): Hosting name. The parameter is required.

Response:

 type: `array`

Example:

(Example too long, see web.)

Hosting_Dsn_Access_Delete

Description:

Delete selected Access Database Source Name.

Version: 1.1

Parameters:

`hosting` (`string`): Hosting name. The parameter is required.

`dsnName` (`string`): DSN name. The parameter is required. Parameter value must be a valid database server name (dsn). Parameter length must be between 1 and 30 characters, only alphanumeric, underscore, dot or dash.

Response:

 type: `void`

Hosting_Dsn_Access_Create

Description:

Creates a new Access Data Source Name.
Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

ddbName (string): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

dsnName (string): DSN name. The parameter is required. Parameter value must be a valid database server name (dsn). Parameter length must be between 1 and 30 characters, only alphanumeric, underscore, dot or dash.

dsnDescription (string): Database description. The parameter is required.

Response:

type: void

Hosting_Dsn_Sqlserver_GetAll

Description:

Returns all SqlServer database source names.
Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: array

Example:

(Example too long, see web.)

Hosting_Dsn_Sqlserver_Delete

Description:

Delete selected Sqlserver Database Source Name.
Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

dsnName (string): DSN name. The parameter is required. Parameter value must be a valid database server name (dsn). Parameter length must be between 1 and 30 characters, only alphanumeric, underscore, dot or dash.

Response:

type: void

Hosting_Dsn_Sqlserver_Create

Description:

Creates a new Sqlserver Data Source Name.
Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

ddbName (string): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

dsnName (string): DSN name. The parameter is required. Parameter value must be a valid database server name (dsn). Parameter length must be between 1 and 30 characters, only alphanumeric, underscore, dot or dash.

dsnDescription (string): Database description. The parameter is required.

Response:

type: void

Hosting_Https_Activate

Description:

Activate HTTPs access.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: void

Hosting_Https_Deactivate

Description:

Deactivate HTTPs access.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: void

Hosting_Https_Get

Description:

Get HTTPs access status.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: bool

Example:

false

Hosting_Ssh_Activate

Description:

Activate SSH access.
Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: void

Hosting_Ssh_Deactivate

Description:

Deactivate SSH access.
Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: void

Hosting_Ssh_Get

Description:

Get SSH access status.
Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: bool

Example:

false

Hosting_IsActive

Description:

Returns if a hosting is active.
Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: bool

Example:

'None'

Hosting_GetDaysWithBackups

Description:

It returns the days with hosting backups.
Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

from (string): It gets the days starting from specified date. If empty, the command returns the dates of the current year. The parameter is optional. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

Response:

type: **struct**

Example:

'None'

Hosting_Test

Description:

Hosting command Testing
Version: 1.0

Parameters:

hosting (string): Domain name, for testing purposes. The parameter is required.

optional (string): Just an optional parameter The parameter is optional.

Response:

type: **struct**

Example:

'None'

Hosting_TlsMail_Activate

Description:

Activate TLS over mail.
Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **void**

Hosting_TlsMail_Deactivate

Description:

Deactivate TLS over mail.
Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

 type: **void**

Hosting_TlsMail_Get

Description:

Get TLS mail activation status.

True means active, false means inactive.

Version: 1.0

Parameters:
hosting (**string**): Hosting name. The parameter is required.

Response:

 type: **bool**

Example:

'None'

Hosting_Backup_Database_GetTables

Description:

It returns the database tables in a hosting backup.

Version: 1.0

Parameters:
hosting (**string**): Hosting name. The parameter is required.

date (**string**): Date of the backup. The parameter is required. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

databaseName (**string**): Database name. The parameter is required.

databaseType (**string**): Database type. The parameter is required. Accepted parameter values: "sqlServer", "otherType".

Response:

 type: **struct**

Example:

'None'

Hosting_Backup_Restore_EmailAccounts

Description:

It restores one or several email accounts from backup.

Version: 1.0

Parameters:
hosting (**string**): Hosting name. The parameter is required.

date (**string**): Date of the backup. The parameter is required. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

emailAccounts (**string**): Email accounts separated by comma. The parameter is required.

notificationEmail (**string**): Email to send the notification of restoring. The parameter is required. Parameter value must be a valid email address.

Response:

type: **struct**

Example:

'None'

Hosting_Backup_Restore_Database_Tables

Description:

It restores one or several database tables from a backup.

Version: 1.0

Parameters:

hosting (**string**): Hosting name. The parameter is required.

date (**string**): Date of the backup. The parameter is required. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

databaseName (**string**): Database name. The parameter is required.

databaseType (**string**): Database type. The parameter is required. Accepted parameter values: "sqlServer", "otherType".

tables (**string**): Database tablenamees separated by comma. The parameter is required.

notificationEmail (**string**): Email to send the notification of restoring. The parameter is required. Parameter value must be a valid email address.

Response:

type: **struct**

Example:

'None'

Hosting_Backup_Restore_Database

Description:

It restores a database backup.

Version: 1.0

Parameters:

hosting (**string**): Hosting name. The parameter is required.

date (**string**): Date of the backup. The parameter is required. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

databaseName (**string**): Database name. The parameter is required.

databaseType (**string**): Database type. The parameter is required. Accepted parameter values: "sqlServer", "otherType".

notificationEmail (**string**): Email to send the notification of restoring. The parameter is required. Parameter value must be a valid email address.

Response:

type: **struct**

Example:

'None'

Hosting_Backup_Restore_Resource

Description:

It restores a resource from a hosting backup.

Version: 1.0

Parameters:

hosting (*string*): Hosting name. The parameter is required.

date (*string*): Date of the backup. The parameter is required. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

resourcePath (*string*): Resource path The parameter is required.

notificationEmail (*string*): Email to send the notification of restoring. The parameter is required. Parameter value must be a valid email address.

Response:

type: **struct**

Example:

'None'

Hosting_Backup_Send_Database_Tables

Description:

It sends one or several database tables from a backup to a specified email.

Version: 1.0

Parameters:

hosting (*string*): Hosting name. The parameter is required.

date (*string*): Date of the backup. The parameter is required. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

databaseName (*string*): Database name. The parameter is required.

databaseType (*string*): Database type. The parameter is required. Accepted parameter values: "sqlServer", "otherType".

tables (*string*): Database tablenamees separated by comma. The parameter is required.

email (*string*): Email to send the backup. The parameter is required. Parameter value must be a valid email address.

Response:

type: **struct**

Example:

'None'

Hosting_Backup_Send_Database

Description:

It sends a database backup to a specified email.

Version: 1.0

Parameters:

hosting (*string*): Hosting name. The parameter is required.

date (*string*): Date of the backup. The parameter is required. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

databaseName (*string*): Database name. The parameter is required.

databaseType (*string*): Database type. The parameter is required. Accepted parameter values: "sqlServer", "otherType".

email (*string*): Email to send the backup. The parameter is required. Parameter value must be a valid email address.

Response:

type: **struct**

Example:

'None'

Hosting_Backup_Send_Resource

Description:

It sends a resource from a hosting backup to a specified email.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

date (string): Date of the backup. The parameter is required. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

resourcePath (string): Resource path The parameter is required.

email (string): Email to send the backup. The parameter is required. Parameter value must be a valid email address.

Response:

type: **struct**

Example:

'None'

Hosting_Backup_GetResources

Description:

It returns the resources in a hosting backup.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

date (string): Date of the backup. The parameter is required. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

folderPath (string): If empty, it returns the root folder content. The parameter is optional.

Response:

type: **struct**

Example:

'None'

Hosting_Backup_GetEmailAccounts

Description:

It returns the email accounts in a hosting backup.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

date (string): Date of the backup. The parameter is required. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

Response:

type: **struct**

Example:

'None'

Hosting_Backup_GetDatabases

Description:

It returns the databases in a hosting backup.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

date (string): Date of the backup. The parameter is required. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

Response:

type: **struct**

Example:

'None'

Hosting_Backup_GetStatus

Description:

It returns the status of the restorings or sendings programmed.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **struct**

Example:

'None'

Hosting_Email_Filter_SetGeolocalization

Description:

Changes geolocalization status. If active, country filters (OriginCountryCode) will take effect on received emails.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

active (bool): True active . The parameter is required. Parameter value must be a boolean (true or false).

Response:

type: **void**

Hosting_Email_Filter_GetAll

Description:

Return email filter rule list.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

country (string): Country. The parameter is optional.

Response:

 type: **array**

Example:

```
array(array('action' => 'mark',
'date' => '2009-07-22 09:25:06',
'ruleId' => 258105,
'searchSubject' => 'EmailSubject',
'searchObject' => 'nvbnbv',
'markLabel' => 'vbn',
))
```

Hosting_Email_Filter_CreateForSpam

Description:

Create a new email filter rule for spam.

Version: 1.1

Parameters:
hosting (**string**): Hosting name. The parameter is required.

action (**string**): Action on filtered emails. The parameter is required. Accepted parameter values: "reject","moveToSpamFolder","moveToFolder","redirectToEmailAccount".

actionDestiny (**string**): Value associated with action. Only required by actions "moveToFolder" and "redirectToEmailAccount". The parameter is optional.

Response:

 type: **void**

Hosting_Email_Filter_Delete

Description:

Delete a existing email filter rule.

Version: 1.1

Parameters:
hosting (**string**): Hosting name. The parameter is required.

ruleId (**int**): Rule ID. The parameter is required.

Response:

 type: **void**

Hosting_Email_Filter_Create

Description:

Create a new email filter rule.

Version: 1.1

Parameters:
hosting (**string**): Hosting name. The parameter is required.

searchObject (**string**): String that must match for filter email (do action). The parameter is required.

searchSubject (**string**): Search subject. The parameter is required. Accepted parameter values: "EmailSubject","EmailFrom","EmailTo","EmailHeaders","OriginCountryCode".

action (**string**): Action on filtered emails. The parameter is required. Accepted parameter values:

"mark", "delete".

markLabel (string): Label for filtered emails if action equals 'mark'. The parameter is optional.

Response:

type: void

Hosting_Email_Filter_GetGeolocalization

Description:

Returns geolocalization status (active true, inactive false).

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: bool

Example:

false

Hosting_Email_Dkim_Activate

Description:

Activate TLS over mail.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: void

Hosting_Email_Dkim_Deactivate

Description:

Deactivate TLS over mail.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: void

Hosting_Email_Dkim_Get

Description:

Get DKIM TXT zone (hostname and text).

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **struct**

Example:

```
array('hostname' => 'default._domainkey',
'text' => 'v=DKIM1; g=*; k=rsa; p='
)
```

Hosting_Email_Dkim_IsActive

Description:

Get DKIM activation status.

True means active, false means inactive.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **bool**

Example:

false

Hosting_Email_Antivirus_SetConfig

Description:

Updates antivirus configuration.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

action (string): Action over infected emails. The parameter is required. Accepted parameter values: "mark", "delete", "none".

Response:

type: **void**

Hosting_Email_Antivirus_GetConfig

Description:

Returns antivirus configuration data.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **struct**

Example:

```
array('delete_mesage' => true,
'label_subject' => false,
'active' => true,
```


)

Hosting_Email_Antivirus_UpdateAttachedFileFilter

Description:

Update antivirus file filters configuration.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

tag (string): Tag. The parameter is required.

action (string): Action on filtered emails. The parameter is required. Accepted parameter values: "allow", "deny", "scan".

Response:

type: void

Hosting_Email_Antivirus_GetAttachedFilesFilters

Description:

Returns antivirus file filters configuration.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: struct

Example:

(Example too long, see web.)

Hosting_Email_Antispam_SetConfig

Description:

Updates spam assasin configuration.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

action (string): Action over detected spam emails. The parameter is required. Accepted parameter values: "mark", "delete", "none".

list (array): Whitelist. The parameter is optional.

Response:

type: void

Hosting_Email_Antispam_Activate

Description:

Activate spam assasin.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: void

Hosting_Email_Antispam_GetScore

Description:

Returns spam assassin aggressivity score.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: int

Example:

6

Hosting_Email_Antispam_Deactivate

Description:

Deactivate spam assassin.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: void

Hosting_Email_Antispam_AddDomainToWhitelist

Description:

Add a domain to whitelist.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

domain (string): Domain added to whitelist. The parameter is required.

Response:

type: void

Hosting_Email_Antispam_SetScore

Description:

Updates spam assassin aggressivity score.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

score (int): New aggressivity score. The parameter is required. Parameter value must be between values 1 and 10 inclusive.

Response:

type: void

Hosting_Email_Antispam_GetConfig

Description:

Returns spam assasin configuration data.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: struct

Example:

```
array('delete_mesage' => false,
'label_subject' => true,
'active' => true,
)
```

Hosting_Email_Antispam_GetWhitelist

Description:

Returns spam assasin white list configuration.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: array

Example:

```
array(array('id' => 4503,
'action' => 'allow',
'domain' => 'ola@ola.com',
))
```

Hosting_Email_Antispam_AddDomainToBlacklist

Description:

Add a domain to blacklist.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

domain (string): Domain added to blacklist. The parameter is required.

Response:

 type: **void**

Hosting_Email_Antispam_GetBlacklist

Description:

Returns spam assasin black list configuration.

Version: 1.1

Parameters:
hosting (**string**): Hosting name. The parameter is required.

Response:

 type: **array**

Example:

```
array(array('id' => 12743,
'action' => 'reject',
'domain' => 'dadasdadsad.com',
),array('id' => 12745,
'action' => 'reject',
'domain' => 'alaaaaa@funciona.com',
))
```

Hosting_Email_Antispam_RemoveDomainFromWhitelist

Description:

Remove a domain from antispam whitelist.

Version: 1.1

Parameters:
hosting (**string**): Hosting name. The parameter is required.

domain (**string**): Domain removed from whitelist. The parameter is required.

Response:

 type: **void**

Hosting_Email_Antispam_RemoveDomainFromBlacklist

Description:

Remove a domain from antispam blacklist.

Version: 1.1

Parameters:
hosting (**string**): Hosting name. The parameter is required.

domain (**string**): Domain removed from blacklist. The parameter is required.

Response:

 type: **void**

Hosting_Email_UsedSpace_GetPerAlias

Description:

Get the used space by an email account.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

alias (string): Account alias (email account without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: void

Hosting_Email_UsedSpace_Get

Description:

Get the used space by email accounts.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: void

Hosting_Email_Account_Activate

Description:

Activates an existing but inactive email account.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

account (string): Email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: void

Hosting_Email_Account_GetAll

Description:

Returns all email accounts.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: struct

Example:

```
array(array('alias' => 'test-linux-personal',
```

```
'account' => 'test-linux-personal@test-linux-personal.dinahosting.com',
'catch-all' => false,
'auto_response' => false,
'date' => '2010-03-17 12:51:02',
'id' => 0,
'disabled' => false,
))
```

Hosting_Email_Account_Delete

Description:

Deletes an existing email account.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

account (string): Email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: void

Hosting_Email_Account_Deactivate

Description:

Deactivates an existing email account.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

account (string): Email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: void

Hosting_Email_Account_SetCopyTo

Description:

Sets copy-to emails for an email account.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

account (string): Email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

destination (array): Array of destination email accounts. The parameter is required.

Response:

type: void

Hosting_Email_Account_Create

Description:

Creates a new email account.

Version: 1.1

Parameters:

hosting (*string*): Hosting name. The parameter is required.

account (*string*): Email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

password (*string*): Account password. The parameter is required. Password length must be between 8 and 35 characters. It can contain only alphanumeric, underscore or dash chars. String must start with a alphanumeric char. String must not contain email alias. String must not contain more than 2 consecutive repeating characters. String must not contain more than 2 consecutive numbers in any order.

Response:

type: *void*

Hosting_Email_Account_GetCopyTo

Description:

Returns copy-to emails for an email account.

Version: 1.1

Parameters:

hosting (*string*): Hosting name. The parameter is required.

account (*string*): Email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: *struct*

Example:

```
array('czxccxz@dinahosting.com','asffsasf@dinahosting.com')
```

Hosting_Email_Account_Get

Description:

Returns an existing email account.

Version: 1.1

Parameters:

hosting (*string*): Hosting name. The parameter is required.

account (*string*): Email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: *struct*

Example:

```
array('alias' => 'test-linux-personal',
      'account' => 'test-linux-personal@test-linux-personal.dinahosting.com',
      'password' => '????????')
```

```
'catch-all' => false,
'auto_response' => false,
'date' => '2010-03-17 12:51:02',
'id' => 0,
'disabled' => false,
)
```

Hosting_Email_Account_SetPassword

Description:

Changes email account password.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

account (string): Email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

password (string): New account password. The parameter is required. Password length must be between 8 and 35 characters. It can contain only alphanumeric, underscore or dash chars. String must start with a alphanumeric char. String must not contain email alias. String must not contain more than 2 consecutive repeating characters. String must not contain more than 2 consecutive numbers in any order.

Response:

type: void

Hosting_Email_Account_RemoveCopyTo

Description:

Remove copy-to for an email account.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

account (string): Email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: void

Hosting_Email_Account_Empty

Description:

Empties an existing email account.

Warning: This process can't be reversed.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

account (string): Email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

 type: `void`

Hosting_Email_Redirection_ActivateCatchAll

Description:

Activate catch-all email redirection.

Version: 1.1

Parameters:
hosting (`string`): Hosting name. The parameter is required.

destination (`array`): Array of destination email accounts. The parameter is required.

Response:

 type: `void`

Hosting_Email_Redirection_DeactivateCatchAll

Description:

Deactivate catch-all email redirection.

Version: 1.1

Parameters:
hosting (`string`): Hosting name. The parameter is required.

Response:

 type: `void`

Hosting_Email_Redirection_Update

Description:

Update an existing email redirection.

Version: 1.1

Parameters:
hosting (`string`): Hosting name. The parameter is required.

alias (`string`): Existing redirection alias (email account without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

destination (`array`): Array of destination email accounts. The parameter is required.

Response:

 type: `void`

Hosting_Email_Redirection_GetAll

Description:

Returns all email account redirections.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **array**

Example:

```
array(array('alias' => 'dfsdf',
'catch-all' => false,
'date' => '2009-07-22 11:30:40',
'active' => true,
'destination' => array('pla@olaa.com'),
))
```

Hosting_Email_Redirection_Delete

Description:

Delete an existing email redirection.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

alias (string): Existing redirection alias (email account without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: **void**

Hosting_Email_Redirection_Create

Description:

Creates a new email redirection on a new alias.

If already exists a redirection alias or an email account over this alias name, this command will fail.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

alias (string): Redirection alias (email account without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

destination (array): Array of destination email accounts. The parameter is required.

Response:

type: **void**

Hosting_Email_Redirection_Get

Description:

Returns an email account configuration.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

alias (**string**): Redirection alias (email account without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: **struct**

Example:

```
array('alias' => 'dfsdf',
'catch-all' => false,
'date' => '2009-07-22 11:30:40',
'destination' => array('pla@olaa.com'),
)
```

Hosting_Email_Autoresponse_Activate

Description:

Activates an existing email autoresponse.

Version: 1.1

Parameters:

hosting (**string**): Hosting name. The parameter is required.

alias (**string**): Existing email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: **void**

Hosting_Email_Autoresponse_Delete

Description:

Deletes an existing email autoresponse.

Version: 1.1

Parameters:

hosting (**string**): Hosting name. The parameter is required.

alias (**string**): Existing email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: **void**

Hosting_Email_Autoresponse_Deactivate

Description:

Deactivates an existing email autoresponse.

Version: 1.1

Parameters:

hosting (**string**): Hosting name. The parameter is required.

alias (**string**): Existing email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash

chars. String must start with a alphanumeric char.

Response:

type: `void`

Hosting_Email_Autoresponse_Create

Description:

Creates a new email autoresponse.

1.1 -> 1.2: Parameter "excluded" is optional.

Version: 1.2

Parameters:

`hosting` (`string`): Hosting name. The parameter is required.

`alias` (`string`): Existing email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

`text` (`string`): Autoresponse text. The parameter is required.

`excluded` (`array`): Exluded emails. The parameter is optional.

`start` (`string`): Start datetime. Format: yyyy-MM-dd . If empty, autoresponse starts now. The parameter is optional. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

`end` (`string`): End datetime. Format: yyyy-MM-dd . If empty, autoresponse doesn't expire. The parameter is optional. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

Response:

type: `void`

Hosting_Email_Autoresponse_Get

Description:

Returns an existing email autoresponse configuration.

Version: 1.1

Parameters:

`hosting` (`string`): Hosting name. The parameter is required.

`alias` (`string`): Existing email account alias (without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: `struct`

Example:

```
array('alias' => 'acura',
'date' => '2007-03-14 00:24:51',
'text' => 'Prueba con fechas',
'from' => '2009-04-20',
'to' => '2009-04-27',
'activated' => true,
'excluded-emails' => "",
)
```

Hosting_Email_AutomaticDeletion_CreateRule

Description:

Creates a new automatic deletion rule for one email account.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

alias (string): Account alias (email account without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

scope (string): All messages or those that have been read. The parameter is required. Accepted parameter values: "all", "read".

antique (string): Antique messages. The parameter is required. Accepted parameter values: "week", "fortnight", "month", "quarter-year", "half-year", "year", "two-year", "three-year", "four-year", "five-year".

ifExceedsSize (string): If used space exceeds indicated size. The parameter is required. Accepted parameter values: "any", "50MB", "100MB", "200MB", "500MB", "1GB".

Response:

type: void

Hosting_Email_AutomaticDeletion_DeleteRule

Description:

Deletes automatic deletion rule for one email account.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

alias (string): Account alias (email account without hostname). The parameter is required. Parameter length must be between 1 and 40 characters. It can contain only alphanumeric, underscore, dot or dash chars. String must start with a alphanumeric char.

Response:

type: void

Hosting_Ddbb_GetAll

Description:

Returns all databases.

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: array

Example:

```
array(array('name' => 'kbsoporte',
'account' => 'kbsoporte',
'date' => '2012-11-05 20:59:35',
'autoinstall' => false,
'type' => 'mysql',
'access_host' => 'any',
))
```

Hosting_Ddbb_Mysql_GetInfo

Description:

Returns selected Mysql Database information.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

ddbName (string): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

Response:

type: **struct**

Example:

```
array('server' => 'hl77.dinasever.com',
'name' => 'test2BBDD',
'account' => 'test2',
'date' => '2009-08-26 22:14:15',
'autoinstall' => false,
)
```

Hosting_Ddbb_Mysql_SetIpAcl

Description:

Sets selected Mysql Database hostname ACL configuration.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

ddbName (string): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

ip (string): Accepted IP v4 . The parameter is required. Parameter value must be a valid IP v4 address.

Response:

type: **void**

Hosting_Ddbb_Mysql_GetAll

Description:

Returns all Mysql databases.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **array**

Example:

(Example too long, see web.)

Hosting_Ddbb_Mysql_Delete

Description:

Delete selected Mysql Database.

Version: 1.1

Parameters:

hosting (*string*): Hosting name. The parameter is required.

ddbName (*string*): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

Response:

type: *void*

Hosting_Ddbb_Mysql_Create

Description:

Creates a new Mysql DataBase.

Version: 1.1

Parameters:

hosting (*string*): Hosting name. The parameter is required.

ddbName (*string*): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

userName (*string*): User name. The parameter is required. Parameter length must be between 6 and 16 characters.

userPassword (*string*): User password. The parameter is required. Parameter length must be between 1 and 41 characters.

accessHost (*string*): Access host. Default: any. The parameter is required. Accepted parameter values: "any", "localhost".

Response:

type: *void*

Hosting_Ddbb_Mysql_SetHostAcl

Description:

Sets selected Mysql Database hostname ACL configuration.

Version: 1.1

Parameters:

hosting (*string*): Hosting name. The parameter is required.

ddbName (*string*): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

hostname (*string*): Accepted hostname or "any" string (without quotes). The parameter is required.

Response:

type: *void*

Hosting_Ddbb_Mysql_BackupTask_GetAll

Description:

Returns all Mysql backup tasks on this hosting.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **struct**

Example:

```
array('oscommerce_47aa503883f33' => '1m',  
)
```

Hosting_Ddbb_Mysql_BackupTask_Delete

Description:

Deletes an existing Backup Task for a selected Mysql dataBase.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

ddbName (string): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

Response:

type: **void**

Hosting_Ddbb_Mysql_BackupTask_Set

Description:

Sets the Backup Task for a selected Mysql dataBase.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

ddbName (string): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

taskPeriod (string): Task Period (##d for days, ##h for hours or ##m for minutes). The parameter is required. Parameter value must be a valid task period (##d ##m ##h).

Response:

type: **void**

Hosting_Ddbb_Mysql_GetAclConfiguration

Description:

Returns selected Mysql Database ACL configuration.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

ddbName (**string**): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

Response:

type: **struct**

Example:

```
array('host' => 'ANY',
)
```

Hosting_Ddbb_Mysql_Backup_Get

Description:

Return an existing Backup Task for a selected Mysql dataBase.

Version: 1.1

Parameters:

hosting (**string**): Hosting name. The parameter is required.

ddbName (**string**): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

Response:

type: **struct**

Example:

(Example too long, see web.)

Hosting_Ddbb_Mysql_Backup_Restore

Description:

Restore an existing Backup Task for a selected Mysql dataBase.

Version: 1.1

Parameters:

hosting (**string**): Hosting name. The parameter is required.

ddbName (**string**): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

file (**string**): Backup file The parameter is required.

Response:

type: **void**

Hosting_Ddbb_Mysql_CreateWithIpAcl

Description:

Creates a new Mysql DataBase with IP ACL.

Version: 1.1

Parameters:

hosting (**string**): Hosting name. The parameter is required.

ddbName (**string**): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or

underscore chars. String must start with a alphabetical char and contain at least one numeric char.

userName (*string*): User name. The parameter is required. Parameter length must be between 1 and 16 characters.

userPassword (*string*): User password. The parameter is required. Parameter length must be between 6 and 16 characters.

accessHostIp (*string*): Accepted IP v4 . The parameter is required. Parameter value must be a valid IP v4 address.

Response:

type: *void*

Hosting_Ddbb_Mysql_SetPassword

Description:

Set new password for selected Mysql Database.

Version: 1.1

Parameters:

hosting (*string*): Hosting name. The parameter is required.

ddbName (*string*): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

password (*string*): New password. The parameter is required.

Response:

type: *void*

Hosting_Ddbb_Postgre_GetAll

Description:

Returns all Postgre databases.

Version: 1.1

Parameters:

hosting (*string*): Hosting name. The parameter is required.

Response:

type: *array*

Example:

```
array(array('server' => 'pgsql01.dinasever.com',
'account' => 'userpostgresiphone',
'name' => 'postgreiphone',
'autoinstall' => false,
'date' => '2011-01-31 14:25:08',
))
```

Hosting_Ddbb_Postgre_Delete

Description:

Delete selected Postgre Database.

Version: 1.1

Parameters:

hosting (**string**): Hosting name. The parameter is required.

ddbName (**string**): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

Response:

type: **void**

Hosting_Ddbb_Postgre_Create

Description:

Creates a new Postgre DataBase.

Version: 1.1

Parameters:

hosting (**string**): Hosting name. The parameter is required.

ddbName (**string**): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

userName (**string**): User name. The parameter is required. Parameter length must be between 1 and 16 characters.

userPassword (**string**): User password. The parameter is required. Parameter length must be between 6 and 71 characters.

Response:

type: **void**

Hosting_Ddbb_Postgre_SetPassword

Description:

Set new password for selected Postgre Database.

Version: 1.1

Parameters:

hosting (**string**): Hosting name. The parameter is required.

ddbName (**string**): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

userName (**string**): User name. The parameter is required. Parameter length must be between 1 and 16 characters.

userPassword (**string**): New password. The parameter is required.

Response:

type: **void**

Hosting_Ddbb_Access_GetAllMdb

Description:

Returns all Access .mdb databases .

Warning: This won't work with accdb databases (access 2007+).

Version: 1.0

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **array**

Example:

```
array('1ruebaRomina.mdb','1ruebaRomina2.mdb','1ruebaRuben.mdb','1ruebaRuben2.mdb')
```

Hosting_Ddbb_MariaDb_GetAll

Description:

Returns all MariaDb databases.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **array**

Example:

```
'None'
```

Hosting_Ddbb_MariaDb_Delete

Description:

Delete selected MariaDb Database.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

ddbName (string): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

userName (string): User name. The parameter is required. Parameter length must be between 1 and 16 characters.

Response:

type: **void**

Hosting_Ddbb_MariaDb_Create

Description:

Creates a new MariaDb DataBase.

Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

ddbName (string): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

userName (string): User name. The parameter is required. Parameter length must be between 1 and 16 characters.

userPassword (string): User password. The parameter is required. Parameter length must be between 6 and 71 characters.

Response:

 type: `void`

Hosting_Ddbb_MariaDb_SetPassword

Description:

Set new password for selected MariaDb Database.

Version: 1.1

Parameters:
hosting (`string`): Hosting name. The parameter is required.

ddbName (`string`): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

userName (`string`): User name. The parameter is required. Parameter length must be between 1 and 16 characters.

userPassword (`string`): New password. The parameter is required.

Response:

 type: `void`

Hosting_Ddbb_MongoDb_GetAll

Description:

Returns all MongoDB databases.

Version: 1.1

Parameters:
hosting (`string`): Hosting name. The parameter is required.

Response:

 type: `array`

Example:

'None'

Hosting_Ddbb_MongoDb_Delete

Description:

Delete selected MongoDB Database.

Version: 1.1

Parameters:
hosting (`string`): Hosting name. The parameter is required.

ddbName (`string`): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

Response:

 type: `void`

Hosting_Ddbb_MongoDb_SetPassword

Description:

Set new password for selected MongoDB Database.

Version: 1.1

Parameters:

hosting (*string*): Hosting name. The parameter is required.

ddbName (*string*): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

userName (*string*): User name. The parameter is required. Parameter length must be between 1 and 16 characters.

userPassword (*string*): New password. The parameter is required.

Response:

type: *void*

Hosting_Ddbb_Sqlserver_SetDataSize

Description:

Set data size for selected Sqlserver Database.

Version: 1.1

Parameters:

hosting (*string*): Hosting name. The parameter is required.

ddbName (*string*): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

dataSize (*int*): Maximum data volume stored (MB). The parameter is required. Parameter value must be greater than 2.

Response:

type: *void*

Hosting_Ddbb_Sqlserver_GetAll

Description:

Returns all SqlServer databases.

Version: 1.1

Parameters:

hosting (*string*): Hosting name. The parameter is required.

Response:

type: *array*

Example:

```
array(array('name' => 'unabddd',
'account' => 'unusuario',
'password' => '?????????',
'date' => '2011-07-13 17:41:03',
'data_space' => 3,
'transaction_space' => 1,
))
```

Hosting_Ddbb_Sqlserver_GetSpaceInfo

Description:

Returns a sqlserver databases space report.

Version: 1.1

Parameters:

hosting (**string**): Hosting name. The parameter is required.

Response:

type: **struct**

Example:

(Example too long, see web.)

Hosting_Ddbb_Sqlserver_Delete

Description:

Delete selected Sqlserver Database.

Version: 1.1

Parameters:

hosting (**string**): Hosting name. The parameter is required.

ddbName (**string**): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

Response:

type: **void**

Hosting_Ddbb_Sqlserver_Create

Description:

Creates a new Sqlserver DataBase.

Version: 1.1

Parameters:

hosting (**string**): Hosting name. The parameter is required.

ddbName (**string**): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

userName (**string**): User name. The parameter is required. Parameter length must be between 1 and 16 characters.

userPassword (**string**): User password. The parameter is required. Parameter length must be between 6 and 71 characters. Parameter value must be an alphanumeric string.

dataSize (**int**): Maximum data volume stored (MB). The parameter is required. Parameter value must be greater than 4.

transactionsSize (**int**): Maximum data volume transmitted (MB). The parameter is required. Parameter value must be greater than 0.

accessFrom (**string**): Access from: Any location (default), Localhost and specific IP (XX.XX.XX.XX), Only localhost (localhost). The parameter is optional.

Response:

type: **void**

Hosting_Ddbb_Sqlserver_GetGlobalSpaceInfo

Description:

It gets the space info of SQL Server formatted in MB: space limit and available space.
Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

Response:

type: **struct**

Example:

```
array('limit' => 200,
'used' => 0,
'reserved' => 0,
'available' => 200,
)
```

Hosting_Ddbb_Sqlserver_SetPassword

Description:

Set new password for selected Sqlserver Database.
Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

ddbName (string): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

password (string): New password. The parameter is required.

Response:

type: **void**

Hosting_Ddbb_Sqlserver_SetTransactionsSize

Description:

Set transaction size for selected Sqlserver Database.
Version: 1.1

Parameters:

hosting (string): Hosting name. The parameter is required.

ddbName (string): Database name. The parameter is required. Parameter value must be a valid database name. Parameter length must be between 1 and 64 characters. It can contain only alphanumeric or underscore chars. String must start with a alphabetical char and contain at least one numeric char.

transactionsSize (int): Maximum data volume transmitted (MB). The parameter is required. Parameter value must be greater than 0.

Response:

type: **void**

Housing commands

Housing_GetDataTransferInfo

Description:

Returns data transfer summary.

Version: 1.0

Parameters:

`serverName` (`string`): Server name. The parameter is required.

Response:

type: `struct`

Example:

(Example too long, see web.)

Housing_Monitorization_Activate

Description:

Activate monitorization.

Version: 1.0

Parameters:

`serverName` (`string`): Server name. The parameter is required.

`emails` (`array`): Array of emails. The parameter is required.

Response:

type: `void`

Housing_Monitorization_Deactivate

Description:

Deactivate monitorization.

Version: 1.0

Parameters:

`serverName` (`string`): Server name. The parameter is required.

Response:

type: `void`

Housing_Monitorization_Get

Description:

Returns monitorization configuration.

Version: 1.0

Parameters:

`serverName` (`string`): Server name. The parameter is required.

Response:

 type: **struct**

Example:

```
array('emails' => array(""),
'activated' => false,
)
```

Housing_GetBandwidthConsumption

Description:

Returns bandwidth consumption summary.

Version: 1.0

Parameters:
serverName (**string**): Server name. The parameter is required.

month (**int**): Month number. The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 12 inclusive.

year (**int**): Year. The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 2002 and 2012 inclusive.

Response:

 type: **struct**

Example:

(Example too long, see web.)

Housing_GetServerInfo

Description:

Returns data transfer summary.

Version: 1.0

Parameters:
serverName (**string**): Server name. The parameter is required.

Response:

 type: **struct**

Example:

```
array('main_ip' => '82.98.148.16',
'ips' => array(),
'url' => "",
)
```

Housing_Kvm_Get

Description:

Returns KVM configuration.

1.0 -> 1.1: new keys: user, password

Version: 1.1

Parameters:
serverName (**string**): Server name The parameter is required.

Response:

 type: **struct**

Example:

```
array('user' => 'lhcw',
'password' => '6olto0e3',
'ip' => '10.10.10.10',
)
```

Housing_Kvm_Unmount

Description:

Unmount KVM.

Version: 1.0

Parameters:

serverName (**string**): Server name The parameter is required.

allowed_ip (**string**): IP that will be granted access. If it's missing, we'll use the requesting client IP. The parameter is optional. Parameter value must be a valid IP v4 address.

Response:

 type: **void**

Housing_Kvm_Mount

Description:

Mount KVM and get public IP.

1.0 -> 1.1: returns mounted IP

1.1 -> 1.2: new parameter: allowed_ip

Version: 1.2

Parameters:

serverName (**string**): Server name The parameter is required.

allowed_ip (**string**): IP that will be granted access. If it's missing, we'll use the requesting client IP. The parameter is optional. Parameter value must be a valid IP v4 address.

Response:

 type: **string**

Example:

```
'None'
```

Housing_GetTransferValue

Description:

Returns max data transfer value (MBs).

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

 type: **int**

Example:

```
0
```

Housing_PowerStatus_Restart

Description:

Restart server.
Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: void

Import commands

Import_GetStatus

Description:

Get import status for a known ticketId

Possible status strings: 'PENDING', 'STARTED', 'OK', 'ERROR', 'CANCEL'

Version: 1.0

Parameters:

importId (**string**): Import ID The parameter is required. Parameter value must be a valid integer.

Response:

type: **string**

Example:

'OK'

Multihosting commands

Multihosting_Hosting_GetSpace

Description:

Returns used hosting space.

Only for multihosting.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

domainName (**string**): Hosting domain name. The parameter is required.

Response:

type: **struct**

Example:

'None'

Multihosting_Hosting_Activate

Description:

Activates an existing but inactive hosting.

Only for multihosting.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

domainName (**string**): Hosting domain name. The parameter is required.

Response:

type: **void**

Multihosting_Hosting_GetAll

Description:

Returns existing hostings on multihosting.

Only for multihosting.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

onlyActiveHostings (**bool**): True to add filter: return only active hostings. False or empty, execute without filter. The parameter is optional. Parameter value must be a boolean (true or false).

Response:

type: **array**

Example:

array('buscador.iumx.eu')

Multihosting_Hosting_Delete

Description:

Deletes an existing hosting.
 Only for multihosting.
 Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.
domainName (**string**): Hosting domain name. The parameter is required.

Response:

type: **void**

Multihosting_Hosting_Deactivate

Description:

Deactivates an existing and active hosting.
 Only for multihosting.
 Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.
domainName (**string**): Hosting domain name. The parameter is required.

Response:

type: **void**

Multihosting_Hosting_Create

Description:

Creates a new hosting.
 Only for multihosting.
 Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.
domainName (**string**): Hosting domain name. The parameter is required.
setupName (**string**): Existing setup name. The parameter is required. Parameter length must be between 1 and 30 characters.
setZones (**bool**): True to set new zones, false to leave them unchanged. Default: true. The parameter is required. Parameter value must be a boolean (true or false).

Response:

type: **void**

Multihosting_Hosting_ChangeSetup

Description:

Changes setup of a existing hosting.
 Only for multihosting.
 Version: 1.0

Parameters:

serverName (*string*): Server name. The parameter is required.

domainName (*string*): Hosting domain name. The parameter is required.

setupName (*string*): Existing setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

Response:

type: *void*

Multihosting_GetInfo

Description:

Returns multihosting info.

Version: 1.0

Parameters:

serverName (*string*): Server name. The parameter is required.

Response:

type: *struct*

Example:

(Example too long, see web.)

Multihosting_GetUsedSpace

Description:

Returns used space.

Only for multihosting.

Version: 1.0

Parameters:

serverName (*string*): Server name. The parameter is required.

Response:

type: *struct*

Example:

```
array('total_space' => 0.5,
'space_limit' => 4000,
'homes_space' => 0.0126953125,
'web_space' => 0.1474609375,
'webmail_space' => 0,
'bds_space' => 0.345703125,
'mail_space' => 0,
'ftp_space' => 0,
'others_space' => 0,
)
```

Multihosting_MailReport_SetOff

Description:

Deactivate consumption email report.

Only for multihosting.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **void**

Multihosting_MailReport_Get

Description:

Returns consumption email report status.

Only for multihosting.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

```
array('periodicity' => 'never',
'emailTo' => ",
)
```

Multihosting_MailReport_Set

Description:

Set consumption email report.

Only for multihosting.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

emailTo (**string**): Email destination. The parameter is required. Parameter value must be a valid email address.

periodicity (**string**): Report periodicity. The parameter is required. Accepted parameter values: "daily", "monthly", "yearly".

Response:

type: **void**

Multihosting_GetLicenses

Description:

Returns licenses information.

Only for multihosting.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

```
array('totalLicenses' => 5,
'availableLicenses' => 4,
'usedLicenses' => 1,
)
```

Multihosting_HostingSetup_Update

Description:

Updates an existing user custom hosting setup.

Only for multihosting.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

setupName (**string**): Existing setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

options (**struct**): New setup options (as returned by Multihosting_HostingSetup_Get). The parameter is required.

Response:

type: **void**

Multihosting_HostingSetup_GetAll

Description:

Returns all available hosting setups.

Only for multihosting.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

```
array(array('common' => 'N',
'SetupName' => 'Unlimited',
),array('common' => 'Y',
'SetupName' => 'hosting correo10',
),array('common' => 'Y',
'SetupName' => 'hosting profesional linux',
),array('common' => 'Y',
'SetupName' => 'hosting personal linux',
))
```

Multihosting_HostingSetup_GetOptions

Description:

Returns all available hosting setup options.

Only for multihosting.

Version: 1.0

Parameters:

`serverName` (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

(Example too long, see web.)

Multihosting_HostingSetup_Delete

Description:

Deletes a existing user custom hosting setup.

Only for multihosting.

Version: 1.0

Parameters:

`serverName` (**string**): Server name. The parameter is required.

`setupName` (**string**): Setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

Response:

type: **void**

Multihosting_HostingSetup_Create

Description:

Creates a new user custom hosting setup.

Only for multihosting.

Version: 1.0

Parameters:

`serverName` (**string**): Server name. The parameter is required.

`setupName` (**string**): Setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

`options` (**struct**): Setup options (as returned by `Multihosting_HostingSetup_Get`). The parameter is required.

Response:

type: **void**

Multihosting_HostingSetup_Get

Description:

Returns an user custom hosting setup.

Only for multihosting.

Version: 1.0

Parameters:

`serverName` (**string**): Server name. The parameter is required.

`setupName` (**string**): Setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

Response:

type: **struct**

Example:

(Example too long, see web.)

Multihosting_GetEmailAccountsNumber

Description:

Returns email accounts number and limit.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

```
array('used_email' => 1,
      'assign_email' => -1,
      'email_limit' => 200,
    )
```

Multihosting_GetUsedTransfer

Description:

Returns used transfer ammount.

Only for multihosting.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

```
array('total_traffic' => 4712,
      'traffic_limit' => 90000,
    )
```

Payment commands

Payment_Method_GetAll

Description:

Returns all payment methods.

1.0 -> 1.1: Only returns payment methods for autorenewals. Other payment methods are discarded.

Version: 1.1

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

(Example too long, see web.)

Payment_Credit_GetDetailed

Description:

Returns detailed credit information.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **struct**

Example:

```
array('credit' => 0,
'points' => 0.1,
'refundable' => 0,
'notRefundable' => 0,
'others' => 0,
'affiliated' => 0,
'entered' => 0,
'bonos' => 0,
'devolucion_credit' => 0,
)
```

Payment_Credit_List

Description:

Returns credit modification list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

(Example too long, see web.)

Payment_Credit_GetTotal

Description:

Returns total credit.
Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **float**

Example:

0.1

Services commands

Services_GetHostings

Description:

Returns hosting list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

(Example too long, see web.)

Services_GetManagedDedicatedServers

Description:

Returns managed dedicated servers list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

```
array(array('serverName' => 'd546.dinserver.com',
'startDate' => '2013-06-05',
'endDate' => '2014-06-05',
))
```

Services_GetHousingServers

Description:

Returns housing servers list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

```
array(array('serverName' => 'colo01.dinserver.com',
'startDate' => '2011-07-01',
'endDate' => '2011-08-01',
),array('serverName' => 'colo02.dinserver.com',
'startDate' => '2011-07-01',
'endDate' => '2011-08-01',
))
```

Services_GetDomains

Description:

Returns domain list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

(Example too long, see web.)

Services_GetUnmanagedCloudServers

Description:

Returns unmanaged cloud server list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

'None'

Services_GetManagedVps

Description:

Returns managed VPS list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

```
array(array('serverName' => 'vl193.dinasever.com',
'startDate' => '2012-12-14',
'endDate' => '2013-08-09',
),array('serverName' => 'vw151.dinasever.com',
'startDate' => '2013-03-19',
'endDate' => '2014-03-19',
))
```

Services_GetAllManagedServersNames

Description:

Returns managed server names list (cloud, dedicated, vps, multihosting).

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

'None'

Services_GetDedicatedServers

Description:

Returns dedicated servers list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

```
array(array('serverName' => 'dw27.dinasever.com',
'startDate' => '2011-02-16',
'endDate' => '2012-02-16',
),array('serverName' => 'd331.dinasever.com',
'startDate' => '2011-07-12',
'endDate' => '2011-10-12',
))
```

Services_GetCloudServers

Description:

Returns cloud server list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

```
array(array('cloudAlias' => 'cl364',
'startDate' => '2011-06-10',
'endDate' => '2011-06-10',
))
```

Services_GetVps

Description:

Returns VPS list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

```
array(array('serverName' => 'vl328.dinasever.com',
```

```
'startDate' => '2011-04-19',
'endDate' => '2011-05-19',
))
```

Services_GetDomainTransfers

Description:

Returns the user's domain transfers list. Status information is not immediate; it may take up to 1 hour to change.

On transfer codes: 'WAIT_INIT','WAIT_APROB','WAIT_AUTH','WAIT_TRANSFER'

Error codes: 'KO_AUTH','FAILED','BLOCKED','REJECTED','CANCELED','DELETED','UNKNOWN'

OK codes: 'ACTIVE'

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

'None'

Services_GetSms

Description:

Returns Sms list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

```
array(array('account' => 650074563,
```

```
'startDate' => '2009-07-17',
```

```
'endDate' => '2013-09-17',
```

```
))
```

Services_GetMultihostings

Description:

Returns Multihostings list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

(Example too long, see web.)

Services_GetUnmanagedDedicatedServers

Description:

Returns unmanaged dedicated servers list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

```
array(array('serverName' => 'dl446.dinasever.com',  
'startDate' => '2013-04-05',  
'endDate' => '2013-07-05',  
))
```

Services_GetManagedCloudServers

Description:

Returns managed cloud server list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

```
array(array('cloudAlias' => 'c568',  
'startDate' => '2014-02-06',  
'endDate' => '2014-02-06',  
))
```

Services_GetUnmanagedVps

Description:

Returns unmanaged VPS list.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

(Example too long, see web.)

Sms commands

Sms_Programmed_Cancel

Description:

Cancel programmed SMS.

Please note that this only works with SMS that has not yet been sent.

Version: 1.0

Parameters:

account (string): Sms account number. The parameter is required.

id (int): History ID. The parameter is required.

Response:

type: void

Sms_GetCredit

Description:

Returns available SMS credit.

Version: 1.0

Parameters:

account (string): Sms account number. The parameter is required.

Response:

type: string

Example:

0.000000

Sms_PanelIndependentAccess_SetPassword

Description:

Set a new password for SMS account panel independent access.

Version: 1.1

Parameters:

account (string): Sms account number. The parameter is required.

newPassword (string): New password. The parameter is required.

Response:

type: void

Sms_SetUp

Description:

Sets a sms account up.

Version: 1.0

Parameters:

account (*string*): Account number. The parameter is required.

alias (*string*): Account alias. The parameter is optional. Parameter length must be between 0 and 100 characters.

sender (*string*): Default sender. The parameter is optional. Parameter length must be between 0 and 11 characters.

Response:

type: *string*

Example:

'None'

Sms_History_GetProgrammed

Description:

Returns a delivery list.

Version: 1.0

Parameters:

account (*string*): Sms account number. The parameter is required.

start (*int*): Start. The parameter is required. Parameter value must be a valid integer.

end (*int*): End. The parameter is required. Parameter value must be a valid integer.

Response:

type: *array*

Example:

'None'

Sms_History_GetBulkSent

Description:

Returns a delivery list.

Version: 1.0

Parameters:

account (*string*): Sms account number. The parameter is required.

start (*int*): Start. The parameter is required. Parameter value must be a valid integer.

end (*int*): End. The parameter is required. Parameter value must be a valid integer.

Response:

type: *array*

Example:

'None'

Sms_History_GetSent

Description:

Returns a delivery list.

Version: 1.0

Parameters:

account (*string*): Sms account number. The parameter is required.

start (*int*): Start. First SMS to obtain, starting at 0. The parameter is required. Parameter value must be a

valid integer.

end (**int**): End. Last SMS to obtain. The parameter is required. Parameter value must be a valid integer.

Response:

type: **array**

Example:

'None'

Sms_Send_Bulk_Limited_Gsm7

Description:

Sends one SMS to one or many destination numbers.

This command accepts GSM7 valid UTF-8 encoded characters only.

Limited to one SMS for destination number.

Valid charlist: @ £ \$ ¥ è é ù ì ò Ç Ø ø Å å ? _ ? ? ? ? ? ? ? ? ^ { } \ [~] | Æ æ ß É ! " # ¨ % ' () + , - . / : ;
 ? ; A B C D E F G H I J K L M N O P Q R S T U V W X Y Z Ä Ö Ñ Ü § ¿ a b c d e f g h i j k l m n o p q r s t
 u v w x y z ä ö ñ ü à 0 1 2 3 4 5 6 7 8 9

Valid special chars: whitespace, carriage return and line feed.

Version: 1.0

Parameters:

account (**string**): Sms account number. The parameter is required.

contents (**string**): Text message. Limited to a 7bit charlist. The parameter is required. Parameter length must be between 1 and 160 characters. Parameter value must contain GSM7 valid chars only.

to (**array**): Destination numbers. The parameter is required.

from (**string**): Sender name. The parameter is required. Parameter length must be between 1 and 11 characters.

when (**string**): Date and time, for programmed sending. Set empty for send now. Year-month-day Hour:minute:second. The parameter is optional. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

Response:

type: **void**

Sms_Send_Bulk_Limited_Unicode

Description:

Sends one SMS to one or many destination numbers.

This command accepts any UTF-8 encoded character.

Limited to one SMS for destination number.

Version: 1.0

Parameters:

account (**string**): Sms account number. The parameter is required.

contents (**string**): Text message. It may contain any UTF-8 character. The parameter is required. Parameter length must be between 1 and 70 characters.

to (**array**): Destination numbers. The parameter is required.

from (**string**): Sender name. The parameter is required. Parameter length must be between 1 and 11 characters.

when (**string**): Date and time, for programmed sending. Set empty for send now. Year-month-day Hour:minute:second. The parameter is optional. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

Response:

type: **void**

Sms_Send_Bulk_Long_Gsm7

Description:

Sends SMS to one or many destination numbers.

This command accepts GSM7 valid UTF-8 encoded characters only.

Please note the SMS may be divided on many smaller SMS (more credit is consumed).

Valid charlist: @ £ \$ ¥ è é ù ì ò Ç Ø ø Å å ? _ ? ? ? ? ? ? ? ? ^ { } \ [~] | Æ æ ß É ! " # ¨ % ' () + , - . / : ;
 ? ; A B C D E F G H I J K L M N O P Q R S T U V W X Y Z Ä Ö Ñ Ü § ¿ a b c d e f g h i j k l m n o p q r s t
 u v w x y z ä ö ñ ü à

Valid special chars: whitespace, carriage return and line feed.

Version: 1.0

Parameters:

account (string): Sms account number. The parameter is required.

contents (string): Text message. Limited to a 7bit charlist. The parameter is required. Parameter length must be between 1 and 765 characters. Parameter value must contain GSM7 valid chars only.

to (array): Destination numbers. The parameter is required.

from (string): Sender name. The parameter is required. Parameter length must be between 1 and 11 characters.

when (string): Date and time, for programmed sending. Set empty for send now. Year-month-day Hour:minute:second. The parameter is optional. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

Response:

type: void

Sms_Send_Bulk_Long_Unicode

Description:

Sends SMS to one or many destination numbers.

This command accepts any UTF-8 encoded character.

Please note the SMS may be divided on many smaller SMS (more credit is consumed).

Version: 1.0

Parameters:

account (string): Sms account number. The parameter is required.

contents (string): Text message. It may contain any UTF-8 character. The parameter is required. Parameter length must be between 1 and 335 characters.

to (array): Destination numbers. The parameter is required.

from (string): Sender name. The parameter is required. Parameter length must be between 1 and 11 characters.

when (string): Date and time, for programmed sending. Set empty for send now. Year-month-day Hour:minute:second. The parameter is optional. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

Response:

type: void

Sms_GetSender

Description:

Returns sender name (used for "from" field).

Version: 1.0

Parameters:

account (**string**): Sms account number. The parameter is required.

Response:

type: **string**

Example:

'Pruebas'

Sms_Phonebook_GetAllContacts

Description:

Returns phonebook contact list.

1.0 -> 1.1: Added missing id key on response.

Version: 1.1

Parameters:

account (**string**): Sms account number. The parameter is required.

Response:

type: **struct**

Example:

```
array("229" => array('name' => 'Soporte',
'number' => 900854000,
'id' => 229,
),
)
```

Sms_Phonebook_DeleteContact

Description:

Delete an existing phonebook contact.

Version: 1.0

Parameters:

account (**string**): Sms account number. The parameter is required.

id (**int**): Contact id. The parameter is required. Parameter value must be a valid integer.

Response:

type: **void**

Sms_Phonebook_CreateContact

Description:

Create a new phonebook contact.

Version: 1.0

Parameters:

account (**string**): Sms account number. The parameter is required.

name (**string**): Contact name. The parameter is required. Parameter length must be between 1 and 50 characters.

phoneNumber (**string**): Contact phone number. The parameter is required. Parameter value must be a valid phone number.

Response:

 type: **void**

Sms_Phonebook_UpdateContact

Description:

Update an existing phonebook contact.

Version: 1.0

Parameters:
account (**string**): Sms account number. The parameter is required.

id (**int**): Contact id. The parameter is required. Parameter value must be a valid integer.

name (**string**): Contact name. The parameter is required. Parameter length must be between 1 and 50 characters.

phoneNumber (**string**): Contact phone number. The parameter is required. Parameter value must be a valid phone number.

Response:

 type: **void**

Sms_DeliveryList_Update

Description:

Update an existing delivery list (overwrites previous ids).

Version: 1.0

Parameters:
account (**string**): Sms account number. The parameter is required.

name (**string**): Delivery list name. The parameter is required. Parameter length must be between 1 and 20 characters.

ids (**array**): New phonebook ids (array). The parameter is required.

Response:

 type: **void**

Sms_DeliveryList_GetAll

Description:

Return all delivery lists.

Version: 1.0

Parameters:
account (**string**): Sms account number. The parameter is required.

Response:

 type: **array**

Example:

```
array('name' => 'sfgjshgef',
'members' => array(),
)
```

Sms_DeliveryList_Delete

Description:

Delete an existing delivery list.

Version: 1.0

Parameters:

account (*string*): Sms account number. The parameter is required.

name (*string*): Delivery list name. The parameter is required. Parameter length must be between 1 and 20 characters.

Response:

type: *void*

Sms_DeliveryList_Create

Description:

Create a new delivery list.

Version: 1.0

Parameters:

account (*string*): Sms account number. The parameter is required.

name (*string*): Delivery list name. The parameter is required. Parameter length must be between 1 and 20 characters.

ids (*array*): Phonebook ids (array). The parameter is required.

Response:

type: *void*

Sms_DeliveryList_Get

Description:

Returns a delivery list.

Version: 1.0

Parameters:

account (*string*): Sms account number. The parameter is required.

name (*string*): Delivery list name. The parameter is required. Parameter length must be between 1 and 20 characters.

Response:

type: *struct*

Example:

```
array('members' => array(),
)
```

Sms_DeliveryList_GetPhones

Description:

Returns a delivery list.

Version: 1.0

Parameters:

account (**string**): Sms account number. The parameter is required.

name (**string**): Delivery list name. The parameter is required. Parameter length must be between 1 and 20 characters.

Response:

type: **array**

Example:

`array(743214323)`

System commands

System_GetResponseTypes

Description:

Returns valid Response Types.

Default response type can be changed with parameter "responseType=xxx".

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: `struct`

System_GetRequestTypes

Description:

Returns valid Request Types.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: `struct`

System_MethodHelp

Description:

Returns command documentation.

Version: 1.0

Parameters:

`commandName` (`string`): Command name. The parameter is required.

Response:

type: `string`

System_MethodSignature

Description:

Returns the method signature.

Warning: This command is intended for automatic XmlRpc client use with XmlRpc requests only .

Version: 1.0

Parameters:

`commandName` (`string`): Command name. The parameter is required.

Response:

type: `array`

System_TestSimulation

Description:

Test if request is on simulation mode.
Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **bool**

System_ListMethods

Description:

Lists command names.
Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

(Example too long, see web.)

System_GetApiVersion

Description:

Returns Api version information.
Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **struct**

Example:

(Example too long, see web.)

User commands

User_GetInfo

Description:

Returns all secondary users.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **struct**

Example:

(Example too long, see web.)

User_Data_GetValidLegalForms

Description:

Returns all valid legal form IDs and descriptions.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

(Example too long, see web.)

User_GetServices

Description:

Returns a list of services.

Version: 1.1

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

(Example too long, see web.)

User_GetNotifications

Description:

Returns user notifications.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

 type: **struct**

Example:

'None'

User_GetInvoicedAmount

Description:

Returns invoiced amount.

Version: 1.0

Parameters:

startDate (**string**): Starting date and time. Example: 2011-01-31 00:00:00. The parameter is optional. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

endDate (**string**): Ending date and time. Example: 2011-12-31 23:59:59. The parameter is optional. Parameter value must be a valid full date: year-month-day hour:minutes:seconds .

Response:

 type: **float**

Example:

9355.02

User_GetLastLoginDate

Description:

Returns user last login date time.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

 type: **string**

Example:

'2011-05-03 13:22:05'

User_Secondary_Update

Description:

Update an existing secondary user.

1.0 -> 1.1 loginData is now flagged as a needed parameter.

Version: 1.1

Parameters:

idSecondaryUser (**int**): Existing secondary user ID. The parameter is required. Parameter value must be a valid integer.

personalData (**struct**): Secondary user personal identification data. The parameter is required. Parameter value must be a struct containing user information: firstname, lastname, NIF

companyData (**struct**): Secondary user company identification data. The parameter is optional. Parameter value must be a struct containing user information: company, legal_form, CIF, company_phone, company_fax

contactData (**struct**): Secondary user contact information. The parameter is required. Parameter value must be a struct containing user information: country_code, state, city, postal_code, address, phone, fax, email_address

loginData (**struct**): Secondary user login data. The parameter is required. Parameter value must be a struct containing user information: login, password

Response:

type: **string**

Example:

'None'

User_Secondary_GetAll

Description:

Returns all secondary users.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:

type: **array**

Example:

(Example too long, see web.)

User_Secondary_Delete

Description:

Delete a secondary user.

Version: 1.0

Parameters:

userId (**int**): Secondary user ID. The parameter is required. Parameter value must be a valid integer.

Response:

type: **string**

Example:

'None'

User_Secondary_Create

Description:

Create a secondary user.

1.0 -> 1.1 loginData is now flagged as a needed parameter.

Version: 1.1

Parameters:

personalData (**struct**): Secondary user personal identification data. The parameter is required. Parameter value must be a struct containing user information: firstname, lastname, NIF

companyData (**struct**): Secondary user company identification data. The parameter is optional. Parameter value must be a struct containing user information: company, legal_form, CIF, company_phone, company_fax

contactData (**struct**): Secondary user contact information. The parameter is required. Parameter value must be a struct containing user information: country_code, state, city, postal_code, address, phone, fax, email_address

loginData (**struct**): Secondary user login data. The parameter is required. Parameter value must be a struct containing user information: login, password

Response:type: **string**

Example:

'None'

User_Default_GetAdminContact

Description:

Returns user default admin contact data.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:type: **struct**

Example:

'None'

User_Default_GetDnss

Description:

Returns user default DNS.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:type: **array**

Example:

array('ns.dinahosting.com','ns2.dinahosting.com','ns3.dinahosting.com','ns4.dinahosting.com')

User_Default_GetTechContact

Description:

Returns user default tech contact data.

Version: 1.0

Parameters:

This command doesn't accept any parameters

Response:type: **struct**

Example:

'None'

Vps commands

Vps_Hosting_Activate

Description:

Activates an existing but inactive hosting.

Only for managed virtual servers.

Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

domainName (string): Hosting domain name. The parameter is required.

Response:

type: void

Vps_Hosting_GetAll

Description:

Returns existing hostings on Vps.

Only for managed virtual servers.

Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

onlyActiveHostings (bool): True to add filter: return only active hostings. False or empty, execute without filter. The parameter is optional. Parameter value must be a boolean (true or false).

Response:

type: array

Example:

```
array('xen.delira.eu','java.delira.eu','soportedinahosting.com','dominiopersonal.com','nophp.com','probaformacion.soportedinahosting.com','pruebapersonal.com','correodeprueba.com')
```

Vps_Hosting_Delete

Description:

Deletes an existing hosting.

Only for managed virtual servers.

Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

domainName (string): Hosting domain name. The parameter is required.

Response:

type: void

Vps_Hosting_Deactivate

Description:

Deactivates an existing and active hosting.
 Only for managed virtual servers.
 Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.
domainName (**string**): Hosting domain name. The parameter is required.

Response:

type: **void**

Vps_Hosting_GetSetupName

Description:

Returns hosting setup name.
 Only for managed vps servers.
 Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.
domainName (**string**): Hosting domain name. The parameter is required.

Response:

type: **string**
 Example:
 'None'

Vps_Hosting_Create

Description:

Creates a new hosting.
 Only for managed virtual servers.
 1.0 -> 1.1: Added an existing setup name validation.
 Version: 1.1

Parameters:

serverName (**string**): Server name. The parameter is required.
domainName (**string**): Hosting domain name. The parameter is required.
setupName (**string**): Existing setup name. The parameter is required. Parameter length must be between 1 and 30 characters.
setZones (**bool**): True to set new zones, false to leave them unchanged. Default: true. The parameter is required. Parameter value must be a boolean (true or false).

Response:

type: **void**

Vps_Hosting_ChangeSetup

Description:

Changes setup of a existing hosting.
 Only for managed virtual servers.
 Version: 1.0

Parameters:

serverName ([string](#)): Server name. The parameter is required.

domainName ([string](#)): Hosting domain name. The parameter is required.

setupName ([string](#)): Existing setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

Response:

type: [void](#)

Vps_GetDataTransferInfo

Description:

Returns data transfer summary.

Version: 1.0

Parameters:

serverName ([string](#)): Server name. The parameter is required.

Response:

type: [struct](#)

Example:

(Example too long, see web.)

Vps_GetMonitorizedPorts

Description:

Returns monitorized ports with their status.

Only for unmanaged virtual servers.

Version: 1.0

Parameters:

serverName ([string](#)): Server name. The parameter is required.

Response:

type: [array](#)

Example:

(Example too long, see web.)

Vps_GetUsedSpace

Description:

Returns used space.

Only for managed virtual servers.

Version: 1.0

Parameters:

serverName ([string](#)): Server name. The parameter is required.

Response:

type: [struct](#)

Example:

```
array('total_space' => 71,
'space_limit' => 10240,
'homes_space' => 0.1240234375,
'web_space' => 66.9951171875,
'webmail_space' => 0,
'bds_space' => 3.171875,
'mail_space' => 0.396484375,
'ftp_space' => 0.0078125,
'others_space' => 0,
)
```

Vps_Monitorization_Activate

Description:

Activate monitorization.

Only for non-managed virtual servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

emails (**array**): Array of emails. The parameter is required.

Response:

type: **void**

Vps_Monitorization_Deactivate

Description:

Deactivate monitorization.

Only for non-managed virtual servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **void**

Vps_Monitorization_Get

Description:

Returns monitorization configuration.

Only for non-managed virtual servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

```
array('emails' => array('ejemplo@example.com'),
'activated' => true,
```

)

Vps_GetAllHostingsFullReport

Description:

Returns a summary of the space, transfer data and plan per hosting.

Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: **struct**

Example:

'None'

Vps_MailReport_SetOff

Description:

Deactivate consumption email report.

Only for managed virtual servers.

Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: **void**

Vps_MailReport_Get

Description:

Returns consumption email report status.

Only for managed virtual servers.

Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: **struct**

Example:

array('periodicidad' => 'nunca',

'direccionDeDestino' => "",

)

Vps_MailReport_Set

Description:

Set consumption email report.

Only for managed virtual servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

emailTo (**string**): Destination emails separated with commas. The parameter is required. Parameter value must be a valid email address.

periodicity (**string**): Report periodicity. The parameter is required. Accepted parameter values: "daily", "weekly", "monthly".

Response:

type: **void**

Vps_Services_GetAll

Description:

Returns services status.

Only for managed virtual servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

```
array('smtp' => 'started',
'streaming' => 'deactivated',
'web' => 'started',
'mysql' => 'started',
'ftp' => 'started',
'pop3' => 'started',
'dinascanner' => 'started',
)
```

Vps_Services_ChangeStatus

Description:

Change server service status.

Only for managed virtual servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

serviceName (**string**): Service name. The parameter is required. Accepted parameter values: "web", "mysql", "pop3", "smtp", "ftp", "dinascanner".

serviceAction (**string**): Action over service. The parameter is required. Accepted parameter values: "start", "stop", "activate", "deactivate", "restart".

Response:

type: **void**

Vps_GetLicenses

Description:

Returns licenses information.
 Only for managed virtual servers.
 Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

```
array('totalLicenses' => 25,
'usedLicenses' => 8,
)
```

Vps_GetBandwidthConsumption

Description:

Returns bandwidth consumption summary.
 Only for non-managed virtual servers.
 Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

month (**int**): Month number. The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 1 and 12 inclusive.

year (**int**): Year. The parameter is required. Parameter value must be a valid integer. Parameter value must be between values 2002 and 2013 inclusive.

Response:

type: **struct**

Example:

(Example too long, see web.)

Vps_GetServerInfo

Description:

Returns VPS server info.
 Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

```
array('name' => 'vl328.dinserver.com',
'main_ip' => '82.98.167.9',
'ips' => array(),
)
```

Vps_HostingSetup_Update

Description:

Updates an existing user custom hosting setup.
 Only for managed virtual servers.
 Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

setupName (**string**): Existing setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

options (**struct**): New setup options (as returned by Vps_HostingSetup_Get). The parameter is required.

Response:

type: **void**

Vps_HostingSetup_GetAll

Description:

Returns all available hosting setups.
 Only for managed virtual servers.
 Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

(Example too long, see web.)

Vps_HostingSetup_GetOptions

Description:

Returns all available hosting setup options.
 Only for managed virtual servers.
 Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

(Example too long, see web.)

Vps_HostingSetup_Delete

Description:

Deletes a existing user custom hosting setup.
 Only for managed virtual servers.
 Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

setupName (**string**): Setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

Response:

type: **void**

Vps_HostingSetup_Create

Description:

Creates a new user custom hosting setup.

Only for managed virtual servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

setupName (**string**): Setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

options (**struct**): Setup options (as returned by Vps_HostingSetup_Get). The parameter is required.

Response:

type: **void**

Vps_HostingSetup_Get

Description:

Returns an user custom hosting setup.

Only for managed virtual servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

setupName (**string**): Setup name. The parameter is required. Parameter length must be between 1 and 30 characters.

Response:

type: **struct**

Example:

(Example too long, see web.)

Vps_Control_GetApacheProcesses

Description:

Returns apache active processes information.

Only for linux managed virtual servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **array**

Example:

(Example too long, see web.)

Vps_Control_GetSystemLoad

Description:

Returns cpu load by hosting information.
Only for managed virtual servers.
Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

(Example too long, see web.)

Vps_Control_GetSystemStatus

Description:

Returns sysyem information.
Only for managed virtual servers.
Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

(Example too long, see web.)

Vps_Control_KillMysqlProcess

Description:

Kill mysql active processes.
Only for managed virtual servers.
Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

pid (**int**): Process id. The parameter is required. Parameter value must be a valid integer.

Response:

type: **void**

Vps_Control_GetMysqlProcesses

Description:

Returns mysql active processes information.
Only for managed virtual servers.
Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: array

Example:

```
array(array('info' => 'show',
'id' => 4614,
'host' => 'gdc.dinasever.com:59830',
'ddbb' => 'NULL',
'user' => 'root',
'command' => 'Query',
'time' => 'NULL',
'status' => 'NULL',
))
```

Vps_Control_GetCpuLoadByHosting

Description:

Returns cpu load by hosting information.

Only for managed virtual servers.

Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: array

Example:

```
array(array('hosting' => 'vl328.dinasever.com',
'used_cpu' => 0.04,
'percent_used_cpu' => 100,
),array('hosting' => 'others',
'used_cpu' => 0,
'percent_used_cpu' => 0,
))
```

Vps_Nfs_Get

Description:

Returns NFS server name

Version: 1.0

Parameters:

serverName (string): Server name The parameter is required.

Response:

type: struct

Example:

'None'

Vps_GetSpaceAndTransferReportPerHosting

Description:

Returns a summary of the space and transfer data per hosting.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **struct**

Example:

'None'

Vps_PowerStatus_Reactivate

Description:

Reactivate suspended server.

Only for non-managed virtual servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **void**

Vps_PowerStatus_TurnOn

Description:

Turn on server.

Only for non-managed virtual servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **void**

Vps_PowerStatus_ElectricRestart

Description:

Electric restart of server.

Only for non-managed virtual servers.

Version: 1.0

Parameters:

serverName (**string**): Server name. The parameter is required.

Response:

type: **void**

Vps_PowerStatus_Pause

Description:

Pause server.
Only for non-managed virtual servers.
Version: 1.0

Parameters:

`serverName` (`string`): Server name. The parameter is required.

Response:

type: `void`

Vps_PowerStatus_Get

Description:

Get server status.
Only for non-managed virtual servers.
Version: 1.0

Parameters:

`serverName` (`string`): Server name. The parameter is required.

Response:

type: `string`

Example:

`'Idle'`

Vps_PowerStatus_Suspend

Description:

Suspend server.
Only for non-managed virtual servers.
Version: 1.0

Parameters:

`serverName` (`string`): Server name. The parameter is required.

Response:

type: `void`

Vps_PowerStatus_TurnOff

Description:

Turn off server.
Only for non-managed virtual servers.
Version: 1.0

Parameters:

`serverName` (`string`): Server name. The parameter is required.

Response:

type: `void`

Vps_PowerStatus_Unpause

Description:

Unpause paused server.
Only for non-managed virtual servers.
Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: void

Vps_PowerStatus_Restart

Description:

Soft restart server.
Only for non-managed virtual servers.
Version: 1.0

Parameters:

serverName (string): Server name. The parameter is required.

Response:

type: void